



UL iQ for Surge Protective Devices



Surge Protective Devices

E314042

Guide Information

Schneider Electric USA, Inc.

Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

Model(s): SDSA1175\$

Permanently Connected

<u>SPD</u> <u>Type</u>	<u>Volts</u> <u>(V)</u>	<u>AC/DC</u> <u>DC PV</u>	<u>Phase</u>	<u>Amps</u> <u>(A)</u>	<u>Ambient</u> <u>Min(°C)</u>	<u>Ambient</u> <u>Max(°C)</u>	<u>Mode</u>	<u>VPR</u> <u>(Vpk)</u>	<u>MCOV</u> <u>(V)</u>	<u>In</u> <u>(kA)</u>	<u>SCCR</u> <u>(kA)</u>
1	240/120	AC	1S	n/a	-35	85	L-L L-N	1200 700	300 150	10	25

Evaluated to: UL 1449 4th Ed. Rev: 2018-08-01 and CSA C22.2 No. 269.1-14, 2014-11

\$ - May be followed by additional suffixes.

Note - All models may be followed by additional suffixes.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2009-03-10

Last Revised: 2019-01-25

© 2019 UL LLC

