



FULL TROWEL WOOD FILLER

DESCRIPTION AND USES

Pro Finisher Full Trowel Wood Filler is a latex based wood filler designed to fill small cracks, nail holes, gouges, broken edges and open wood grain prior to finishing oak hardwood floors. Formulated to be full bodied but thin enough for easy full trowel applications.

Full Trowel Wood Filler is recommended for use on commercial and residential bare oak hardwood floors. Full Trowel Wood Filler is formulated to match background grain color of red oak and white oak flooring.

FEATURES

- Safe, non-flammable water base formula
- Pre-shaded for red oak & white oak
- Dries in 15 minutes
- Ready to sand in 30 to 60 minutes
- Sands easily with final drum sanding
- Accepts stains

PRODUCTS

SKU	Description
138913	1-Gallon Red Oak
138914	1-Quart Red Oak
138924	1-Quart White Oak

PRODUCT APPLICATION

SURFACE PREPARATION

Surface must be clean, dry, and free from old finish, wax, grease and dust.

Sand Floor: For best results, follow NWFA (National Wood Flooring Association) accepted method or see Pro Finisher Professional Techniques for sanding details. Remove all sanding dust with a vacuum and wipe clean with a lint-free cloth. Pro Finisher Wood Filler should be used prior to final sanding.

WARNING! SANDING DUST CAN BE A SPONTANEOUS COMBUSTION HAZARD. ALWAYS DISPOSE OF COLLECTED SANDING DUST IMMEDIATELY.

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

WARNING! If you scrape sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLY FILLER

Select wood filler to match floor species. Be sure to remove all dust, dirt, oil and wax from floor surface before applying Pro Finisher wood filler. Pour a workable puddle of wood filler on the floor. With a smooth edge finishing trowel, work filler back and forth across the floor, being sure to have a good angle and downward pressure on trowel. Just pushing filler across the floor is not adequate. The filler must be worked down into the cracks to ensure they are filled from bottom to top. Spot fill larger cracks and holes with multiple layers.

FINAL SAND

Allow to dry thoroughly before final sanding. When complete there should be a haze or film left on the surface of the wood. Depending on the humidity, temperature and air movement, the filler should dry in approximately 30 minutes. Large filled areas will require additional dry time. When dry and all filled areas are level with the surface of the wood, sand the floor to remove filler from the surface of the wood. Remove all sanding dust and wipe clean with a lint-free cloth.

CLEAN UP

Clean up application tools and equipment with soap and water.

STORAGE

Store the container in dry and cool environment. Keep container sealed when not in use.

**TECHNICAL DATA****FULL TROWEL WOOD FILLER****PHYSICAL PROPERTIES**

		FULL TROWEL WOOD FILLER
Resin		Acrylic
Pigment Type		Limestone, Talc
Solvents		Propylene Glycol, Water
Weight	Per Gallon	14.0 lbs.
	Per Liter	1.68 kg
Solids	By Weight	71.2%
	By Volume	51.4 %
Volatile Organic Compounds		< 4 g/l (< 0.04 lbs. /gal.)
Practical Coverage		Varies with porosity of wood and application method
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Sand	30-60 minutes
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-889
Rev.: 121516