



Wear

This carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, this carpet offers strength from face fiber to secondary backing.



Backing Performance

Carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



This product has passed the standard test method for critical radiant flux of floor-covering systems using a radiant heat energy source and meets the standards as defined within ASTM E648.



Lifetime Warranty

- Commercial Wear
- Backing Performance



02 | Brownstone



04 | Iced Tea



01 | Basket Weave



07 | Pinstripe



03 | Chic Sable



08 | Casting Shadows



05 | Black Walnut



specifications

•		
Fiber system	100% BCF Solution dyed nylon	
Construction	Pattern scroll loop	
Backing system	EuroBac™ Plus Modular	
Pile weight	18 oz./y ²	600 g/m ²
Pile height	0.08"/0.15"/0.2"	2 mm/3.8 mm/5 mm
Gauge	1/12	47.2 rows/10 cm
Stitches	9.4 s.p.i.	37 stitches/10 cm
Density	5400	9.4 kilotex/cm ²
CRI/CCI air quality test	Green Label Plus	GLP 2116
Environmental awareness	Eligible for any recycling program	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	Radiant Panel ASTM E648 – Class I (direct glue)	
	DOC FF 1-70 - passes	
	ASTM E662 - < 450 (flaming mode)	
Colorfastness to light	5.0 (AATCC 16)	
Modular size (w x I)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton	6 y ² /carton
	52.8 lbs/carton	32 cartons/pallet
Recommended adhesive	High quality pressure sensitive adhesive	
Installation method	Monolithic, Quarter-Turn, Ashlar and Brick	
Lifetime Warranties	Commercial Wear	
(See full text for details)	Backing Performanc	e
The natural characteristics of geometric or linear patterns in carpet tile con		

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colors may vary due to print processes and monitor display settings.

E&OE.

1607