

### Safety Data Sheets (SDSs)

Client	Wuhan Lixing (Torch) Power Sources Co., Ltd.
Add. of Client	The Guandong Industrialized Country of East Lake High and New Technology Development Zone, Wuhan
Description	Lithium Manganese Dioxide Battery
Model /Type	CR123A
Manufacturer	Wuhan Lixing (Torch) Power Sources Co., Ltd.
Add. of Manufacturer	The Guandong Industrialized Country Of East Lake High and New Technology Development Zone, Wuhan
Nominal Voltage	3.0V, 1500mAh
Date of Receipt	2017-02-24

Laboratory	Guangzhou CP-UP Certification Technology Service Co., Ltd.
Address	No 2 Guangxing Hongmian Road, jingkeng Industrial Park, Nancun Town, Panyu District, Guangzhou City, China

Approved Signatory	justin Zhang
--------------------	--------------



Inspected by	Arvin Shang
--------------	-------------



Censored by	Candy Wu
-------------	----------



## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product Identifier

Product name: Lithium Manganese Dioxide Battery

Model: CR123A

### Other means of identification

Synonyms:none

### Recommended use of the chemical and restrictions on use

Recommended Use:Used in portabl electronic equipments;

Uses advised against:

- a) Do not dismantle, open or shred batteries.
- b) Do not expose batteries to heat or fire. Avoid storage in direct sunlight.
- c) Do not short-circuit battery. Do not store batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- d) Do not remove a battery from its original packaging until required for use.
- e) Do not subject batteries to mechanical shock.
- f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- g) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- h) Do not use any cell or battery which is not designed for use with the equipment.
- i) Do not mix cells of different manufacture, capacity, size or type within a device.
- j) Battery usage by children should be supervised.
- k) Seek medical advice immediately if a cell or a battery has been swallowed.
- l) Always purchase the battery recommended by the device manufacturer for the equipment.
- m) Keep cells and batteries clean and dry.
- n) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.
- o) Use only the cell or battery in the application for which it was intended.
- p) When possible, remove the battery from the equipment when not in use.
- q) Dispose of properly.

### Details of the supplier of the safety data sheet:

Supplier Name: Wuhan Lixing (Torch) Power Sources Co., Ltd.

Address: The Guandong Industrialized Country of East Lake High And New Technology Development Zone ,  
Wuhan

Telephone number of the supplier: 0086-027- 87561046

Fax: 0086-027-87561046

Postcode: 430074

E-mail address: 1qc@lisun.com

### Emergency telephone number

**Company Emergency Phone Number: 0086-027-87561046**

## 2. HAZARDS IDENTIFICATION

### Classification

No harm at the normal use. If contact the Electrolyte in the Lithium manganese dioxide cylindrical cell, reference as follows:

### Classification of the substance or mixture

Classification according to GHS

Acute Toxicity, Oral(Hazard category 4)

Acute Toxicity, inhalation(Hazard category 4)

Serious eye damage/eye irritation (Hazard category 2A)

### GHS Label elements, including precautionary statements:



GHS07

**Signal word: Warning**

**Hazard statement(s):**

**H319:**Causes serious eye irritation;

**H332:**Harmful if inhaled;

**H302:**Harmful if swallowed;

**precautionary statements:**

**Prevention:**

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

**Response:**

P312:Call a Poison center or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists:Get medical advice/attention.

P304+P340 IF INHALED:Remove person to fresh air and keep comfortable for breathing.

P301+P312:IF SWALLOWED:Call a Poison center or doctor/physician if you feel unwell.

P330 Rinse mouth.

**Storage:**

None

**Disposal**

**P501:** Dispose of contents/container in accordance with local/national regulations

**Hazards not otherwise classified (HNOC)**

Not Applicable

**Other information**

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical characterization: Mixtures**

**Description:**

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number	EC No.
Lithium(Li)	3.6	7439-93-2	231-102-5
Manganese dioxide(MnO <sub>2</sub> )	31.0	1313-13-9	215-202-6
Graphite (C)	4.6	7782-42-5	231-955-3
Lithium Perchlorate	1.0	7791-03-9	232-237-2
Ethylene Glycol dimethylether(LiClO <sub>4</sub> )	7.0	110-71-4	203-794-9
Propylene carbonate(C <sub>4</sub> H <sub>10</sub> O <sub>2</sub> )	8.0	108-32-7	203-572-1
Box-hat(Fe)	33.8	7439-89-6	231-096-4
Chromium(Cr)	8.0	7440-47-3	231-157-5
Molybdenum(Mo)	1.2	7439-98-7	210-478-4
Polypropylene((C <sub>3</sub> H <sub>6</sub> ) <sub>n</sub> )	0.5	9003-07-0	---
PVDF(-[CH <sub>2</sub> -CF <sub>2</sub> -] <sub>n</sub> )	0.8	24937-79-9	----
PTFE(C <sub>2</sub> F <sub>4</sub> ) <sub>n</sub>	0.5	9002-84-0	204-126-9

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

### 4. FIRST-AID MEASURES

**First aid measures**

**Eye Contact** Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

**Skin Contact** Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

**Swallowing** Do not induce vomiting. Get medical attention.

**Most Important Symptoms/Effects** No information available.

**Indication of any immediate medical attention and special treatment needed**

Notes to Physician Treat symptomatically

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical powder, water spray.

Unsuitable Extinguishing Media: No information available.

### Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

### Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

### Special hazards arising from the substance or mixture:

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

### Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

### Conditions for safe storage, including any incompatibilities

If the Lithium manganese dioxide cylindrical cell is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Lithium manganese dioxide cylindrical cell periodically.

3 months: -10°C~+40°C, 45 to 85%RH

And recommended at 0°C~+35°C for long period storage.

Do not storage Lithium manganese dioxide cylindrical cell haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Lithium manganese dioxide cylindrical cell to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

**Incompatible Products** None known.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Control parameters

CAS Number	ACGIH	NIOSH	OSHA
7782-42-5	TLV-TWA 2mg/m <sup>3</sup>	RELs-TWA2.5mg/m <sup>3</sup>	PELs-TWA 15mppcf
1333-86-4	TLV-TWA 3mg/m <sup>3</sup>	RELs-TWA3.5mg/m <sup>3</sup>	PELs-TWA 3.5mg/m <sup>3</sup>
1313-13-9	PELs-TWA 0.1mg/m <sup>3</sup> PELs-TWA 0.02mg/m <sup>3</sup>	N/A	N/A

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

### Appropriate engineering controls

**Engineering Measures** Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection:**



**Tightly sealed goggles**

**Body protection:**

Protective work clothing.

**Skin protection:**



**Protective gloves**

**Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material:**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Form: button
	Color: silver
	Odour: Odourless
	Odor Threshold: No information available
Change in condition:	
pH, with indication of the concentration	Not determined.
Melting point/freezing point	Not determined.
Initial boiling point and Boiling range:	Not determined.
Flash Point	Not determined.
Evaporation rate	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapor Pressure:	Not determined.
Vapor Density:	Not determined.

relative density:	Not determined.
Solubility in Water:	Not determined.
Solubility in other solvents	Not determined.
n-octanol/water partition coefficient	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Odour threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	:
Voltage	3.0V
Electric capacity	1500mAh
Lithium content	16.8g

## 10. STABILITY AND REACTIVITY

**Reactivity:** Stable under recommended storage and handling conditions (see section 7, Handling and storage).

**Chemical stability:** Stable under normal conditions of use, storage and transport.

**Thermal decomposition/conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of Hazardous Reactions:** None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

**Conditions to avoid:** Strong heating, fire, Incompatible materials.

**Incompatible materials:** Strong oxidizing agents. Strong acids. Base metals.

**Hazardous Decomposition Products:** Carbon oxides, Other irritating and toxic gases.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** No data available.

LD/LC50 values relevant for classification:
---

Not available.
----------------

**Skin corrosion/irritation:** No irritant effect.

**Serious eye damage/irritation:** Cause serious eye irritation.

**Respiratory or skin sensitization:** No sensitizing effects known.

**Specific target organ system toxicity:** No information available.

**CMR effects(carcinogenity, mutagenicity and toxicity for reproduction):** No information available.



## 12. Ecological Information

### Toxicity:

Acquatic toxicity:

No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

**Other adverse effects:** No information available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

### Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

## 14. TRANSPORT INFORMATION

### Land transport

ADR/RID class: Not regulated.

UN-Number: UN3090 or UN3091.

### Maritime transport

IMDG Class: Class 9.

UN Number: UN3090 or UN3091.

Marine pollutant: No

### Air transport

ICAO/IATA Class: Class 9

UN/ID Number: UN3090 or UN3091

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The Lithium manganese dioxide cylindrical cell had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The lithium ion batteries according to Section II of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION 969~970 of the Dangerous Goods regulations 58<sup>th</sup> Edition may be transported. The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of Special Provision 188 of IMDG(37-14) to be transported as non-dangerous goods  
 Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

**Authorisations:** No information available.

**Restrictions on use:** No information available.

### Regulatory information

CAS No.	EU (EINECS)	US (TSCA)	Japan (ENCS)	Canada (DSL/ NDSL)	Australia (AICS)	Korea (ECL)	China (IECSC)
7439-93-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7791-03-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
25037-45-0	Listed	Listed	Listed	DSL	Listed	Listed	Listed
115-10-6	Listed	Listed	Listed	DSL	Listed	Listed	Listed
9003-07-0	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1313-13-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1333-86-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed
65997-19-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
110-71-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed

**Chemical safety assessment** A Chemical Safety Assessment has not been carried out.

## 16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.

\*\*\*\*\*End of SDS\*\*\*\*\*