

SOAR

 Ceiling mounted • Dry location listed **PROGRESS LED**

P2542-0930K

Description:

With a white opal shade and a 17W dimmable LED module, the 54" Soar ceiling fan offers energy- and cost-savings benefits for a variety of living spaces. The four-blade fan comes with a remote control and is available in a Brushed Nickel finish. LED source features a 3000K-color temperature.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- White Opal lens
- 54" 5 Blade Fan with LED Light
- Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Mounting hardware is included
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 80" of wire supplied
- Black blades, plywood construction
- 12 degree blade pitch
- Remote Control Included
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately.
- Triple capacitor speed control, manual reverse control
- Meets California Title 24 JA8-2016
- Airflow: 4814 CFM*
- Energy consumption: 65 watts (excluding lights)*
- Airflow efficiency: 74 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1500/88.2 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016

Images:



Dimensions:

Diameter: 54"
Height: 14-1/2"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$11

\$3 | \$34

Cost Range of Similar Models (19" – 84")

- Based on 12 cents per kWh and 6.4 hours use per day
- **Your cost depends on rates and use**
- Energy Use: 41 Watts

Airflow

3,384

Cubic Feet Per Minute

- The higher the airflow, the more air the fan will move
- Airflow Efficiency: 83 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy