

The Pro's Choice Since 1936

SAKRETE®

Concrete Glue

SAKRETE® Concrete Glue is a liquid latex bonding adhesive for bonding new concrete, mortar or gypsum plaster to existing surfaces. Easy to apply. Eliminates the need for roughing or scoring old surfaces.

SAFETY:

READ and UNDERSTAND the Material Safety Data Sheet (MSDS) before using this product. WARNING: Wear protective clothing and equipment. See HMIS block. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA). KEEP OUT OF REACH OF CHILDREN.

PREPARATION:

Concrete or plaster surface should be structurally sound and free of any oil, gas, grease, paint, etc. New paint should be at least 60 days old and firmly adhered to the under surface. Glossy surfaces should be dulled by sanding. Gently shake or stir concrete glue before use. Do not thin.

APPLICATION: Concrete surfaces to be repaired should be damp but have no standing water. Apply SAKRETE® Concrete Glue by brush, roller or spray. Fresh cement topping or plaster may be applied after the surface has become tacky (usually ten minutes to one hour.)

COVERAGE: To determine coverage see table below. Coverage will vary depending on porosity and texture of existing surface. Do not apply to frozen surfaces.

1 qt. (0.95 L)	50 - 75 sq. ft.
1 gal. (4.5 L)	200 - 300 sq. ft.
5 gal. (18.9 L)	1,000 - 1,500 sq. ft.

CONTAINS: Water: Water (CAS#7732-18-5), Ethylene Glycol (CAS#23085-46-5), PVA Emulsion (CAS#9003-207) and Biocide (CAS#2634-33-5).
CLEAN UP: Use soap and water.

STORAGE:

Store in a tightly closed container off the floor in a dry place.

PACKAGING:

1 qt. (0.95 L) - UPC: 7-64661-18816-2
1 Gallon (4.5 L) UPC: 7-64661-18764-6
5 Gallon. (18.9 L) - UPC: 7-64661-18775-2

LIMITED PRODUCT WARRANTY

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the date the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement of defective product or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.

ENVIRONMENTAL ADVISORY:

Uncured or crushed cured cement is an environmental hazard, which may adversely affect fish and wildlife. Dispose of construction debris containing cement, including empty bags, at a permitted municipal disposal firm. Do not use crushed concrete as a fill near an aquatic habitat.

CAUTION: Vapors may cause irritation of eyes, nose and throat. May cause skin sensitization for other allergic responses. **HARMFUL IF SWALLOWED.** Do not breathe vapors. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use. Do not transfer to unmarked container. **FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get prompt medical attention; for skin, wash thoroughly with plenty of soap and water. If vapors or fumes are inhaled, remove person to fresh air. If swallowed, give plenty of water and call a Physician immediately. **DO NOT INDUCE VOMITING.**

The SAKRETE Companies
866-SAKRETE
866-725-7383

REV 3-10