



Step Flashing Flat for Shingle Roofing

Step flashing: provides a moisture barrier that protects the interface between roof and wall connections for shingle roof applications.

Item # 11961 STEP FLASH FLAT AL ST 5"X7" CT PK 100

Description: *Step flashing* Flat Aluminum 5"X7" shingles protect the interface between a roof and a wall. This product can be bent on the job to fit custom or fill in flashing requirements. Small flashing pieces that are woven into the shingles as you work your way up the wall to protect from water leaks that can cause hidden damage.

Installation: When installing step flashing for shingle roof to wall applications, separate pieces of step flashing are installed as each course of shingles are applied. The upper edge of each piece of step flashing should extend approx. 2" inches above each course of shingles. The lower edge should be approx. 1/2" inch above the butte of the shingles forming the next course. This step application allows for all fasteners to be concealed.

Features: Step Flash for Shingle Roofing

- **This product can be bent on the job to fit custom or fill in flashing requirements.**
- **Weatherproofs around chimneys, skylights and dormers**
- **Also available in preformed sizes and colors**

Material; This product is made from Standard Gauge Mill Finished Aluminum for added corrosion protection, so that they will last over the life of the structure, length 7", width 5"

- 100 pieces per bundle, (Contractor Pack)

