

SAFETY DATA SHEET

Issuing Date 16-Mar-2015

Revision Date 16-Mar-2015

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Toro 4 Cycle Oil

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Engine (motor) oil for Auto or Boat

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name The Toro Company

Supplier Address 8111 Lyndale Avenue South
Bloomington
MN
8515
US

Supplier Phone Number Phone:952-887-8515
Contact Phone951-785-3482

Supplier Email eden.allen@toro.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Carcinogenicity	Category 1A
-----------------	-------------

GHS Label elements, including precautionary statements

Emergency Overview



Signal word	Danger
Hazard Statements May cause cancer 	
Appearance	Physical state
Clear, amber	Oil Liquid
	Odor Oily

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	60 - 100	*
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate	72162-32-4	1 - 5	*
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Note: When using this product in high pressure equipment - Accidental high velocity dermal injection of this material requires immediate medical attention.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately if symptoms occur.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Call a physician or poison control center immediately. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Uniform Fire Code

Combustible Liquid: III-B

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place.

Incompatible Products Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral	
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4	-	TWA: 1 mg/m ³ Ni (vacated) TWA: 0.1 mg/m ³ Ni	IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ except Nickel carbonyl Ni

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health



Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Oil, Liquid	Odor	Oily
Appearance	Clear, amber	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	400 °C / 752 °F	None known
Flash Point	254 C / 489 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	0.89	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available



Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	> 15 g/kg (Rat)	-	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
---------------	-------	------	-----	------

Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	A2	Group 1		X
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4		Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	Contains a known or suspected carcinogen.
Target Organ Effects	Skin.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)		48h EC50: > 1000 mg/L
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3		96h LC50: 1.0 - 5.0 mg/L (Pimephales promelas) 96h LC50: 10.0 - 35.0 mg/L (Pimephales promelas)		48h EC50: 1 - 1.5 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 221

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3	Toxic

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name NOT REGULATED
Hazard Class NON REGULATED
 N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA
Proper Shipping Name Not regulated
Hazard Class NON REGULATED
 N/A

IMDG/IMO
Hazard Class Not regulated
 N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate - 72162-32-4	72162-32-4	1 - 5	0.1
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts - 68649-42-3	68649-42-3	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4		X		
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate - 72162-32-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
phosphorodithioic acid O,O-dialkyl(C=I-14) esters zinc salts 68649-42-3			X	X	
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4			X	X	X

International Regulations

Mexico**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Sulfuric acid, nickel salt, reaction products with sulfurized calcium phenolate 72162-32-4 (1 - 5)		Mexico: TWA 0.1 mg/m ³ Mexico: STEL 0.3 mg/m ³

*Mexico - Occupational Exposure Limits - Carcinogens***Canada****WHMIS Hazard Class**

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 1*	Flammability 1	Physical Hazard 0	Personal Protection
				X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 16-Mar-2015
Revision Date 16-Mar-2015
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

SAFETY DATA SHEET

Issuing Date 16-Mar-2015

Revision Date 30-Jan-2014

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Fuel Treatment

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name The Toro Company

Supplier Address 8111 Lyndale Avenue South
Bloomington
MN
8515
US

Supplier Phone Number Phone:952-887-8515
Contact Phone951-785-3482

Supplier Email eden.allen@toro.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 4

GHS Label elements, including precautionary statements



Emergency Overview

Signal word		Danger	
Hazard Statements			
May cause genetic defects			
May be fatal if swallowed and enters airways			
Combustible liquid			
			
Appearance Liquid		Physical state Liquid	Odor Gasoline oil

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation
Toxic to aquatic life
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Petroleum naphtha, light aromatic	64742-95-6	60 - 100	*
Petroleum distillates, hydrotreated light	64742-47-8	60 - 100	*
Xylene	1330-20-7	3 - 7	*
1,2,3-Trimethylbenzene	526-73-8	3 - 7	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin contact

Wash with soap and water.

Inhalation

Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed**Most Important Symptoms and Effects**

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code

Combustible Liquid: III-A

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with eyes. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Dam up. Take precautionary measures against static discharges. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)	
Xylene 1330-20-7	STEL = 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
1,2,3-Trimethylbenzene 526-73-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid	Odor	Gasoline oil
Appearance	Liquid	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	79 C / 174 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	.8146	None known	
Water Solubility	Liquid	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact

Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	There is no data for this product. Contains a known or suspected mutagen.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		

*IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans*

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	Contains a known or suspected mutagen. Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. May cause adverse effects on the bone marrow and blood-forming system.
Target Organ Effects	May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Blood. Central Nervous System (CNS). Eyes. Skin. Kidney. Liver.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
86,000.00 mg/kg
ATEmix (dermal)
22,000.00 mg/kg (ATE)
ATEmix (inhalation-gas)
90,000.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
30.00 mg/l
ATEmix (inhalation-vapor)
220.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum naphtha, light aromatic 64742-95-6		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L
Petroleum distillates, hydrotreated light 64742-47-8		96h LC50: = 2.2 mg/L (Lepomis macrochirus) 96h LC50: = 2.4 mg/L (Oncorhynchus mykiss) 96h LC50: = 45 mg/L (Pimephales promelas)		96h LC50: = 4720 mg/L
Xylene 1330-20-7		96h LC50: = 13.4 mg/L (Pimephales promelas) 96h LC50: = 19 mg/L (Lepomis macrochirus) 96h LC50: 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50: 2.661 - 4.093 mg/L (Oncorhynchus mykiss) 96h LC50: = 780 mg/L (Cyprinus carpio) 96h LC50: > 780 mg/L (Cyprinus carpio) 96h LC50: 30.26 - 40.75 mg/L (Poecilia reticulata) 96h LC50: 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50: 7.711 - 9.591 mg/L (Lepomis macrochirus)	EC50 = 0.0084 mg/L 24 h	48h EC50: = 3.82 mg/L 48h LC50: = 0.6 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Xylene 1330-20-7	3.15

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Xylene 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT
Proper Shipping Name NOT REGULATED
Hazard Class NON REGULATED
 N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA
Proper Shipping Name Not regulated
Hazard Class NON REGULATED
 N/A

IMDG/IMO
Hazard Class Not regulated
 N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	3 - 7	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ= 100 lb final RQ RQ= 45.4 kg final RQ

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Xylene 1330-20-7	X	X	X	X	X
1,2,3-Trimethylbenzene 526-73-8	X	X			X

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Xylene 1330-20-7 (3 - 7)		Mexico: TWA= 100 ppm Mexico: TWA= 435 mg/m ³ Mexico: STEL= 150 ppm Mexico: STEL= 655 mg/m ³
1,2,3-Trimethylbenzene 526-73-8 (3 - 7)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³



Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class
Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards * 2	Flammability 2	Physical Hazard 0	Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501
Issuing Date	16-Mar-2015
Revision Date	30-Jan-2014
Revision Note	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet