

Safety Data Sheet

1. Identification

1.1 Product Name	BATHWORKS® DIY Refinishing Kit - Part A Base Color	
1.2 Distributor	Munro Products 9150 Clarence Center Road Clarence Center, NY 14032	(716) 741-9450 www.bath-works.net
1.3 Emergency Information	CHEMTREC® Poison Control Center	(800) 424-9300 (800) 854-6813

2. Hazard Identification

2.1 Classification of the substance or mixture

Flam. Liq. 3;	H226 Flammable liquid and vapor.
Org. Perox. C;	H242 Heating may cause a fire.
Skin Irrit. 3;	H316 Causes mild skin irritation.
Eye Irrit. 2;	H319 Causes serious eye irritation.
Skin Sens. 1;	H317 May cause an allergic skin reaction.
Aquatic Acute 2;	H401 Toxic to aquatic life.
Aquatic Chronic 3;	H412 Harmful to aquatic life with long lasting effects

2.2 Label Elements



Flammable



Danger

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P234 Keep only in original container.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P331 Do NOT induce vomiting.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P333 If skin irritation or a rash occurs:.
 P337 If eye irritation persists:.
 P363 Wash contaminated clothing before reuse.
 P370 In case of fire: Use water spray, fog, or regular foam..
 P403+233 Store in a well ventilated place. Keep container tightly closed.
 P410 Protect from sunlight.
 P420 Store away from other materials.
 P501 Dispose of contents / container in accordance with local / national regulations.

2.3 HMIS Rating

Health: 3

Flammability: 3

Reactivity: 0

3. Ingredient Composition

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	----	[1][2]
ACRYLIC POLYMER (PROPRIETARY) CAS Number: Proprietary	10 - 25	Eye Dam. 2A;H319	[1]
Methyl n-amyl ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Barium sulfate CAS Number: 0007727-43-7	10 - 25	----	[1][2]
BUTYL ACETATE CAS Number: 0000123-86-4	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Silica, amorphous CAS Number: 0007631-86-9	1.0 - 10	----	[1][2]
Aluminum hydroxide CAS Number: 0021645-51-2	1.0 - 10	Eye Irrit. 2;H319 STOT SE 3;H335	[1]
Ethyl orthoformate CAS Number: 0000122-51-0	1.0 - 10	Flam. Liq. 2;H225	[1]
Mixed Diamedes Compound (Proprietary) CAS Number: Proprietary	1.0 - 10	----	[1]
Dicumyl peroxide CAS Number: 0000080-43-3	1.0 - 10	Org. Perox. F;H242 Eye Irrit. 2;H319 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1]
BUTYL PEROXYBENZOATE CAS Number: 0000614-45-9	1.0 - 10	Org. Perox. C;H242 Acute Tox. 4;H332 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Acute 1;H400	[1]
Bis (1,2,2,6,6-pentamethyl-4-piperidiny)l sebacate CAS Number: 0041556-26-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410 Aquatic Acute 1;H400	[1]
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P CAS Number: 0082919-37-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16

4. First Aid

4.1 General First Aid Measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Firefighting

5.1 Extinguishing media

CAUTION:	This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.
CAUTION:	For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.
Small Fires:	Use dry chemical, CO ₂ , water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2 Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS:	Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.
-----------------------------	--

5.3 Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

5.4 ERG Guide No. 128

6. Accidental Release

6.1 Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. **LARGE SPILLS:** Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling & Storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing. Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use. Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation

8. Exposure Controls & Personal Protection

8.1 Control Parameters

CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL
		Brazil	No Established Limit
0000122-51-0	Ethyl orthoformate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000123-86-4	BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m ³ TWA200 ppm STEL; 950 mg/m ³ STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m ³ TWA200 ppm STEL; 950 mg/m ³ STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA LMPE-PPT; 710 mg/m ³ TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m ³ STEL [LMPE-CT]
		Brazil	No Established Limit
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007631-86-9	Silica, amorphous	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	6 mg/m ³ TWA3000 mg/m ³ IDLH
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
		ACGIH	10 mg/m ³ TWA
		NIOSH	10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m ³ TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m ³ TWA (total dust)
		ACGIH	10 mg/m ³ TWA
		NIOSH	5000 mg/m ³ IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m ³ TWA
		Mexico	10 mg/m ³ TWA LMPE-PPT (as Ti)20 mg/m ³ STEL [LMPE-CT] (as Ti)
		Brazil	No Established Limit
0021645-51-2	Aluminum hydroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit

		Mexico	No Established Limit
		Brazil	No Established Limit
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
Proprietary	Mixed Diamedes Compound (Proprietary)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data			
CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	NIOSH	No Established Limit
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000122-51-0	Ethyl orthoformate	NIOSH	No Established Limit
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations
0000614-45-9	BUTYL PEROXYBENZOATE	NIOSH	No Established Limit
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-sebacate piperidinyl)	NIOSH	No Established Limit
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-	NIOSH	No Established Limit
Proprietary	Mixed Diamedes Compound	NIOSH	No Established Limit
Proprietary	ACRYLIC POLYMER	NIOSH	No Established Limit

CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000122-51-0	Ethyl orthoformate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0021645-51-2	Aluminum hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	Mixed Diamedes Compound (Proprietary)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No

8.2 Exposure Controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical & Chemical Properties

Appearance	Colored Liquid
Odor threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	100 (C) 212 (F)
Flash Point	27 (C) 80 (F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .6 Upper Explosive Limit: No Established Limit
Vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.28
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured

Viscosity (cSt)

No Established Limit Not Measured

VOC %

Refer to the Technical Data Sheet or label where information is available.

10. Stability & Reactivity	
10.1. Reactivity	No data available
10.2. Chemical stability	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
10.3. Possibility of hazardous reactions	No data available
10.4. Conditions to avoid	No data available
10.5. Incompatible materials	Strong oxidizing agents.
10.6. Hazardous decomposition products	HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological Information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	No data available	No data available	No data available	No data available
Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
BUTYL ACETATE - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available
Silica, amorphous - (7631-86-9)	5,110.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Aluminum hydroxide - (21645-51-2)	5,000.00, Rat - Category: 5	No data available	No data available	No data available
Ethyl orthoformate - (122-51-0)	7,060.00, Rat - Category: NA	17,820.00, Rabbit - Category: NA	No data available	No data available

Mixed Diamedes Compound (Proprietary) - (Proprietary)	No data available	No data available	No data available	No data available
Dicumyl peroxide - (80-43-3)	4,000.00, Rat - Category: 5	No data available	No data available	No data available
BUTYL PEROXYBENZOATE - (614-45-9)	4,838.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	4.90, Rat - Category: 4
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate - (41556-26-7)	2,615.00, Rat - Category: 5	No data available	No data available	No data available
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P -	No data available	No data	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological Information

12.1 Toxicity No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	Not Available	Not Available	Not Available
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
BUTYL ACETATE - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Silica, amorphous - (7631-86-9)	10,000.00, Danio rerio	10,000.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
Aluminum hydroxide - (21645-51-2)	Not Available	Not Available	Not Available
Ethyl orthoformate - (122-51-0)	592.00, Leuciscus idus	Not Available	Not Available
Mixed Diamedes Compound (Proprietary) - (Proprietary)	Not Available	Not Available	Not Available
Dicumyl peroxide - (80-43-3)	Not Available	Not Available	Not Available

BUTYL PEROXYBENZOATE - (614-45-9)	1.50, Danio rerio	Not Available	Not Available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	Not Available
DECANEDIOIC ACID, METHYL 1,2,2,6,6- PENTAMETHYL-4-P - (82919-37-7)	Not Available	Not Available	Not Available

12.2 Persistence and degradability	No data available
12.3 Bioaccumulative potential	Not Measured
12.4 Mobility in soil	No data available
12.5 Results of PBT and vPvB assessment	This product contains no PBT/vPvB chemicals.
12.6 Other adverse effects	No data available

13. Disposal Information

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transportation Information

14.1 UN number	UN 1263
14.2 UN proper shipping name	PAINT
14.3 Transport hazard class(es)	

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)
Proper Shipping Name	PAINT	PAINT
UN Number	UN 1263	UN 1263
Hazard Class	3	3, Sub Class 3
Packaging Group	III	III
	CERCLA/DOT RQ: 3482 gal. / 37136 lbs	System Reference Code: 1

14.4 Packing group	III
14.5 Environmental hazards	IMDG Marine Pollutant: No
14.6 Special precautions for user	Not Applicable
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not Applicable

15. Regulatory Information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory
WHMIS Classification	B2 D2B C
DOT Marine Pollutants (10%):	(No Product Ingredients Listed)
DOT Severe Marine Pollutants (1%):	(No Product Ingredients Listed)
EPCRA 311/312 Chemicals and RQs (>.1%):	BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)) Xylenes (o-, m-, p- isomers)(100 lb final RQ; 45.4 kg final RQ)
EPCRA 302 Extremely Hazardous (>.1%):	(No Product Ingredients Listed)
EPCRA 313 Toxic Chemicals (>.1%):	Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :	Barium sulfate Methyl n-amyl ketone BUTYL ACETATE Silica, amorphous BUTYL PEROXYBENZOATE Titanium dioxide
Penn RTK Substances (>1%) :	Barium sulfate Ethyl orthoformate Methyl n-amyl ketone BUTYL ACETATE Silica, amorphous BUTYL PEROXYBENZOATE Titanium dioxide
Penn Special Hazardous Substances (>.01%) :	(No Product Ingredients Listed)
RCRA Status:	(No Product Ingredients Listed)
N.J. RTK Substances (>1%) :	Barium sulfate Ethyl orthoformate Methyl n-amyl ketone BUTYL ACETATE Silica, amorphous BUTYL PEROXYBENZOATE Titanium dioxide
N.J. Special Hazardous Substances (>.01%) :	Benzene, ethyl- Ethyl orthoformate BUTYL ACETATE Quartz BUTYL PEROXYBENZOATE Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous Substances (>.1%) :	Xylenes (o-, m-, p- isomers)
Proposition 65 - Carcinogens (>0%):	Benzene, ethyl- Quartz Titanium dioxide
Proposition 65 - Female Repro Toxins (>0%):	(No Product Ingredients Listed)
Proposition 65 - Male Repro Toxins (>0%):	(No Product Ingredients Listed)
Proposition 65 - Developmental Toxins (>0%):	(No Product Ingredients Listed)

16. Other Information

SDS Revision Date:	10/20/2014
--------------------	------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

1. Identification

1.1 Product Name	BATHWORKS® DIY Refinishing Kit – Part B Base Hardener	
1.2 Distributor	Munro Products	(716) 741-9450
	9150 Clarence Center Road	
	Clarence Center, NY 14032	www.bath-works.net
1.3 Emergency Information	CHEMTREC®	(800) 424-9300
	Poison Control Center	(800) 854-6813

2. Hazard Identification

- 2.1. Classification of the substance or mixture
- Flam. Liq. 3; H226 Flammable liquid and vapor.
 - Skin Sens. 1; H317 May cause an allergic skin reaction.
 - Resp. Sens. 1; H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled.
 - Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

P370 In case of fire:.

P403+233 Store in a well ventilated place. Keep container tightly closed.

2.3 HMIS Rating

Health: 3

Flammability: 3

Reactivity: 0

3. Ingredient Composition

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Hexamethylene diisocyanate homopolymer CAS Number: 0028182-81-2	75 - 100	Skin Sens. 1;H317	[1]
BUTYL ACETATE CAS Number: 0000123-86-4	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304 Aquatic Chronic 2;H411 (Self Classification)	[1]
Hexamethylene diisocyanate CAS Number: 0000822-06-0	0.10 - 1.0	Acute Tox. 3;H331 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First Aid

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. May cause allergic respiratory reaction.
Inhalation	Harmful if inhaled. May cause lung injury. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea
Eyes	Causes severe eye irritation. Avoid contact with eyes
Skin	Causes skin irritation. May be harmful if absorbed through the skin
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	None known

5. Firefighting

5.1. Extinguishing media	<p>CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.</p> <p>CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.</p> <p>SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam.</p> <p>LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.</p>
5.2. Special hazards arising from the substance or mixture	<p>HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.</p>
5.3. Advice for fire-fighters	<p>Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.</p>
5.4. ERG Number	128

6. Accidental Release

6.1. Personal precautions, protective equipment and emergency procedures	<p>ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.</p>
6.2. Environmental precautions	<p>Do not allow spills to enter drains or watercourses.</p>
6.3. Methods and material for containment and cleaning up	<p>CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).</p>

7. Handling & Storage

7.1. Precautions for safe handling	<p>Handling: Vapors may cause flash fire or ignite explosively.</p> <p>In Storage: Keep away from heat, sparks and flame</p>
7.2. Conditions for safe storage, including any incompatibilities	<p>Store between 40-100F (4-38C).</p> <p>Avoid contact with eyes, skin and clothing.</p> <p>Strong oxidizing agents.</p> <p>Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone</p>
7.3. Specific end use(s)	<p>Close container after each use.</p> <p>Wash thoroughly after handling.</p> <p>Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.</p>

8. Exposure Controls & Personal Protection

8.1. Control parameters

CAS No.	Ingredient	Source	Value
---------	------------	--------	-------

0000123-86-4	BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m ³ TWA 200 ppm STEL; 950 mg/m ³ STEL
		ACGIH	150 ppm TWA 200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m ³ TWA 200 ppm STEL; 950 mg/m ³ STEL 1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA 200 ppm STEL
		Mexico	150 ppm TWA LMPE-PPT; 710 mg/m ³ TWA LMPE-PPT 200 ppm STEL [LMPE-CT]; 950 mg/m ³ STEL [LMPE-CT]
		Brazil	No Established Limit
		0000822-06-0	Hexamethylene diisocyanate
ACGIH	0.005 ppm TWA		
NIOSH	0.005 ppm TWA; 0.035 mg/m ³ TWA 0.020 ppm Ceiling (10 min); 0.140 mg/m ³ Ceiling (10 min)		
Supplier	No Established Limit		
OHSA, CAN	0.005 ppm TWA (designated substances regulation, listed under Isocyanates, organic compounds); 0.02 ppm Ceiling (designated substances regulation, listed under Isocyanates, organic compounds) 0.005 ppm TWA (listed under Isocyanates, organic compounds (Hexamethylene diisocyanate (HDI)));		
Mexico	No Established Limit		
Brazil	No Established Limit		
0028182-81-2	Hexamethylene diisocyanate homopolymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0000822-06-0	Hexamethylene diisocyanate	NIOSH	Respiratory effects and sensitization pulmonary irritation (Listed under
0028182-81-2	Hexamethylene diisocyanate homopolymer	NIOSH	No Established Limit

0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit
--------------	-------------------	-------	----------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000822-06-0	Hexamethylene diisocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0028182-81-2	Hexamethylene diisocyanate homopolymer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure Controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **FOR USERS OF 3M RESPIRATORY PROTECTION ONLY:** For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. **INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES**

MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. A supplied air respirator (either positive pressure or continuous flow type) is required. Follow manufacturer's directions for respirator use and observe requirements specified in 29 CFR 1910.134.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Depending on the site-specific conditions of use, provide adequate ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove

soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical & Chemical Properties	
Appearance	Colored Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	145 (C) 293 (F)
Flash Point	27 (C) 80 (F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0.6 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.12
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit
VOC %	Refer to the Technical Data Sheet or label where information is available.
Other information	No further information

10. Stability & Reactivity	
10.1. Reactivity	No data available
10.2. Chemical stability	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
10.3. Possibility of hazardous reactions	No data available
10.4. Conditions to avoid	No data available
10.5. Incompatible materials	Strong oxidizing agents.
10.6. Hazardous decomposition products	HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological Information	
Acute toxicity	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Hexamethylene diisocyanate homopolymer - (28182-81-2)	5,000.00, Rat - Category: 5	No data available	No data available	No data available
BUTYL ACETATE - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available
Petroleum naphtha - (64742-95-6)	6,800.00, Rat -Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Hexamethylene diisocyanate - (822-06-0)	No data available	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological Information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Toxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Hexamethylene diisocyanate homopolymer - (28182-81-2)	100.00, Danio rerio	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus
BUTYL ACETATE - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Hexamethylene diisocyanate – (822-06-0)	82.80, Danio rerio	89.10, Daphnia magna	77.40 (72 hr), Desmodesmus subspicatus

- | | |
|--|--|
| 12.1. Persistence and degradability | No data available |
| 12.2. Bioaccumulative potential | Not Measured |
| 12.3. Mobility in soil | No data available |
| 12.4. Results of PBT and vPvB assessment | This product contains no PBT/vPvB chemicals. |
| 12.5. Other adverse effects | No data available |

13. Disposal Information

13.1 Waste treatment methods Do not allow spills to enter drains or watercourses.
Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transportation Information

14.1 UN number UN 1263
14.2 UN proper shipping name PAINT
14.3 Transport hazard class(es)

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)
Proper Shipping Name	PAINT	PAINT
UN Number	UN 1263	UN 1263
Hazard Class	3	3, Sub Class 3
Packaging Group	III	III
	CERCLA/DOT RQ: 5359 gal. / 50000 lbs.	System Reference Code: 1

14.4 Packing group III
14.5 Environmental hazards IMDG Marine Pollutant: No
14.6 Special precautions for user Not Applicable

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

15. Regulatory Information

Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification	B2 D2A
DOT Marine Pollutants (10%):	(No Product Ingredients Listed)
DOT Severe Marine Pollutants (1%):	(No Product Ingredients Listed)
EPCRA 311/312 Chemicals and RQs (>.1%):	Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ) Hexamethylene diisocyanate (100 lb final RQ; 45.4 kg final RQ) BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))
EPCRA 302 Extremely Hazardous (>.1%):	(No Product Ingredients Listed)
EPCRA 313 Toxic Chemicals (>.1%):	Benzene, ethyl- Hexamethylene diisocyanate
Mass RTK Substances (>1%) :	BUTYL ACETATE
Penn RTK Substances (>1%) :	BUTYL ACETATE
Penn Special Hazardous Substances (>.01%):	(No Product Ingredients Listed)
RCRA Status:	(No Product Ingredients Listed)
N.J. RTK Substances (>1%):	BUTYL ACETATE
N.J. Special Hazardous Substances (>.01%):	Benzene, ethyl- BUTYL ACETATE
N.J. Env. Hazardous Substances (>.1%):	Benzene, ethyl-
Hexamethylene diisocyanate Proposition 65 - Carcinogens (>0%):	Benzene, ethyl-

Proposition 65 - Female Repro Toxins (No Product Ingredients Listed)
(>0%):
Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed)
Proposition 65 - Developmental Toxins (No Product Ingredients Listed)
(>0%):

16. Other Information

SDS Revision Date: 3/11/2014

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

1. Identification

1.1 Product Name	Bathworks® Liquid Primer	
1.2 Distributor	Munro Products	(716) 741-9450
	9150 Clarence Center Road	
	Clarence Center, NY 14032	www.bath-works.net
1.3 Emergency Information	CHEMTREC®	(800) 424-9300
	Poison Control Center	(800) 854-6813

2. Hazard Identification

- 2.1 Classification of the substance or mixture
- FLAMMABLE LIQUIDS - Category 3
 - ACUTE TOXICITY (inhalation) - Category 4
 - SKIN CORROSION/IRRITATION - Category 2
 - SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
 - CARCINOGENICITY - Category 3
 - TOXIC TO REPRODUCTION (Unborn child) - Category 2
 - SPECIFIC TARGET ORGAN TOXICITY
 - SINGLE EXPOSURE (Respiratory tractirritation and Narcotic effects) - Category 3
 - REPEATED EXPOSURE - Category 2
 - ASPIRATION HAZARD - Category 1

2.2 Label Elements

Pictograms



Signal Word

Danger

Hazard Statements

Flammable liquid and vapor.
 Harmful if inhaled.
 Causes serious eye irritation. Causes skin irritation.
 Suspected of damaging the unborn child. Suspected of causing cancer.
 May be fatal if swallowed and enters airways. May cause respiratory irritation.
 May cause drowsiness and dizziness.
 May cause damage to organs through prolonged or repeated exposure

2.3 Precautionary statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response

Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off

	contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	None known.

2.4 HMIS Health: 2 Flammability: 0 Physical Hazards: 0

3. Ingredient Composition

Ingredient name	% by weight	CAS number
Xylene	84.9	1330-20-7
Ethylbenzene	15.0	100-41-4
Toluene	0.1	108-88-3

4. First Aid

4.1 General First Aid Measures

Eyes	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms and effects, both acute and delayed

Eyes	Causes serious eye irritation.
------	--------------------------------

Inhalation	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
Skin	Causes skin irritation.
Ingestion	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.
4.3 Overexposure signs & symptoms	
Eyes	Adverse symptoms may include the following: pain or irritation, watering, redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation, coughing, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations
Skin	Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths skeletal, malformations
Ingestion	Adverse symptoms may include the following: nausea or vomiting, reduced fetal weight, increase in fetal deaths, skeletal malformations
4.4 Indication of immediate medical attention and special treatment needed, if necessary	
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	None
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

5. Firefighting

5.1 Extinguishing Media	
Suitable extinguishing media	Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	Do not use water jet.
5.2 Specific hazards arising from the chemical	Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
5.3 Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide, carbon monoxide
5.4 Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
5.5 Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release

6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the

information in "For non- emergency personnel".
 Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.2 Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling & Storage

7.1 Protective measures Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2 Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.3 Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure Controls & Personal Protection

8.1 Control Parameters

Ingredient name	Exposure limits
Xylene	ACGIH TLV (United States, 4/2014). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m ³ 15 minutes.
	OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours.

	TWA: 435 mg/m ³ 8 hours.
	ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours.
Ethylbenzene	NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m ³ 15 minutes.
	OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes.
Toluene	NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes.
	ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours.

8.2 Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8.3 Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

8.4 Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. Physical & Chemical Properties
--

Physical state	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	136°C (276.8°F)
Flash point	Closed cup: 27°C (80.6°F) [Pensky-Martens Closed Cup]
Evaporation rate	0.8 (butyl acetate = 1)
Flammability (solid, gas)	Not available.
Lower and upper explosive (flammable) limits	Lower: 1%, Upper: 7%
Vapor pressure	0.13 kPa (0.946 mm Hg) [at 20°C]
Vapor density	3.66 [Air = 1]
Relative density	0.86
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt)
Heat of combustion	0.00002764 kJ/g

10. Stability & Reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

11.1 Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

Xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-

11.2 Irritation Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
Ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

11.3 Classification

Product/ingredient name	OSHA	IARC	NTP
Xylene	-	3	-
Ethylbenzene	-	2B	-
Toluene	-	3	-

11.4 Sensitization Not available.

11.5 Mutagenicity Not available.

11.6 Carcinogenicity Not available.

11.7 Reproductive toxicity Not available.

11.8 Teratogenicity Not available.

11.9 Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Xylene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

11.10 Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Xylene	Category 2	Not determined	Not determined
Ethylbenzene	Category 2	Not determined	Not determined
Toluene	Category 2	Not determined	Not determined

11.11 Aspiration hazard

Name	Result
Xylene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1

11.12 Numerical measures of toxicity

Route	Acute Toxicity Estimate (ATE)
Oral	4163.1 mg/kg
Inhalation (gases)	5892.1 ppm

12. Ecological Information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Xylene	Acute LC50 8500 µg/l Marine water	Crustaceans – Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae – Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae – Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
Toluene	Acute EC50 12500 µg/l Fresh water	Algae – Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans – Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene	-	-	Readily
Ethylbenzene	-	-	Readily
Toluene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	-	8.1 to 25.9	low
Toluene	-	90	low

12.4 Soil/water partition coefficient (KOC) Not available

12.5 Other adverse effects No known significant effects or critical hazards.


13. Disposal Information

13.1 Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transportation Information

14.1 Proper Shipping Name UN1307

14.2 UN Number	XYLENES
14.3 Hazard Class	3 
14.4 Packaging Group	III
14.5 Environmental Hazards	None
14.6 Additional Information	
IMDG	Emergency schedules (EmS) F-E, S-D
Mexico	ERG #130
14.7 Bulk Transportation	Not available
14.8 Special Precautions	Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. Regulatory Information

California Prop. 65	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm
---------------------	--

16. Other Information

SDS Revision Date:	5/1/2015
--------------------	----------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

Safety Data Sheet

1. Identification

1.1 Product Name	BATHWORKS® Etching Cleaner	
1.2 Distributor	Munro Products 9150 Clarence Center Road Clarence Center, NY 14032	(716) 741-9450 www.bath-works.net
1.3 Emergency Information	CHEMTREC® Poison Control Center	(800) 424-9300 (800) 854-6813

2. Hazard Identification

2.1 Classification of the substance or mixture

Skin corrosion: 2

Eye Irritant: 2A

2.2 Label Elements



WARNING; Harmful if swallowed.
Eye and skin irritant.
May cause burns.

2.3 NFPA Rating: Health: 2 Fire: 0 Instability: 0

3. Ingredient Composition

CHEMICAL NAME	CAS Number	%WT	STEL	TWA
Trisodium Phosphate Dodecahydrate	10101-89-0	75-80%	Not listed	Not Listed
Sodium Sesquicarbonate	533-96-0	20-25%	Not listed	Not Listed

4. First Aid

4.1 First Aid Procedures

Skin	Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse
Eyes	Flood with plenty of water with eyelids held open for at least 15 minutes and get medical attention promptly.
Inhalation	If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention.
Ingestion	DO NOT induce vomiting. If conscious and alert, give 2-4 cupfuls of milk or water. Get medical aid immediately.

4.2 General Health Considerations

Skin	Prolonged and/or repeated contact may cause irritation and/or dermatitis. Contact with skin causes irritation and positive burns, especially if the skin is wet or moist.
Eyes	Eye contact can cause irritation, redness, tearing, blurred vision and may cause transient injury to cornea.
Inhalation	Inhalation of dust can cause nasal and respiratory irritation
Ingestion	May cause irritation, burns to mouth and esophagus. Aspiration of the swallowed or vomited product can cause severe pulmonary complications

4.3 Notes to physician	Treat symptomatically. No specific antidote available.
4.4 Aggravation of pre-existing conditions	Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema, or bronchitis. Skin contact may aggravate existing skin disease.

5. Firefighting

5.1 Flash Point:	None.
5.2 Extinguishing Media:	Not combustible. Use extinguishing method suitable for surrounding fire.
5.3 Fire Fighting Procedures:	Solutions are moderately to strong alkaline. Wear full protective clothing.
5.4 Fire and Explosion Hazards:	Oxides of sodium and oxides of phosphorus

6. Accidental Release

6.1 Small Spill	Wipe or scrape up any material. Wash area thoroughly with detergent and water; ventilate adequately with good fresh air movement at floor level.
6.2 Large Spill	Wipe or scrape up any material. Wash area thoroughly with detergent and water; ventilate adequately with good fresh air movement at floor level.
6.3 Environmental Precautions	Do not release into sewers or waterways.
6.4 Methods for Containment	Shovel up and dispose of at an appropriate waste disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal

7. Handling & Storage

7.1 Handling	Avoid direct or prolonged contact with skin and eyes. Avoid breathing dusts. Do not ingest.
7.2 Storage:	Store in area that is cool and dry. Moisture can cause caking.

8. Exposure Controls & Personal Protection
--

8.1 Airborne Exposure Limits	See section 3
8.2 Engineering Controls	When a potential for excessive exposure exists, use local ventilation at the point of generation
8.3 Personal Protection Equipment	
Eye Protection:	Use dust proof goggles if dust is irritating eyes.
Respiratory Protection:	Wear NIOSH/MSHA approved dust respirator, if dust is formed.
Skin Protection:	Use dust proof gloves.

9. Physical & Chemical Properties

Appearance:	White crystalline solid
Odor:	None.
Boiling Point:	Decomposes
Vapor Pressure:	N/A
Solubility In Water:	Moderate
pH (1% in H ₂ O)	11-12
VOC %: N/A	N/A
Specific Gravity (H ₂ O=1):	1.035
Evaporation Rate:	N/A
Melting Point	No data
Freezing Point	No data
Flash Point	No data
Autoignition Temperature	No data

Lower explosive limit No data
Upper explosive limit No data

10. Stability & Reactivity

10.1 Stability: Stable
10.2 Conditions to Avoid:
10.3 Incompatibility: Solutions in water are highly alkaline and may produce hydrogen gas when in contact with aluminum. Will react with acids to form carbon dioxide
10.4 Hazardous Decomposition Products: Oxides of sodium and oxides of phosphorous.
10.5 Hazardous Polymerization: Will not occur.

11. Toxicological Information

11.1 Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP or OSHA
11.2 Acute: This product has not been tested as a whole.
11.3 Subchronic: This product has not been tested as a whole.
11.4 Routes of Exposure: Inhalation, Ingestion.

12. Ecological Information

12.1 Environmental Fate: While the alkalinity of this material is readily reduced in natural waters, the resulting phosphate may persist indefinitely or incorporate into biological systems.

13. Disposal Information

Small quantities may be deposited in general trash and residue flushed down drain with water. Large spills must be disposed of in accordance with local state and federal regulations.

14. Transportation Information

Not Regulated for Transportation
14.1 Proper Shipping Name N/A
14.2 UN Number N/A
14.3 Hazard Class N/A
14.4 Packaging Group N/A
14.5 Bulk Shipping N/A

15. Regulatory Information

15.1 OSHA: The international regulated ingredients of this product are listed
15.2 CERCLA-RQ: Product component (Trisodium Phosphate Dodecahydrate-5,000 lbs.)
15.3 SARA Hazard Category: None
15.4 SARA 313: Not listed
15.5 TSCA: CAS#10101-89-0 is not on the TSCA Inventory because it is a hydrate. It is considered to be listed if the CAS number for the anhydrous form is on the inventory (40CRF720.3(u)(2)). CAS#7601-54-9 is listed on the TSCA inventory

16. Other Information

SDS Revision Date: 8/14/2018

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.