

KILZ® ODORLESS® INTERIOR OIL-BASE PRIMER



- Primer/sealer/stainblocker with lower solvent odor
- Interior use
- Fast odor dissipation formula for no lingering odor
- Seals porous surfaces
- Blocks most interior stains including water, tannin and smoke from tobacco and fire
- Seals pet, smoke and food odors
- Excellent adhesion to most interior surfaces
- Fast dry: Recoat in 1 hour



Mineral Spirits
Clean-Up



300 - 400 sq. ft.*



30 Min - Dry Time to Touch
1 Hr - Dry Time to Recoat



Protect from
Freezing

WHERE TO USE

KILZ ODORLESS® oil-base is a powerful interior stain blocker with no lingering odor. Ideal for use in offices, schools, dining areas, apartments and other areas where high odor levels are prohibitive. Use KILZ ODORLESS to block stains including water, tannin and smoke from tobacco and fire. Not recommended for floors.

SURFACE PREPARATION

 (The following steps are recommended for product performance)

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew, loose peeling paint, rust and all other foreign substances.
- If washing is necessary, use a non-soapy detergent or a TSP substitute, rinse well and allow to dry.
- Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface.
- Mold or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before priming. Note: KILZ® PREMIUM and KILZ 2® primers are recommended for mildew-prone surfaces.
- Masonry, Brick, Stucco and Plaster: KILZ ODORLESS primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ ODORLESS primer.
- While KILZ Adhesion Primer is formulated to bond without sanding, it is recommended that a small area be tested for adhesion prior to beginning the job.

WARNING If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

- Eye protection is recommended. Do not thin. Stir thoroughly before and occasionally during use. Apply using a brush, roller or sprayer. Any slight odor that is detected during application will diminish quickly.
- Use product when painting surface and air temperatures are between 35°F (2°C) and 90°F (32°C).
- Brush – High quality Nylon/Polyester
- Roller – High quality 3/8-1/2" nap on smooth surfaces or 1/2-3/4" nap on semi-rough or porous surfaces.
- Airless spray – .015 - .019 tip / 60 mesh filter
- Prime the entire surface to ensure a uniform appearance of the topcoat.
- Stainblocking: After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before topcoating the entire area. If bleeding continues, a longer dry time is needed before topcoating.
- Tinting: Up to 2 ounces of universal colorant per gallon. Tinting to a lighter shade than topcoat is recommended.

- Coverage: 300 - 400 sq. ft. (27.87 - 37 m²) per gallon depending on application method and surface porosity.
- Dry Time @ 77°F (25°C) / 50% RH: Touch 30 minutes, Recoat 1 hour.

CLEAN-UP & DISPOSAL

- Clean equipment and paint spatters with mineral spirits or acetone. Immediately after use, dispose of soiled rags and waste in a closed, water-filled container.
- Do not dispose of this product down a drain. Please consider donating any unused product.
- Please consider donating any unused product.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal information contact your local household refuse collection service.



WARNING Cancer and Reproductive Harm
www.P65Warnings.ca.gov

USE ONLY WITH ADEQUATE VENTILATION

VENTILATION REQUIRED To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross-ventilation by opening windows and doors during application and drying. CONTAINS PETROLEUM DISTILLATES. VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Follow respirator manufacturer's directions for respirator use. Causes eye, skin, nose and throat irritation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling and before smoking and eating. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. VAPORS MAY CAUSE FLASH FIRE. Keep away from sparks, heat and open flame. Do not smoke. Vapors are heavier than air, and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. Close container after each use. To avoid spontaneous combustion, soak soiled rags and waste immediately after use in a closed, water-filled metal container. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **FIRST AID:** If swallowed, do not induce vomiting. Call a physician immediately. If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY

LIMITED WARRANTY: For one year from the date of purchase, Masterchem Industries LLC warrants to the original residential consumer purchaser (1) that the product meets Masterchem Industries LLC's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. In the event that this product proves to be defective within one year from the date of purchase, Masterchem Industries LLC will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. For warranty service, call: 1-866-774-6371, or email: techservice@masterchem.com. Masterchem Industries LLC reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

* Depending on the surface texture, porosity and application method

**At 77°F (25°C), 50% RH. Longer dry time may be required in cooler temperatures and in higher humidity and stains



©2018 Masterchem Industries LLC
1-866-774-6371 • www.kilz.com
REV. 07/18 • 1004
MAX VOC <350 Grams/Litre (2.92 Pounds/Gallon)