



**ENERGY STAR® Certified**  
In all 50 States



**Exterior Doors**  
**Majestic Steel Door**  
**JEL-M-1 Low E**

**ENERGY PERFORMANCE RATINGS**

Product Description* Default Frame** Wood	U-Factor <sup>1</sup> /Solar Heat Gain Coefficient (SHGC)			
	Individual Option Number			
	1/4 Lite ≤410†	1/2 Lite ≤900†	3/4 Lite ≤1100†	Full Lite >1100†
Dual/Low E/Air/.75	0.29	0.32	0.34	0.37
	0.09	0.16	0.21	0.28
	02281-00001	02282-00001	02283-00001	02284-00001
Dual/Low E/Air/.75 With Grids	0.29	0.32	0.34	0.37
	0.08	0.14	0.19	0.25
	02293-00001	02294-00001	02295-00001	02296-00001
Dual/Low E/Air/.625	-	-	0.33	-
	-	-	0.21	-
	-	-	02361-00001	-
Dual/Low E/Air/.50 SDL	-	-	0.35	0.38
	-	-	0.17	0.22
	-	-	02864-00001	02865-00001
Dual/Low E/Air/.81 With Blinds	-	0.32	0.34	0.36
	-	0.09	0.12	0.15
	-	02455-00001	02456-00001	02457-00001
Triple/Low E/Air/.50/.81 With Blinds/Grids	-	0.29	-	0.32
	-	0.11	-	0.20
	-	02462-00001	-	02463-00001
<b>Flush</b> F02211-00001	<b>U-Factor<sup>1</sup></b>	<b>0.24</b>	<b>SHGC</b>	<b>0.01</b>
<b>Embossed</b> E2212-00001	<b>U-Factor<sup>1</sup></b>	<b>0.24</b>	<b>SHGC</b>	<b>0.01</b>

**Air Leakage - ≤0.30 cfm/ft<sup>2</sup>**

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.  
 \* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)  
 \*\* per NFRC 100 † square inches †btu/hr ft<sup>2</sup>F  
 \*\*\* Numbers below the performance ratings are referenced in the NFRC Certified Products Directory (e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)  
[www.nfrc.org](http://www.nfrc.org)