

TCL



UH Series Comfortable & Intelligent

Window Type Air Conditioner



Other Function

▶ ECO Energy-saving



By pressing ECO button AC will automatically run with suitable temperature to cut most energy than normal model.

▶ Filter-cleaning Reminder



The indicator for filter-clean reminder will be lighted after a 500 hours running time of the unit.

▶ 8-way Air Outlets



Brand new outlook and panel design, top discharge air outlet, 360° air supply with extra comfort.

* : Optional

Enjoy a good sleep*



▶ Sleep mode

This function ensures you to have a sweetly sleep, without suffering a under-cooling or over-heating experience at night.


Mode			5000 BTU	6000 BTU	8000 BTU	10000 BTU	12000 BTU
Control type			Mechanical	Remote Control	Remote Control	Remote Control	Remote Control
Power supply		Ph-V-Hz	1Ph, 115V~, 60Hz	1Ph, 115V~, 60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz
Cooling	RATED Capacity	Btu/h	5000	6000	8,000	10,000	12,000
	RATED EER	Btu/w.h,w/w	11.0	12.2	12.1	12.1	12.1
	RATED Input	W	451	492	661	826	992
	RATED Current	A	3.9	4.3	5.8	7.3	8.6
Power Cord Length		ft	6.5	6.5	6.5	8.2	8.2
Energy star			NO	Energystar	Energystar	Energystar	Energystar
Indoor noise level (Hi/Med/Lo)		dB(A)	55~/50	55/52/50	58/56/53	59/56/54	59/57/55
Outdoor noise level		dB(A)	60	63	64	66	66
Indoor air flow		CFM	135	141	206	282	270
Dimension(W*D*H)		mm	406x386x318	472x396x338	472x440x338	502x546x372	502x546x372
		inch	15.98x15.2x12.52	18.58x15.59x13.31	18.58x17.32x13.31	19.76x21.5x14.6	19.76x21.5x14.6
Packing (W*D*H) 1A package		mm	455x428x378	543x444x378	543x486x378	555x601x441	555x601x441
		inch	17.9x16.9x14.6	21.37x17.48x14.88	21.38x19.13x14.88	21.85x23.66x17.36	21.85x23.66x17.36
Net/Gross weight 1A package		Kg	18/20	20/23	23/26	29/33	33/37
		lbs	39.68/44.09	44.09/50.71	50.71/57.32	63.93/72.75	72.75/81.57
Loading quantity 20' /40' /40'HQ 1A package		Pieces	390/840/980	338/703/805	304/624/672	190/395/492	190/395/492

Mode			15000 BTU	18000 BTU	22000 BTU	24000 BTU
Control type			Remote Control	Remote Control	Remote Control	Remote Control
Power supply		Ph-V-Hz	1Ph, 115V, 60Hz	1Ph, 230/208V, 60Hz	1Ph, 230/208V, 60Hz	1Ph, 230/208V, 60Hz
Cooling	RATED Capacity	Btu/h	15,000	18000 /17600	22000/21600	24000/23600
	RATED EER	Btu/w.h,w/w	11.9	11.9	10.4	10.4
	RATED Input	W	1261	1513/1479	2116/2078	2308/2270
	RATED Current	A	11.0	7.1/6.6	10.2/9.3	11/10.1
Power Cord Length		ft	8.2	5.9	5.9	5.9
Energy star			Energystar	Energystar	Energystar	Energystar
Indoor noise level (Hi/Med/Lo)		dB(A)	56/53/52	57/54/52	60/58/56	60/58/56
Outdoor noise level		dB(A)	65	66	67	67
Indoor air flow		CFM	370	382	459	447
Dimension(W*D*H)		mm	600x645x455	600x645x455	671x682x476	671x682x476
		inch	23.6x25.4x17.9	23.6x25.4x17.9	26.4x26.9x18.7	26.4x26.9x18.7
Packing (W*D*H) 1A package		mm	652x754x505	652x754x505	740x780x513	740x780x513
		inch	25.67x29.69x19.88	25.67x29.69x19.88	29.2x30.7x20.2	29.2x30.7x20.2
Net/Gross weight 1A package		Kg	48/53	53/58	56/61	59/64
		lbs	105.82/116.85	116.85/127.87	123.46/134.48	130.07/141.10
Loading quantity 20' /40' /40'HQ 1A package		Pieces	96/216/270	96/216/270	84/188/235	84/188/235

Standard Features:



Optional Features:



Remark:

Specifications may be subject to change without prior notification. Final specifications please refer to technology specifications shared by the sales representatives.