TECHNICAL DATA SHEET



WET-LOOK SEALER

NO. 985 HIGH GLOSS

PRODUCT INFORMATION

BEHR PREMIUM® Wet-Look Sealer is a clear, non-yellowing, high solids, acrylic-based masonry sealer. It is formulated to seal, protect and beautify concrete and masonry surfaces with a high gloss, wet-look finish. BEHR PREMIUM Wet-Look Sealer No. 985 is also an excellent topcoat for paints and stains.

Unglazed Tile

Pavers

RECOMMENDED USES:

Properly prepared or previously coated interior or exterior, vertical or horizontal concrete, stone and tile surfaces, such as:

Concrete

Concrete Aggregate

- Brick
- Natural & Artificial Stone
- Stucco

PRODUCT SPECIFICATIONS:

Fill Level:

No. 985 Wet Look High Gloss 128 oz. No. 986 Wet Look Low Lustre 128 oz.

Gloss: 80-90 @ 60°

Resin Type: Acrylic

Weight per Gallon: 8.5 lbs.

% Solids by Volume: 25.4%

% Solids by Weight: 27.6%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 12-24 sec, #2 Zahn Cup

Recommended Film Thickness:

1st Coat Wet: 8.0 Dry: 2.0 mils @ 200 Sq. Ft./Gal. **2nd Coat Wet:** 3.5 Dry: 0.9 mils @ 450 Sq. Ft./Gal.

Coverage: 200-450 Sq. Ft./Gal. depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8"-1/2" nap

Airless Spray: At packaged consistency

Tip: .015"-.019"

Filter: 60 mesh

Thinning: Do Not Thin

Dry Time: @ 77° & 50% RH Longer dry time may be required in cooler temperatures and higher humidity. To Touch: 1 hour To Recoat: 4 hours Allow surface to dry 24-48 hours before subjecting surface to heavy foot traffic.

SURFACE PREPARATION:

Masonry: Concrete, Cut Masonry Units (CMUs), Split-Faced Block: New and Uncoated: All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using a product such as a muriatic acid or with mechanical means. Remove loose aggregate and debris.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS:

New or uncoated Masonry:

- All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.
- BEHR Concrete & Masonry Bonding Primer No. 880

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.



COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	AIM	99
CARB	YES	LEED v.3 (2009) [†]	YES
OTC	YES	MPI#	99
LADCO	YES		

[†]Please visit www.usgbc.org/LEED for additional details.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F 80°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24-48 hours.
- Allow 72 hours before repositioning furniture
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

Warning Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. If on skin: Wash with plenty of soap and water. If swallowed: Rinse mouth and get medical attention if you feel unwell.