

The L-Series



Shown with 3/8" and 1/4" Horizontal Filter Head



Shown with 3/8" and 1/4" Vertical Filter Head

A patented keyed design, and available auto shut-off make the L-Series unique.

For the past 40 years Omnipure Filter Company® has been revolutionizing the in-line filter industry. Meet our newest family member, the unique L-Series of filters. The L-Series was developed to offer our customers easy change-outs. Available with or without auto shut-off. The new L-Series offers a patented keyed design. A quarter turn design helps ensure product integrity.

Made of highly durable injection-molded polypropylene, the L-Series is constructed from 100% NSF (National Sanitation Foundation) certified materials. We offer a variety of standard media options including granular activated carbon (GAC) for taste and odor reduction, depth filtration media to address sand, grit and sediment problems that can clog or damage down line equipment and a special blend polyphosphate media designed to control scaling associated with hard water.

The L-Series can also be ordered with the premium OmnipureBlock™ media. This family of carbon blocks utilizes technology that optimizes surface area for better contaminant adsorption. Omnipure-Block™ is available in a high capacity ten micron activated carbon version and a water polishing, cysts-reducing one micron version. Carbon/scale inhibitor and carbon/lead reduction versions are available for your specific application needs.

The Best Inline Water Filters in the World ...Pure and Simple.



1-800-398-0833 USA

www.Omnipure.com

(208) 454-2597 • FAX: (208) 454-0026

1904 Industrial Way, Caldwell, Idaho, 83605

Filtration Media Reference Guide

The following list shows the various standard media configurations offered in the Omnipure L-Series family of filters.

The table on the reverse page presents the complete specifications for each media and the unique water conditions they address.

GRANULAR MEDIA

TASTE, ODOR AND CHLORINE REDUCTION
Granular Activated Carbon (GAC)

- L5_28
- L5_33
- L5_40
- L5_86

SCALE REDUCTION
GAC with Polyphosphate

- L5_86

BLOCK MEDIA
SEDIMENT REDUCTION
Polypropylene Depth Filtration

- L5_05

TASTE, ODOR AND CHLORINE REDUCTION
GAC Alone or with Speciality Media

- L5_20
- L5_21
- L5_15

CYST REDUCTION
One Micron GAC in Block Form

- L-20
- L-15

SCALE REDUCTION
GAC in Block Form with Polyphosphate

- L5_20-P
- L5_21-P
- L5_15-P

LEAD/CYST REDUCTION
One Micron GAC in Block Form with Lead-Specific Media

- L5_15

Specifications for the L-Series Inline Filters

Granular Media

Granular Activated Carbon
20x50 Mesh

- Taste, odor & chlorine reduction
- Pre R.O.
- Class 1 filtration media
- Maximum one-year service life
- Available in T/28 or T/36 Carbon

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life	Cubic Inch Volume
L5328/L5336	2.5"x6"	1250 Gallons	14.7
L5428/L5436	2.5"x8"	1500 Gallons	21.6
L5528/L5536	2.5"x10"	2000 Gallons	28.6
L5628/L5636	2.5"x12"	2500 Gallons	35.5
L5728/L5736	2.5"x14"	3000 Gallons	41.0

Block Media

Sediment Reduction

- Polypropylene depth filtration
- Reduction of sediment as small as 5 microns
- Protects downline equipment

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5305	2.5"x6"	1500 Gallons
L5405	2.5"x8"	2000 Gallons
L5505	2.5"x10"	2500 Gallons
L5605	2.5"x12"	3000 Gallons
L5705	2.5"x14"	3500 Gallons

Block GAC 1 Micron

- Taste, odor & chlorine reduction
- Cyst reduction

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5320	2.5"x6"	1500 Gallons
L5420	2.5"x8"	2000 Gallons
L5520	2.5"x10"	2500 Gallons
L5620	2.5"x12"	3000 Gallons
L5720	2.5"x14"	3500 Gallons

Block GAC 10 Micron

- Taste, odor & chlorine reduction
- Maximum one-year service life

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5321	2.5"x6"	1500 Gallons
L5421	2.5"x8"	2000 Gallons
L5521	2.5"x10"	2500 Gallons
L5621	2.5"x12"	3000 Gallons
L5721	2.5"x14"	3500 Gallons

Custom media options may be available under certain conditions. Call your Omnipure representative for complete details.

Speciality Block Media

Block GAC 1 Micron With Lead Specific Media

- Taste, odor & chlorine reduction
- Cyst reduction
- Lead reduction
- Maximum one year service life

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5315	2.5"x6"	750 Gallons
L5415	2.5"x8"	1000 Gallons
L5515	2.5"x10"	1250 Gallons
L5615	2.5"x12"	1500 Gallons
L5715	2.5"x14"	2000 Gallons

Block GAC 1 Micron With Scale Inhibitor

- GAC with polyphosphate
- Taste, odor & chlorine reduction
- Cyst reduction
- Scale inhibitor
- Ideal for equipment protection
- Maximum one-year service life

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5320-P	2.5"x6"	1500 Gallons
L5420-P	2.5"x8"	2000 Gallons
L5520-P	2.5"x10"	2500 Gallons
L5620-P	2.5"x12"	3000 Gallons
L5720-P	2.5"x14"	3500 Gallons

Block GAC 10 Micron With Scale Inhibitor

- Taste, odor & chlorine reduction
- Maximum one-year service life

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5321-P	2.5"x6"	1500 Gallons
L5421-P	2.5"x8"	2000 Gallons
L5521-P	2.5"x10"	2500 Gallons
L5621-P	2.5"x12"	3000 Gallons
L5721-P	2.5"x14"	3500 Gallons

Block GAC 1 Micron With Lead Specific and Scale Inhibitor

- Taste, odor & chlorine reduction
- Cyst reduction
- Lead reduction
- Inhibits scaling
- Maximum one-year service life

2 1/2" diameter filter bodies.

Model #	Body Size	Service Life
L5315-P	2.5"x6"	750 Gallons
L5415-P	2.5"x8"	1000 Gallons
L5515-P	2.5"x10"	1250 Gallons
L5615-P	2.5"x12"	1500 Gallons
L5715-P	2.5"x14"	2000 Gallons

Test Information: The L-Series filter housing and fittings have been tested for performance under NSF Standard 42. Tests included Hydrostatic Testing at 300 psig and Cycle Testing of 100,000 repetitions from 1 to 150 psig. Complete test results are available from Omnipure. Omnipure products have been tested and listed under Standard 42 for taste, odor and chlorine reduction; or particulate reduction; or have been materials certified. All filters should be installed on cold water lines only. NOTE: Activated carbon filters are not intended to be used where the water is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the unit.

Warranty Information: Omnipure Filter Company warrants that the products delivered will be free from any defects in workmanship or materials. Further, the warranty provided herein applies only when used within the products' specifications and service life, from the date of installation or 5 years from the date of manufacture whichever occurs first, beyond which time or use Omnipure is absolved of any and all liability for any use of the product. In the event of defect or non-conformity, buyer shall promptly notify Omnipure in writing, supplying proof of purchase dates, installation dates and will protect and retain the products for investigation, or Omnipure is absolved of any and all liability for any use of the product. There are no other warranties, either merchantability or fitness, either expressed or implied.



1-800-398-0833 USA

www.Omnipure.com

(208) 454-2597 • FAX: (208) 454-0026 • 1904 Industrial Way, Caldwell, Idaho, 83605

The Best Inline Water Filters in the World... Pure and Simple.