Top View Knockouts S= 1/2", 3/4", 1", 1-1/4",1-1/2" K G= 1/2", 3/4", 1" K 1.5 -1-1/2" HUB HOLE 3,8 **Front View** Left Side **Front View Front View** Side View View Interior **External Cover Inside Cover** -5/16' MOUNTING HOLE (3X) -3 CIRCUIT 70 AMP LOAD CENTER 50 AMP. BREAKER 2-POLE 20 AMP. BREAKER 1-POLE 6,9-6.5 2.2 12.6 12.5 13.9 14.0 12.6 14-50R −3.0- 50 AMP. RECEPTACLE--5-20R2GFI 20 AMP. GFI DUPLEX **Bottom View** Wire Range Size imagination at work ALUMINUM COPPER CONNECTOR 3.6 SOLID SOLID STRAND STRAND LINE 14-8 14-2 12-8 12-2 LOAD 14-10 14-10 GE RV EQUIP- 100A - MLO - UNMETERED - 50A&20A RECEPT NEUTRAL 14-8 12-8 12-2 3.3-SURFACE MOUNT- SINGLE SIDE - UNLIGHTED - N3R - G90

NEUTRAL

EQUIP GRND.

14-8

12-8

12-2

12-8

12-8

12-4

12-2

CAT NO

GE1LU502SS

Right

0

DWG DATE

05/13/2016

12.6

REV#

01