greenfiber

THIS IS GREENFIBER® BLOW-IN CELLULOSE INSULATION

Application Coverage Chart — DO NOT ADD WATER TO THIS PRODUCT — 19.05 lbs (8.64Kg) — **INS541LD**

R-Value at 75° F Mean Temperature Valor de resistincia termica (valor R) a 75® F de temperatura media	Minimum Thickness (Inches) Expesor minimo (en pulgadas)		Net Coverage (no adjustment for framing) Recumbrimiento neto (Sin compensacion para el entramado)			Gross Coverage (based on 2"x 6" framing on 16" centers) Recubrimiento Bruto (basado en armazón de 5.08 cm x 15.24 cm en centro de 40.64 cm)	
	Initial installed thickness Espesor inicial instalado	Settled Thickness Espesor assentado	Maximum Sq. Ft. per Bag Metros cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad minima de bolsas por 1,000 ples cuadrados	Minimum Weight per Sq. Ft. (lbs/sq. ft.) Peso minimopor pie cuadrado (lb/pie2)	Maximum Sq. Ft. per Bag. Metros cuadrado maximos por bolsa	Minimum Bags per 1,000Sq. Ft. Cantidad minima de bolsas por 100 metros cuadrados
R13	4.29	3.86	56.0	17.9	0.340	61.8	16.2
R19	6.19	5.57	36.7	27.2	0.519	40.0	25.0
R22	7.12	6.41	31.1	32.2	0.613	33.5	29.8
R25	8.05	7.25	26.8	37.2	0.710	28.7	34.9
R30	9.57	8.62	21.7	46.1	0.878	22.9	43.6
R38	11.97	10.77	16.4	61.1	1.164	17.1	58.5
R49	15.20	13.68	12.0	83.5	1.591	12.4	80.7
R60	18.37	16.53	9.3	108.1	2.059	9.5	105.0

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 19.05 LBS. USING THE GREENFIBER MONARCH BLOWING MACHINE. SETTINGS ARE NOT ADJUSTABLE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQUARE FEET AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF DESIRED R-VALUE. **THIS PRODUCT MUST BE INSTALLED DRY.** THIS COVERAGE CHART DOES NOT APPLY TO FLOOR APPLICATIONS. **DO NOT ADD WATER TO THIS PRODUCT.** JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 18.1 LBS.

Dry Dense Pack Sidewall Applications (3.5 pcf minimum installed density) DO NOT ADD WATER TO THIS PRODUCT

Thermal Resistance R-Value Valor de resistincia termica (valor R)	Framing Armazón	Installed Thickness Inches Espesor instalado (pulgados)	Minimum Wt. Per Sq. Ft. Peso minimopor pie cuadrado	Maximum Coverage Per Bag (not adjusted for framing) Recumbrimiento máximos por bolsa (Sin compensacion para el entramado)	Maximum Coverage per Bag (adjusted for framing) Recumbrimiento máximos por bolsa (con compensacion para el entramado) Square Feet per Bag	
					16" OC	24" OC
R13	2x4	3.5	1.02	18.7	20.6	19.9
R21	2x6	5.5	1.60	11.9	13.1	12.7

THE ABOVE COVERAGE CHART IS FOR **DRY APPLIED APPLICATIONS** ONLY AND IS BASED ON THE KRENDL KS200, WITH **MATERIAL APPLIED DRY.** FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC SPACING IS 9.375%; FOR 24" OC SPACING THE FRAMING FACTOR IS 6.25%.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:
This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____
Company Name: _____
Date: _____

Applicator's Signature: _____
Company Name: _____
Date: _____

FOR MORE INFORMATION CONTACT GREENFIBER:
800.228.0024
greenfiber.info@greenfiber.com

GreenFiber Corporate Office
2500 Distribution Street, Suite 200
Charlotte NC 28203
(p) 800.228.0024 (f) 704.379.0685
www.greenfiber.com

MANUFACTURING LOCATIONS:

Delphos, OH 45833
Debert, Nova Scotia
Norfolk, NE 68701
Chandler, AZ 85043
Salt Lake City, UT 84119
Tampa, FL 33605
Vars, Ontario
Waco, TX 76704
Wilkes-Barre, PA 18702

UL Classified.
see complete marking on back of packaging

MADE IN THE USA

Seal and Insulate with ENERGY STAR
LEARN MORE AT energystar.gov