# SAFETY DATA SHEET

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product Name:	PRIMETIME WB ACRYLIC PRIMER/STAIN BLOCKER
Product Code:	PT2000
Product Use:	Primer

#### Manufacturer

Strong Arm Group, LLC 1901 Avenue of the Stars Century City, CA 90067 PHONE 310-383-0055

#### 24 Hour Emergency Telephone Number

CHEMTEL (US):	(800)255-3924
CHEMTEL (International):	(813)248-0585

#### 2. HAZARDS IDENTIFICATION

Classification:	This material is considered hazardous by the 2012 OSHA Hazard	
Classification	Communication Standard (29 CFR 1910.1200)	
	Skin Sensitization: Category 1	
	Carcinogenicity: Category 2	
Signal Words		
Signal Word:	Warning	
Pictograms:		
Hazard	H317: May cause an allergic skin reaction	
Statements:	H351: Suspected of causing cancer	
Prevention	P201: Obtain special instructions before use	
Precautionary		
Statements:	understood	
	P261: Avoid breathing dust/fumes/gas/mist/vapors/spray	
	P272: Contaminated work clothing should not be allowed out of the	
	workplace	
	P280: Wear protective gloves/protective clothing/eye protection/face	
	protection	
	P281: Use personal protective equipment as required	
Response	P302+352: IF ON SKIN: Wash with plenty of water	
Precautionary		
Statements:	P333+313: If skin irritation or a rash occurs: Get medical	
Statements	advice/attention	
	P363: Wash contaminated clothing before reuse	
Storage	P405: Store locked up	
Precautionary		
Statements:		
	PE01. Dispace of container to an ensued wester dispaced whether	
Disposal	P501: Dispose of contents/container to an approved waste disposal plant	
Precautionary		
Statements:		
Hazards Not	May cause allergic skin reaction	
Otherwise		
Classified:		

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Calcium carbonate	10% to 20%	1317-65-3
Titanium dioxide	5% to 10%	13463-67-7
Zinc oxide	1% to 5%	1314-13-2
Propylene glycol	0% to 1%	57-55-6
Tri(ethylene glycol) bis(2-	0% to 1%	94-28-0
ethylhexanoate)		
Texanol ester alcohol	0% to 1%	25265-77-4
Kaolin	0% to 1%	1332-58-7
Carbendazim	0% to 1%	10605-21-7
4,4-dimethyloxazolidine	0% to 1%	51200-87-4
Silica gel	0% to 1%	112926-00-8

#### **4. FIRST AID MEASURES**

General Advice:	No hazards requiring special first aid measures
Eyes:	Remove contact lenses, if applicable. Flush eyes with water for at least
	10 minutes. Keep eyes wide open while flushing. Consult a physician if
	symptoms persist.
Skin:	
	water. Consult a physician if irritation persists. Wash contaminated
	clothing before re-use.
Ingestion:	
	large amounts of water. Consult a physician if symptoms persist.
Inhalation:	Move to fresh air. If not breathing, give artificial respiration and consult
	a physician immediately. Consult a physician if symptoms persist.
Most Important	May cause allergic skin reaction
Symptoms/Effects:	
Notes to Physician:	Treat symptomatically

#### **5. FIRE FIGHTING MEASURES**

Suitable	Use measures suitable to the circumstances and environment	
Extinguishing		
Media:		
Precautions for	Wear self-contained breathing apparatus and protective gear	
Firefighters:		
Specific Hazards:	Sealed containers may rupture if exposed to high temperatures	

#### 6. ACCIDENTAL RELEASE MEASURES

Personal	Use proper personal protective equipment. Avoid contact with skin,	
Precautions:	eyes, and clothing. Avoid breathing vapors.	
<b>Other Precautions:</b>	If safe to do so, prevent additional spillage	
Clean-Up Method:	Soak up with non-combustible absorbent material. Dispose of used	
_	absorbent in suitable containers.	

#### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, **Precautions:** mists, or dust. Wear respiratory equipment if ventilation is insufficient.

# StorageKeep container upright, properly labeled, tightly closed, and out of reachPrecautions:of children in a cool, dry, well-ventilated area.Incompatible<br/>Materials:None

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Calcium carbonate(1317-65-3)		
NIOSH TWA:	5 mg/m3 (respirable fraction)	10 mg/m3 (total dust)
OSHA PEL:	5 mg/m3 (respirable fraction)	15 mg/m3 (total dust)
Kaolin(1332-58-7)		
ACGIH TWA: 2 mg/m3	NIOSH TWA: 5 mg/m3	OSHA TWA: 5 mg/m3
Propylene glycol(57-55-6)		
WEEL TWA:	10 mg/m3	
Silica gel(112926-00-8)		
OSHA TWA:	6 mg/m3	20 mppcf
Titanium dioxide(13463-67-7)		
TWA:	ACGIH: 10 mg/m3	OSHA: 15 mg/m3
Zinc oxide(1314-13-2)		
ACGIH	TWA: 2 mg/m3	STEL: 10 mg/m3
NIOSH	TWA: 5 mg/m3	ST: 10 mg/m3
OSHA	TWA: 5 mg/m3	

Engineering	Maintain adequate ventilation to keep exposure to airborne
Measures:	contaminants at safe levels. Use explosion-proof equipment.
Hygiene Measures:	eyes, and clothing. Wash hands, forearms, and face after handling.
	Wash contaminated clothing before re-use.
Eye/Face	Safety glasses/goggles
Protection:	
Skin Protection:	Protective gloves and protective clothing
Respiratory	Respiratory equipment if ventilation is inadequate
Protection:	

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	White
Odor:	Little to none
Odor Threshold:	No information available
pH:	8.5-9.5
Melting Point (°F):	No information available
Boiling Point (°F):	No information available
Flash Point (°F):	Over 212° F
Flash Point	Pensky-Martens closed cup method
Method:	
Evaporation Rate:	No information available
Flammability	No information available
(Solid/Gas):	
Flammability	No information available
Limits:	
Vapor Pressure	No information available
(mm Hg):	
Vapor Density:	No information available

Specific Gravity:	No information available
% Solubility in	No information available
Water:	
Octanol/Water	No information available
Partition	
Coefficient:	
Auto-Ignition	No information available
Temperature (°F):	
Decomposition	No information available
Temperature (°F):	
Viscosity (KU):	95-100
Volatile Organic	40
Compounds (g/L):	

# **10. STABILITY AND REACTIVITY**

Reactivity:	Not applicable
Possibility of	None under normal conditions of use
Hazardous	
Reactions:	
Hazardous	None under normal conditions of use
Decomposition	
Products:	
Stability:	Stable under normal storage conditions
Incompatible	None
Materials:	
Conditions to	Freezing
Avoid:	

# **11. TOXICOLOGICAL INFORMATION**

Carbendazim(10605-21-7)	
Dermal LD50 (rabbit):	8500 mg/kg
Oral LD50 (rat):	6400 mg/kg
Propylene glycol(57-55-6)	
Dermal LD50 (rabbit):	20800 mg/kg
Intramuscular LD50 (rat)	14 g/kg
Intraperitoneal LD50 (mouse):	9718 mg/kg
Intraperitoneal LD50 (rat):	6660 mg/kg
Intravenous LD50 (dog):	26 g/kg
Intravenous LD50 (mouse):	6630 mg/kg
Intravenous LD50 (rabbit):	6500 mg/kg
Intravenous LD50 (rat):	6423 mg/kg
Oral LD50 (rat):	20000 mg/kg
Subcutaneous LD50 (mouse):	17370 mg/kg
Subcutaneous LD50 (rat):	22500 mg/kg
Texanol ester alcohol(25265-77-4)	
Dermal LD50 (rabbit):	15200 mg/kg
Oral LD50 (rat):	6500 mg/kg
Titanium dioxide(13463-67-7)	
Dermal LD50 (rabbit):	>10000 mg/kg
Oral LD50 (rat):	>10000 mg/kg
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)	
Dermal LD50 (rat):	>2000 mg/kg
Inhalation LC50 (rat, 4 hrs):	>2 mg/L

## Oral LD50 (rat): >2000 mg/kg

Zinc oxide(1314-13-2)

# Inhalation LC50 (mouse): 2500 mg/m3 Oral LD50 (mouse): 7950 mg/kg

Primary Routes of Exposure:	Eye contact, skin contact, inhalation
Acute Toxicity:	No information available

Exposure Effects	
Eye Contact:	Irritation
Skin Contact:	Irritation, drying
Inhalation:	Irritation of respiratory system
Ingestion:	Gastrointestinal irritation, diarrhea, nausea, vomiting
Target Organ	No information available
(Single Exposure):	
Target Organ	No information available
(Repeated	
Exposure):	
Sensitization:	No information available
Carcinogenicity:	No information available
Mutagenicity:	No information available
Reproductive	No information available
Toxicity:	
Other:	No information available

# **12. ECOLOGICAL INFORMATION**

Carbendazim(10605-21-7)		
BCF:	17	
Bioaccumulation (Ictalurus punctatus, 48 hrs):	45 μg/L	
EC50 (water flea, 48 hrs):	0.01-0.04 mg/L	
LC50 (rainbow trout, 96 hrs):	0.3 mg/L	
Propylene glycol(57-55-6)		
EC50 (water flea, 48 hrs):	>10000 mg/L	
Mortality NOEC (fathead minnow, 96 hrs):	52930 mg/L	
Mortality NOEC (water flea, 48 hrs):	13020 mg/L	
Texanol ester alcohol(25265-77-4)		
Biodegradability (aerobic, 28 days):		
Static EC50 (green algae, 72 hrs):		
Static EC50 (water flea, 48 hrs):	147.8 mg/L	
Static LC50 (fathead minnow, 96 hrs):	33 mg/L	
Titanium dioxide(13463-67-7)		
EC50 (water flea, 48 hrs):	>1000 mg/L	
LC50 (fish, 96 hrs):	>1000 mg/L	
Tri(ethylene glycol) bis(2-ethylhexanoate)(94-28-0)		
Biodegradability (aerobic, 28 days):	92%	
Static EC50 (green algae, 72 hrs):	>55.9 mg/L	
Static EC50 (water flea, 48 hrs):	38.7 mg/L	
Static LC50 (fathead minnow, 96 hrs):	>97 mg/L	
Zinc oxide(1314-13-2)		
EC50 (water flea, 48 hrs):	0.098 mg/L	
LC50 (rainbow trout, 96 hrs):	1.1 mg/L	

_	The environmental impact of this substance has not been fully evaluated
Effects:	No information available
Degradability:	
Bioaccumulative	No information available
Potential:	
Environmental	No information available
Mobility:	
Other Effects:	No information available

#### **13. DISPOSAL CONSIDERATIONS**

**Disposal Method:** Dispose of in accordance with federal, state, provincial, and local regulations.

#### **14. TRANSPORT INFORMATION**

DOT:	Not regulated
ICAO/IATA:	Not regulated
IMDG/IMO:	Not regulated

#### **15. REGULATORY INFORMATION**

TSCA (US):	Not all components are listed
DSL/NDSL	All components are listed or exempt
(Canada):	

311/312 Hazard	
<u>Categories</u>	
Fire:	No
Pressure	No
Generating:	
Reactivity:	No
Acute:	Yes
Chronic:	Yes

CERCLA Section 302	
Reportable Quantities:	Carbendazim, 10 lbs

#### SARA 313

This material does not contain any hazardous components exceeding the reporting thresholds established by SARA Title III, Section 313.


State Right-to-Know					
Chemical Name	CAS Number	MA	NJ	PA	RI
Calcium carbonate	1317-65-3	Х	Х	Х	Х
Titanium dioxide	13463-67-7	Х	Х	Х	Х
Zinc oxide	1314-13-2	Х	Х	Х	Х
Propylene glycol	57-55-6		Х	Х	Х
Tri(ethylene glycol) bis(2-					
ethylhexanoate)	94-28-0		Х	Х	
Texanol ester alcohol	25265-77-4		Х	Х	

Kaolin	1332-58-7	Х	Х	Х	Х
Carbendazim	10605-21-7		Х	Х	
4,4-dimethyloxazolidine	51200-87-4		Х	Х	
Silica gel	112926-00-8	Х	Х	Х	

California	This product does not contain any materials known to the state of
<b>Proposition 65:</b>	California to cause cancer or reproductive harm.
	Titanium dioxide and silicon dioxide (airborne, unbound particles of
	respirable size) are known to the state of California to cause cancer. This
	listing does not cover titanium dioxide or silicon dioxide when they
	remain bound within a product matrix.

## **16. OTHER INFORMATION**

HMIS RATING	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

<b>Revision Indicator:</b>	Revised 3/26/2019
Disclaimer:	The information contained in this Safety Data Sheet (SDS) is provided in
	good faith and is believed to be accurate as of the effective date listed.
	The information applies only to the product as provided and may not be
	valid if combined with other materials. No warranty is implied or given.
	The user is responsible for complying with all applicable laws and
	regulations.