

³⁰⁰ HEAVY DUTY

DUCT TAPE



Polyethylene Coated Cloth	
Natural Rubber	
N/A	
N/A	
Silver	
1.89 in x 30 yd x 10 mil	
(48 mm x 27.4 m x 254 μm)	

Applications

- Long-lasting seal, patch, and bond
- Household patch and repair
- Hanging and sealing poly sheeting materials
- General purpose abatement and contractor uses
- Quick fixes

Features	Benefits
Natural Rubber Adhesive	 High adhesion and holding power for both rough and smooth surfaces Good indoor/outdoor performance
Polyethylene Coated Cloth Backing	 Clean, crisp, straight tear Conforms well to irregular surfaces Resists twisting and curling
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method	
Total Thickness	10.0 mils	254 μm	ASTM D-1000	
Adhesion to Steel	46 oz/in	5.03 N/cm	PSTC-101	
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000	
Operating Temperature	40 to 200 °F	4 to 93 °C		
VOC Content	< 1 g/L			
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH				
Standard Shelf Life (at 25 °C): 36 months from date of manufacture				

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Parkway Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.nashuatape.com