

Project:

Fixture Type: Location:

Contact:

Images:

Ceiling mounted • Dry location listed PROGRESS LED

GAZE

Description:

P2554-1530K

Three-blade 60" Gaze ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. An opal white shade contains an 18W dimmable, 3000K LED module. Full range dimming and remote control with batteries is included. Reversible blades are included in a Polished Chrome finish.

Specifications:

- · Polished Chrome (-15) (plated)
- Steel construction
- Frosted lens
- 60" 3 Blade Fan with LED light
- · Oversized, textured die cast hanger ball reduces noise and wobble vibrations
- Mounting hardware is included
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- 54 in of wire supplied
- Whitewashed Grey/Cherry reversible blades, plywood construction
- 12 degree blade pitch
- Remote Control Included
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately. Triple capacitor speed control, manual reverse control
- Meets California Title 24 JA8-2016Airflow: 5902 CFM*
- Energy consumtion: 75 watts (excluding lights)*
- Airflow efficiency: 79 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1400/77.8 (LM-79)
ССТ	3000 K
CRI	90+
Life (hours)	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	Limited Lifetime warranty
Labels	UL Dry location listed
	Meets California Title 24 JA8-2016



Dimensions:

Diameter: 60" Height: 13-1/8"

