



WALLPAPER STRIPPER CONCENTRATE

DESCRIPTION AND USES

Zinsser® Wallpaper Stripper Concentrate is a biodegradable, non-toxic and non-staining wallpaper stripper. The concentrated formula will make up to 8 gallons of stripper, enough to remove the wallpaper from four 12'x24' rooms.

PRODUCTS

SKU	Description
338695	16 Fluid Ounces

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

PRODUCT APPLICATION (cont.)

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying.

APPLICATION

Mix 1-2 ounces (1 cap = 1 ounce) with 1 gallon of warm water. Use the mixed solution immediately. Apply the Wallpaper Stripper Concentrate solution with a garden-type sprayer, sponge or roller. Do not use a fine mist sprayer. Wait 2-5 minutes and scrape off with the Paper Scraper™. If the top layer does not peel off easily, score (10 holes per square inch) with Paper Tiger™ and apply more Wallpaper Stripper Concentrate. Allow it to penetrate for 2-5 additional minutes. Repeat the removal process and re-apply the stripper if necessary. To remove residual adhesive, re-apply the Wallpaper Stripper Concentrate solution, wait 2-5 minutes and scrape or sponge off. Rinse with clean water.

KEEP OUT OF REACH OF CHILDREN.

SPILLAGE

Open container carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly.

CLEAN-UP

Clean up tools and equipment with soap and water.

**TECHNICAL DATA****WALLPAPER STRIPPER CONCENTRATE****PHYSICAL PROPERTIES**

Physical Properties		WALLPAPER STRIPPER CONCENTRATE
Composition		Ethoxylated Alcohols, Propylene Glycol, Water
Weight	Per Gallon	8.4 lbs.
	Per Liter	1.01 kg
Volatile Organic Compounds		22 g/l
Practical Coverage		Varies with porosity of wallpaper
Shelf Life		5 years
Flash Point		200°F (93°C)
Caution!		Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.