SAFETY DATA SHEET



Date Issued: 10/24/2013

SDS No:48

Date Revised: 08/02/2018

Revision No: 4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: One Match Gelled Fire Starter

GENERAL USE: Fire starter **PRODUCT CODE:** 48

PRODUCT FORMULATION NAME: One Match Gelled Fire Starter

MANUFACTURER

Rutland Products 7 Crabtree Rd. Jacksonville, IL 62650

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 217-245-7810

Customer Service: 800-544-1307 **E-Mail:** sales@rutland.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical): (800) 222-1222 CHEMTREC (US Transportation): (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Flammable Liquids, Category 3 Eye Irritation, Category 2A

GHS LABEL





Flame

Exclamation mark

SIGNAL WORD: WARNING HAZARD STATEMENTS

H226: Flammable liquid and vapour. H319: Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash thoroughly after handling.

Response:

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
2-Propanol	Withheld, trade secret.	67-63-0
Ethyl Alcohol	Withheld, trade secret.	64-17-5
Cellulose, 2-Hydroxypropyl Methyl Ether	Withheld, trade secret.	9004-65-3

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. After initial flushing, remove contact lenses and continue flushing for at least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to mechanical action.

SKIN: Wash with plenty of water. Get medical attention if irritation develops or persists.

INGESTION: If Swallowed, do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Never give anything by mouth to an unconscious or convulsive person.

INHALATION: Remove to fresh air. Seek medical attention if cough or other symptoms develop or persist.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Flammable

GENERAL HAZARD: Flammable liquid and vapor! Dangerous fire hazard when exposed to heat or flame. Vapors can flow along

surfaces to distant ignition source and flash back.

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide or foam. Treat as a petroleum fire.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and carbon dioxide

EXPLOSION HAZARDS: None Expected.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus operated in pressure-demand mode, (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb spilled material and place in appropriate container for disposal.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin, and clothing.

HANDLING: Use with adequate ventilation. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep away from food and drinking water.

STORAGE: Store in a well-ventilated area suitable for flammable materials, away from incompatible substances. Protect from sources of ignition, heat or flame. Containers should be bonded and grounded for transfers to avoid static sparks.

STORAGE TEMPERATURE: Store in a cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
	EXPOSURE LIMITS				
Chemical Name	Туре		ppm	mg/m³	
2-Propanol	OSHA PEL	TWA	400	980	
	ACGIH TLV	TWA	200	490	
		STEL	400	960	
	Supplier OEL	TWA	NL	NL	
		STEL	NL	NL	
Ethyl Alcohol	OSHA PEL	TWA	1000	1900	
	ACGIH TLV	TWA	1000	1884	

ENGINEERING CONTROLS: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields. Chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent) are recommended.

SKIN: Wear protective clothing, including long sleeves and gloves, to prevent skin contact. Thoroughly wash clothing before reuse.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Gel
ODOR: Slight alcohol odor.

ODOR THRESHOLD: None known

pH: Not Available

FLASH POINT AND METHOD: 15.6°C (60°F) Closed cup.

FLAMMABLE LIMITS: Not Available

AUTOIGNITION TEMPERATURE: Not Available

VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: Not Available FREEZING POINT: Not Available MELTING POINT: Not Available

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Not Available

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Available

EVAPORATION RATE: Not Available

DENSITY: 7.9 Lbs/Gal SPECIFIC GRAVITY: 0.94 VISCOSITY: Not Available

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable product.

CONDITIONS TO AVOID: Heat, flame, other sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS: May include, and are not limited to: oxides of carbon

INCOMPATIBLE MATERIALS: Strong oxiding agents

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Chemical Name	IARC Status	
2-Propanol	3	

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Effect of low concentrations on aquatic life is unknown. May be dangerous if it enters water intakes. Notify local health and wildlife officials and operators of nearby water intakes in accordance with local, state and federal regulations.

ECOTOXICOLOGICAL INFORMATION: None known BIOACCUMULATION/ACCUMULATION: None known

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this product in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PRIMARY HAZARD CLASS/DIVISION: ORM-D

AIR (ICAO/IATA)

SHIPPING NAME: Ethanol solutions, 3, II

UN/NA NUMBER: 1170 VESSEL (IMO/IMDG)

SHIPPING NAME: Ethanol solutions, 3, II

UN/NA NUMBER: 1170

MARINE POLLUTANT #1: IMDG regulated
CANADA TRANSPORT OF DANGEROUS GOODS

PRIMARY HAZARD CLASS/DIVISION: Limited quantity

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Chronic health: Carcinogen Acute health: Adverse effect to target organs

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Vol. %	CAS
2-Propanol	Withheld, trade secret.	67-63-0

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-Propanol	67-63-0
Cellulose, 2-Hydroxypropyl Methyl Ether	9004-65-3

TSCA STATUS: All components are listed on the TSCA Inventory or are excluded or exempt.

CALIFORNIA PROPOSITION 65: WARNING:

Combustion of this product will result in the emission of carbon monoxide, soot, and other combustion by-products which are known by the State of California to cause cancer, birth defects, or other reproductive harm.

16. OTHER INFORMATION

PREPARED BY: Chad Stewart Date Revised: 08/02/2018

REVISION SUMMARY: This SDS replaces the 02/09/2016 SDS. Revised: Section 11: CARCINOGENICITY.

MANUFACTURER DISCLAIMER: The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to their circumstances.