



BEHR PRO® i300 Interior Eggshell

- Superior Hide and Coverage
- Great Flow & Leveling
- Zero VOC
 - This product, like most Zero VOC paints, emits very low amounts of VOCs.
 - Most emissions occur during painting and for 48 hours after. Some continue for two weeks or longer.
 - While VOC emissions are very low, sensitive groups such as babies and asthma/ allergy sufferers should minimize exposure.

No. PR330 White Base
No. PR333 Deep Base
No. PR334 Medium Base



1 Hr Dry Time
2 Hr Recoat Time



300-400 sq ft
Coverage per Gallon



Soap & Water
Clean-Up



Protect
from Freezing

FOR MEDIUM AND DEEP BASES – DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS

WHERE TO USE

Ideal for family rooms, living rooms, dining rooms, bedrooms, kid's rooms and hallways.

PREPARATION

All surfaces should be properly prepared and cleaned. Remove loose paint, wash off dirt and grease with detergent, rinse and allow to dry. Remove mildew stains with a mildew stain removing product. Scuff sand glossy surfaces and repair imperfections. Remove all dust with a damp cloth, allow to dry. Allow new concrete, plaster and masonry to cure for 30 days before painting.

PRIME

Prime new drywall with a product such as BEHR PREMIUM PLUS Interior All-In-One Primer & Sealer No. 75 or BEHR PREMIUM PLUS Multi-Surface Primer & Sealer No. 436. For stain-blocking, or over oil-based or glossy surfaces, use a product such as BEHR PREMIUM PLUS Interior All-In-One Primer & Sealer No. 75. For disaster restoration use a product such as water-base KILZ MAX® Primer or oil-base KILZ® Original Primer to permanently block severe stains and odors. After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, allow primer to dry a full 24 hours before top-coating.

***LIMITED WARRANTY** For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. In the event this product proves to be defective within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty.** Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133 ext.2. Behr Process Corporation reserves the right to inspect any and all applications of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2018 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) < 5 g/L • REV. 08/18

APPLICATION

Apply when air and surface temperatures are between 35-90° F (2-32° C). Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity. Use a high quality 3/8"-3/4" nap roller cover, nylon/polyester brush or airless sprayer (.015 - .021" spray tip, 60 mesh filter). Product is formulated for use at package consistency only. **DO NOT THIN.** Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time. After 2 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

DISPOSAL

For disposal of empty containers, unused paint and soiled rags, contact your household refuse collection service.

Visit behr.com for painting tips, project advice and color coordination with the ColorSmart by BEHR® Tool, or download the ColorSmart by BEHR App on your mobile device.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.



⚠ WARNING Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION IRRITANT MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.