# 7043 Park Avenue Tile

Dec 7, 2011



### Modular

Carpet tile has great flexibility in design by mixing colors and patterns you can create your own unique look. Tile is easy to handle and can be installed in stages minimizing renovation downtime. Maintenance or repairs are simple, if a spill occurs the affected tile can be removed and cleaned or simply replaced if damaged, rather than replacing the entire floor.



## Stain Proof – No Exceptions™

This carpet is stain proof - ideal for environments with frequent spills including corridors, rental units and hospitality spaces.



### 10 Year Warranties

- Commercial wear
- Commercial backing performance
- Stain Proof No Exceptions<sup>™</sup>

See full text for details.

Style 7043

01 Steel 05 Coffee 02 Graphite 06 Khaki 03 Biscuit

04 Acorn



Style	Park Avenue Tile	
CONSTRUCTION		
Fiber system Construction Backing system Pile weight Gauge Stitches Density	100% BCF Polypropyle Patterned multi-level loc EuroBac™ Modular 18 oz.y <sup>2</sup> 1/12 12.2 s.p.i. 5800	610 g/m <sup>2</sup> 47.2 rows/10 cm 48.0 stitches/10 cm
SUSTAINABILITY		
CRI/CCI air quality test Recycled content	Green Label Plus certified EuroBac™ Modular Backing - min. 20% pre-consumer	
PERFORMANCE		
Static generation Flammability	3.0 kV or less (AATCC 134) USA: Radiant Panel ASTM E648 – Class I (direct glue) Methenamine Pill – DOC FF 1-70 - passes	
Light fastness	L5	
Change on wet cleaning	Gray scale 5	
INSTALLATION		
Modular size (w x l) Packaging	19.7" x 19.7" 20 tiles/carton 37 lbs/carton 32 cartons/pallet	50 cm x 50 cm 6 y²/carton
Recommended adhesive	Pressure sensitive carpet tile adhesive	
Installation method	Quarter-turned, Brick, Ashlar or Monolithic	
WARRANTIES		
10 Year Warranties	Commercial wear	
(see full text for details)	Commercial backing performance Stain Proof – No Exceptions™	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. \*Percentages of recycled content are accurate at date of printing. The availability of these inputs may fluctuate.

E&OE.

## Dec 6, 2011

