

In-Wall Timer - Electronic Countdown Timer with Preset Times Item EC200WK / EAN-Code

| | | 30 M | IN | |
|---|---|------|----|--|
| • | D | 15 M | IN | |
| - | Ð | 10 M | IN | |
| - | Ð | 5 M | IN | |
| • | B | HOL | D | |
| | m | матс | | |

FEATURES

- Provides silent operation in time ranges from five minutes to 30 minutes
- ► Single-button time selection, with a HOLD mode, for continuous ON operation
- Replaces any standard wall switch
- ► Incandescent/fluorescent/CFL/LED compatible
- ► For use with decorator-style wall plate (not included
- ► Requires neutral connection

APPLICATIONS

- Bathroom Fans
- Spas
- Hot Tubs
- Storage Closets
- ► Garage Lights

| TE | CH | NIC | AL | DA. | ГА |
|----|----|-----|----|-----|----|
| | | | | | |

| General | |
|--------------------------------|--|
| Application Compatibilities | Incandescent |
| | Fluorescent |
| | Compact Fluorescent |
| | LED |
| Warranty | 1-year limited |
| Mechanism Type | Digital/Electrical |
| UPC Code | 078275143548 |
| Description | Electronic Countdown Timer with Preset Times |
| Model Number | EC200WK |
| Brand | Intermatic |
| Harmonized Code | 9107.00.4080 |
| Country of Origin (Intermatic) | CHINA |
| | |
| Mechanical Specifications | |
| Wall Plate Configurations | Single-Gang |
| | |
| Electrical Specifications | |
| Neutral Connection Required | True |
| Wiring Configurations | Single |
| Input Voltages | 120 VAC, 60 Hz |
| | |
| Material Specifications | |
| Includes Wall Plate | False |
| Color | White |
| Shipping Weight (kg) | 0.181 |
| Shipping Weight (lbs) | 0.4 |
| | |
| Control Specifications | |
| Hold Mode Included | True |
| | |

In-Wall Timer - - Electronic Countdown Timer with Preset Times



| Time Presets | 5 min |
|--|----------------------|
| | 10 min |
| | 15 min |
| | 30 min |
| Setpoint Program Count | 4 |
| Operation Mode | Countdown |
| Countdown Time | 30 min |
| | |
| Environmental Specifications | |
| Operating Temperature Min (°C) | 0 |
| Operating Temperature Min (°F) | 32 |
| Operating Temperature Max (°C) | 50 |
| Operating Temperature Max (°F) | 122 |
| California Proposition 65 | DEHP |
| | |
| Load Ratings | |
| Incandescent Load Ratings (Multi-Gang) | 8.3 A, 1000 W, 60 Hz |
| Electronic Ballast | 500 VA, 60 Hz |
| Resistive | 15 A, 1800 W, 60 Hz |
| Inductive | 8 A, 1000 VA, 60 Hz |
| Motor | 1/4 HP, 60 Hz |
| | |
| Standards and Certifications | |
| UL Certification | cULus |
| | |
| Dimensions | |
| Dimension | 42.93x104.8x36.5mm |
| Product Width (in) | 1.6875 |
| Product Height (in) | 4.125 |
| Product Height (mm) | 104.8 |
| Product Depth (mm) | 36.5 |
| Product Depth (in) | 1.4375 |
| Unit Carton Height (in) | 4.88 |
| Unit Carton Width (in) | 3 |
| Unit Carton Length (in) | 2.13 |
| | |