

- > Easy installation including MAGNA MOUNT<sup>™</sup> and screw mount.
- > Adjustable light angle and dimmable.
- > Amber White 2200K to Soft White 3000K CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free No Bulb Replacements
- > 5 Year Limited Warranty

## 32" Beam Adjustable Under Cabinet

1000lm | 120VAC | Model 53505111 | Part UC-32-10-930-SV-D



## **SPECIFICATIONS**

Model	53505111
Part	UC-32-10-930-SV-D
Description	32" Beam Adjustable Under Cabinet Light
Input Voltage (VAC)	120
Wattage	15
Dimmability	Triac
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	1000
CCT <sup>3</sup>	2200-3000K
Location Rating	UL Damp
CRI⁴	90
Beam Angle	118
Operating Temperature	Min -4°F (-20° C) Max 113°F  (45° C)
Power Factor	>0.9
R9	64
DUV	-0.00422
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance

2 Thermally stable typical lumens (±10%) 3 Thermally stable CCT (±10%)

4 Color rendering index/Ra



TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754





## 32" Beam Adjustable Under Cabinet

1000lm | 120VAC | Model 53505111 | Part UC-32-10-930-SV-D

## **SHIPPING INFORMATION**

Model	53505111
Part	UC-32-10-930-SV-D
UPC	849489009261
Product Dimensions (L x W x H in.)	32 x 2 13/32" x 1 3/32"
Product Dimensions (L x W x H cm.)	81.3 x 6.1 x 2.8
Product Weight (Ibs.)	2.12
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (Ibs)	N/A
Master Carton Quantity	5
Master Carton Bar Code	50849489009266
Master Carton Dimensions (L x W x H in.)	3' 3 11/64"× 9 11/16" × 3 37/64"
Master Carton Dimensions (L x W x H cm.)	99.5 x 24.6 x 9.1
Master Carton Weight (Ibs)	13.97
Pallet Quantity	625

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754