

**BEHR**  
**MARQUEE**

**CEILING PAINT**  
**NO. 1458 PURE WHITE**



**PRODUCT INFORMATION**

BEHR MARQUEE® Ceiling Paint offers one-coat-hide guarantee and stain resistance plus an Exclusive MARQUEE Interior One-Coat Color Collection (colors denoted with a “u.”)

**RECOMMENDED USES:**

On properly prepared coated and uncoated interior ceilings:  
• Drywall/Gypsum Board • Plasterboard

• Cured plaster

**PRODUCT SPECIFICATIONS:**

**Tint Bases/Max Tint Load:**

Pure White No. 1458 126 oz / 4 oz

**Gloss:** <3 @ 60°

**Sheen:** <3 @ 85°

**Resin Type:** 100% Acrylic

**Weight per Gallon:** 13.0 lbs.

**% Solids by Volume:** 46 ± 2%

**% Solids by Weight:** 63 ± 2%

**VOC:** <50 g/L

**Flash Point:** N/A

**Viscosity:** 105-120 KU

**Recommended Film Thickness:**

Wet: 4.0 Dry: 1.8 mils @ 400 sq ft/gal

**Coverage:** Up to 400 sq ft/gal depending on application method and substrate porosity. Does not include the loss of material from spraying.

**APPLICATION:**

**Brush:** Nylon/polyester

**Roller:** 3/8" - 1/2" nap

**Airless Spray:** At packaged consistency

**Tip:** .015" - .019"

**Filter:** 60 mesh

**Thinning:** (If required) No more than 1/2 pint of water per gallon.

**Dry Time:** @ 77° & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

**To Touch:** 1 hour

**To Recoat:** 2 hours

**Full Cure:** 4 weeks

**SURFACE PREPARATION:**

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

**New Drywall:** All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating. **Previously Painted Drywall:** Remove all loose and peeling paint and all

other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material. Let dry completely and sand smooth.

Remove all dust with a wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

**New Plaster:** New plaster should be thoroughly dried out and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize. **Previously Painted Plaster:** Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a tack or wiping cloth. Fill all gaps with a 100% acrylic, siliconized, paintable caulking, and allow to completely dry prior to coating. **Glossy Surfaces:** For maximum adhesion, sand the surface thoroughly before coating.

**Stain-Blocking:** After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time may be needed before top-coating.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

COMPLIES WITH THE BELOW AS OF 6/1/2017			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) <sup>†</sup>	YES

This coating conforms to USDA regulatory requirements for incidental food-contact materials intended for use on surfaces not in direct contact with food, such as walls, floors and ceilings.

<sup>†</sup>Please visit [www.usgbc.org/LEED](http://www.usgbc.org/LEED) for additional details.

**RECOMMENDED PRIMER/SYSTEMS:**

**PROPERLY PREPARED NEW SURFACES:**

**Drywall, Plaster, Masonry and Wood:**

• 2 coats is the minimum required for new or uncoated surfaces and surfaces with severe tannin and stains.

**PREVIOUSLY PAINTED SURFACES:**

• Use a full coat, or spot prime repaired surfaces with heavy stains, including tannin, with BEHR MARQUEE® Interior Paint.

**CLEAN UP:**

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

**CAUTIONS/LIMITATIONS:**

- Protect from freezing.
- Do not use on floors.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- Allow four weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.



BEHR  
MARQUEE

CEILING PAINT  
NO. 1458 PURE WHITE

**GENERAL INFORMATION:**



**Warning!** Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, and eye & face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.

