



# DYC7200

## CLEAR PAVER SEALER

### 7200 Data Sheet

#### CHARACTERISTICS

Dyco 7200 Cement Paver Sealer is a solvent acrylic, non-yellowing clear sealer for sealing non-sealed or coated pavers. Paver Sealer gives a wet-look and enhances the true color of the paver. How to determine if your pavers have been sealed with a latex water base sealer: Test the surfaces by pouring a small amount of water on the surface. If it penetrates quickly, the surface is porous and ready for 7200 Paver Sealer. If it does NOT and takes 2-20 minutes to penetrate, then DO NOT apply 7200 Paver Sealer.

#### RECOMMENDED USES

- Concrete Cement Pavers

#### FEATURES/BENEFITS

- Resists Tire Marking
- Resists Mildew
- Resists Cracking & Peeling
- Easy To Apply

#### SPECIAL NOTES

DANGER! EXTREMELY FLAMMABLE! CONTAINS XYLENE!  
See instructions on reverse side or label for details.

#### FOR ADDITIONAL INFORMATION

See MSDS or call toll-free 1-800-282-7901.

#### TECHNICAL DATA

Vehicle Type ..... Solvent Acrylic  
 Finish/Sheen ..... Gloss  
 Solids by Weight ..... 25.84%  
 Solids by Volume ..... 21.56%  
 Viscosity ..... #2 Zahn- 19 Sec.  
 VOC <sup>(less exempt solvents)</sup> ..... Less than 600 g/L.  
 Weight per Gallon ..... 7.68 LBS

#### COVERAGE

100-125 S.F./Gal.  
(Actual coverage may vary depending on type of substrate, and application method.)

#### KEY ATTRIBUTES

Application Temperatures: 50 - 110°F (10 - 43.33°C)  
 Application Tools: Brush, Roller, or Spray  
 Dry Times: Touch - 1 Hour, Foot Traffic – 2 Hour, Vehicle Traffic 72 Hour  
 (Dry Time Based on 77°F (25°C), 50% RH)  
 Thinner: Do not thin.  
 Clean Up: Cleans with Xylene solvents.

#### PHYSICAL PROPERTIES

Mildew Resistance .. Excellent  
 Flash Point ..... 81°F (27.2°C)





# DYC7200

## CLEAR PAVER SEALER

### 7200 Precautions & Application Guide

**PRECAUTION:** Do not freeze. Wear protective clothing, gloves and eyewear during application and cleanup of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperature above 100°F (37.77°C). Do not use in drinking water or food systems. DO NOT apply in temperatures below 50° F to a damp surface. On excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly, causing trapped vapors to bubble. If this occurs, we recommend application during a cooler time of day. Keep away from children. Keep away from direct heat and open flame. This product is not recommended for wood or Bominite surfaces. Close container after each use.

**MIXING:** Stir from bottom with vigorous strokes. Do not add oil or other paints.

**APPLICATION:** On bare pavers, the surface must be clean, dry, and free of all grease, oil, and dirt. If necessary, clean with a good degreaser and brush, and/or pressure wash for best results. When applying use a short nap solvent resistant roller cover (3/8" Nap). Apply evenly, and do not leave puddles or roller marks. Dip roller cover into the Paver Sealer and roll forward allowing wet sealer in front of the roller to penetrate the deeper crevices around the paver. Do not dry roll, keep plenty of sealer on roller cover. Do not apply to areas where standing water is evident. If there has been a skid-texture added to the sealer, this product may perform properly but all precautions must be taken. On bare concrete, the surface must be clean and dry.

**TOOLS:** Brush, roll, or spray.

**DRY TIME:** Surface will be tack free in 1 hour, ready for foot traffic in 2 hours and vehicle traffic in 72 hours.

**COVERAGE:** Recommended coverage is 100-125 sq. ft. per gallon. Actual coverage may vary depending on substrate and application method.

Only one coat is recommended.

**THINNING:** Do not thin.

**LIMITATIONS:** Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to DYCO quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or other consequential damages are hereby excluded.

#### CAUTION!

**CONTAINS XYLENE. HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.**

To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave area.

**CALIF. PROP. 65 • CHEMICAL WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

**FIRST AID:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Material Safety Data Sheet available upon request.

