



# ADVANCED DECKOVER® SMOOTH COATING

NO. 5000

## PRODUCT INFORMATION

BEHR PREMIUM ADVANCED DECKOVER® Smooth is an innovative solid color coating that resurfaces properly prepared weathered wood and concrete. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. ADVANCED DECKOVER Smooth is designed to conceal splinters & cracks up to 1/4" and creates a smooth, slip-resistant finish. Our latest formula now features even better adhesion and cracking resistance. It can be tinted to 54 solid custom colors.

## RECOMMENDED USES:

Recommended for properly prepared interior and exterior weathered or cracked horizontal and vertical surfaces such as:

- Wood
- Composite
- Concrete

Do not use on drivable surfaces such as garage floors and driveways.

## PRODUCT SPECIFICATIONS:

### Tint Bases/Max Tint Load:

No. 5000 Deep Base 116 fl oz / 14 fl oz

**Resin Type:** 100% Acrylic

**Weight per Gallon:** 11.45 lb

**% Solids by Volume:** 51% ± 2%

**% Solids by Weight:** 65% ± 2%

**VOC:** < 50 g/L

**Flash Point:** N/A

**Viscosity:** 95 – 105 KU (Paste Paddle)

### Recommended Film Thickness:

Wet: 10.7 mils / Dry: 5.5 mils per coat  
(Total Dry Film Thickness: 10.9 mils for 2 coats)

**Coverage:** 75 sq ft/gal in two coats (required)

## APPLICATION:

**Brush:** Nylon/polyester

**Roller:** 1/4" – 1/2" nap roller cover, depending on surface texture

**Airless Spray:** At packaged consistency

**Tip:** .027" – .035"

**Filter:** Remove

**Fluid Pressure:** 2,400 – 3,200 psi

- For nail holes and cracks up to 1/4", completely fill in with ADVANCED DECKOVER Coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nailholes and cracks require additional filling.
- Use pressure while rolling and apply a generous, even coat using a 1/2" nap roller. For a smoother texture, use a brush or thinner nap roller (i.e., 1/4")
- For optimum performance, film uniformity, leveling, adhesion and crack filling, a second coat MUST be applied.
- Maintain a wet edge when applying.

- For best results, coat all accessible board ends.
- Airless spray is recommended for experienced applicators only. When spraying vertical surfaces, apply a very thin coat (one pass only) at a spread rate of 400 sq ft/gal and do not back brush/roll. When spraying horizontal surfaces, follow the standard spread rate of 75 sq ft/gal.

**Thinning:** DO NOT THIN. Product is formulated for use at package consistency only.

**Dry Time:** 77°F & 50% RH

**To Touch:** 4 hours

**To Recoat:** 4 – 6 hours

**Light Foot Traffic:** 24 – 48 hours

**Full Cure:** 72 hours

Dry times are temperature, humidity, and film thickness dependent.

## SURFACE PREPARATION:

### The following steps and products are required:

All surfaces must be clean, sound, dry and free of any dirt, oil, and grease before application.

**Wood Surfaces:** Replace rotting or unstable boards and remove loose splinters. Remove mildew stains, dirt, oil and grease with a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner prior to application. Use a product such as BEHR PREMIUM No. 64 Wood Stain & Finish Stripper (must be followed by No. 63) to remove all loose wood fibers, peeling paint/stain or deteriorated coatings prior to application of DECKOVER®. On new wood, use No. 63 to remove mill glaze and open the pores of the wood.

**Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure up to 8 psi. Allow new surfaces to cure for 30 days. Clean and etch surface using a product such as a muriatic acid to achieve a textured profile similar to 150 grit sandpaper. Follow all label instructions. If the previous coating is failing or peeling, use a paint stripper to remove old coating.

COMPLIES WITH THE BELOW AS OF 6/1/2020			
SCAQMD	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC Phase II	YES	MPI#	127
OTC	YES		

After etching or using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. If needed, lightly sand to remove any wood fibers/fuzz.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## CLEAN UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.





## ADVANCED DECKOVER® SMOOTH COATING

### NO. 5000

#### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Intermix multiple containers to ensure color uniformity.
- Stir product occasionally throughout application.
- While this product provides a slip resistant finish, surfaces may still become slippery when wet.
- Do not use on drivable surfaces such as garage floors and driveways.
- DO NOT USE ON wood surfaces that are in direct contact with the ground or exposed to excessive ground moisture.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Temperatures above 90°F can cause the paint to dry too fast, whereas temperatures below 50°F can inhibit proper film formation.
- Do not use if rain is expected within 24 hours and avoid painting if humidity is expected to be greater than 80%.
- Avoid applying paint in direct sunlight or hot surfaces.
- Test product for color on a small hidden area before proceeding.
- A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.
- Shelf life under normal conditions is two years unopened.

#### GENERAL INFORMATION:

**CAUTION! IRRITANT. HARMFUL IF SWALLOWED.**  
CONTAINS: ACRYLIC RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY**