



# EcoTouch® PINK® Fiberglas™ Insulation with PureFiber® Technology

Contractor \_\_\_\_\_

Project \_\_\_\_\_

Owens Corning® EcoTouch® Insulation with PureFiber® Technology is flexible light density insulation with a variety of facings and uses for thermal and acoustic benefits. EcoTouch® Insulation is dimensionally stable and will not slump within the cavity. Due to its inorganic fibers, EcoTouch® Insulation is not a food source for mold, it will not rot or mildew and it is not corrosive to steel, copper or aluminum.

ASTM C665 Classification	Description
Type I	Blankets without membrane coverings.
Type II	Blankets with nonreflective membrane coverings:
Class A	Membrane-faced surface flame spread of 25 or less.
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm <sup>2</sup> (0.11 Btu/ft <sup>2</sup> xs) or greater.
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder.
Category 2	Membrane is not a vapor retarder.
Type III	Blankets with reflective membrane coverings:
Class A	Membrane-faced surface flame spread of 25 or less.
Class B	Membrane-faced surface with critical radiant flux of 0.12 W/cm <sup>2</sup> (0.11 Btu/ft <sup>2</sup> xs) or greater.
Class C	Membrane-faced surface not rated for flame propagation resistance
Category 1	Membrane is a vapor retarder.
Category 2	Membrane is not a vapor retarder.

### Unfaced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- UL File #BKNV 3576 (Fire rated assemblies)

- |                                   |                                     |
|-----------------------------------|-------------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-25 8"    |
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30C 8¼"  |
| <input type="checkbox"/> R-15 3½" | <input type="checkbox"/> R-30 9½"   |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-38C 10¼" |
| <input type="checkbox"/> R-20 5½" | <input type="checkbox"/> R-38 12"   |
| <input type="checkbox"/> R-21 5½" | <input type="checkbox"/> R-49 14"   |
| <input type="checkbox"/> R-22 6¾" |                                     |

### Kraft Faced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type II, Class C
- ASTM E84 Not rated
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E90, E413 (3½", 6¼")
- ASTM E96 Perm Rating -1 perm

- |                                   |                                     |
|-----------------------------------|-------------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-22 6¾"   |
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30C 8¼"  |
| <input type="checkbox"/> R-15 3½" | <input type="checkbox"/> R-30 9½"   |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-38C 10¼" |
| <input type="checkbox"/> R-20 5½" | <input type="checkbox"/> R-38 12"   |
| <input type="checkbox"/> R-21 5½" | <input type="checkbox"/> R-49 14"   |

### Unfaced—EcoTouch® Sound Attenuation Batts

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in metal framing to allow for friction fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM E136 Non-Combustible
- ASTM C518
- ASTM E90, E413 (2½", 3½")
- UL File #BKNV 3576 (Fire rated assemblies)

- |                                  |                                   |
|----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-8 2½" | <input type="checkbox"/> R-11 3½" |
|----------------------------------|-----------------------------------|

### FSK or PSK E Faced—EcoTouch® Flame Spread 25 Batt Insulation

Fiberglass insulation with facing that can be left exposed that is designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood or metal framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type II (PSK) or Type III (FSK), Class A
- ASTM E84 <25/<50
- ASTM C1338 Mold/mildew resistant
- ASTM C518
- ASTM E96 Perm Rating -.5 perm
- UL File #BKNV 3576 (Fire rated assemblies)

#### FSK

- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-38½"   |
| <input type="checkbox"/> R-21 5½" |                                   |

#### PSK-E

- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-19 6¼" | <input type="checkbox"/> R-30 9½" |
|-----------------------------------|-----------------------------------|

#### FSK-E

- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-19 6¼" |                                   |

## Foil Faced—EcoTouch® Batt Insulation

Fiberglass insulation designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in metal framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type III, Class B and C
  - ASTM E84 75/150
  - ASTM C1338 Mold/mildew resistant
  - ASTM C518
  - ASTM E90, E413 (3½", 6¼")
  - ASTM E96 Perm Rating 0.5
- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-19 6¼" |
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-30 9½" |
| <input type="checkbox"/> R-15 3½" |                                   |

## Kraft Faced— PROPINK® FastBatt™ Insulation

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of wall and roof/ceiling assemblies. Fits tightly in wood framing to allow for friction fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type II, Class C
  - ASTM E84 not rated
  - ASTM C1338 Mold/mildew resistant
  - ASTM C518
  - ASTM E90, E413 (3½", 6¼")
  - ASTM E96 Perm Rating -1 perm
- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-13 3½" | <input type="checkbox"/> R-19 6¼" |
| <input type="checkbox"/> R-15 3½" | <input type="checkbox"/> R-21 5½" |

## Unfaced— EcoTouch® Sonobatts® Insulation

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of suspended ceiling assemblies. 24" x 48" to fit on top of most drop in ceiling tiles.

- ASTM C665 Type I
  - ASTM E84 <25/<50
  - ASTM C1338 Mold/mildew resistant
  - ASTM E136 Non-Combustible
  - ASTM C518
  - ASTM E90, E413 (3½", 6¼")
  - UL File #BKNV 3576 (Fire rated assemblies)
- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-19 6¼" |
|-----------------------------------|-----------------------------------|

## Kraft Faced— EcoTouch® Sonobatts® Insulation

Fiberglass insulation with PureFiber® Technology designed to improve thermal and acoustic performance of suspended ceiling assemblies. 24" x 48" to fit on top of most drop in ceiling tile.

- ASTM C665 Type II, Class C
  - ASTM E84 Not Rated
  - ASTM C1338 Mold/mildew resistant
  - ASTM E96 perm Rating -1 perm
  - ASTM C518
  - ASTM E90, E413
- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> R-11 3½" | <input type="checkbox"/> R-19 6¼" |
| <input type="checkbox"/> R-13 3½" |                                   |

## Unfaced—EcoTouch® QuietZone® Acoustic Batt Insulation

Fiberglass insulation designed to improve acoustic performance of wall assemblies. Fits tightly in wood framing to allow for friction fit installation. Different sizes available to fit specific applications.

- ASTM C665 Type I
  - ASTM E84 <25/<50
  - ASTM C1338 Mold/mildew resistant
  - ASTM E136 Non-Combustible
  - ASTM E90, E413 (3½", 5½")
  - UL File #BKNV 3576 (Fire rated assemblies)
- |                              |                              |
|------------------------------|------------------------------|
| <input type="checkbox"/> 3½" | <input type="checkbox"/> 5½" |
|------------------------------|------------------------------|

## Kraft Faced—EcoTouch® QuietZone® Acoustic Batt Insulation

Fiberglass insulation designed to improve acoustic performance of wall assemblies. Fits tightly in wood framing to allow for friction fit installation. Flanges can be inset or face stapled as needed. Different sizes available to fit specific applications.

- ASTM C665 Type II, Class C
  - ASTM E84 Not Rated
  - ASTM C1338 Mold/mildew resistant
  - ASTM E90, E413 (3½")
  - ASTM E96 Perm Rating -1 perm
  - UL File #BKNV 3576 (Fire rated assemblies)
- |                              |
|------------------------------|
| <input type="checkbox"/> 3½" |
|------------------------------|

Visit [www.ocbuildingspec.com](http://www.ocbuildingspec.com) to access a variety of learning, application and design resources to build your spec. For current product availability, please contact an Owens Corning Distributor or Area Sales Manager.

## Certifications and Sustainable Features

- Unfaced EcoTouch® Insulation and Kraft-Faced EcoTouch® Insulation are participating in Declare and are Living Building Challenge Compliant
- Certified by SCS Global Services to contain an average of 55% recycled glass content, 18% pre-consumer and 37% post-consumer
- GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg)
- Environmental Product Declaration (EPD) has been certified by UL Environment
- Material Health Certificate from Cradle to Cradle Products Innovation Institute



## Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobalservices.com](http://www.SCSglobalservices.com).



OWENS CORNING INSULATING SYSTEMS, LLC  
ONE OWENS CORNING PARKWAY  
TOLEDO, OHIO, USA 43659

1-800-GET-PINK®  
[www.owenscorning.com](http://www.owenscorning.com)

Pub. No. 10019001-1. Printed in U.S.A. July 2018.  
THE PINK PANTHER™ & © 1964–2018 Metro-Goldwyn-Mayer Studios Inc.  
All Rights Reserved. The color PINK is a registered trademark of Owens Corning.  
© 2018 Owens Corning. All Rights Reserved.

