

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Name** Lithium-ion Battery

### Other means of identification

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** LITHIUM ION BATTERIES

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Supplier Name** JiangSu Tenpower Lithium Co.,Ltd.  
**Supplier Address** Nangang Rd, Emerging industries Zone, Jinfeng Town, Zhangjiagang City, Jiangsu, 215636  
 China  
**Supplier Phone Number** Phone: +860512-80159851  
 Fax: +860512-80159851  
 Contact Phone +860512-80159851  
**Supplier Email** [haiyan.ai@tenpower.cc](mailto:haiyan.ai@tenpower.cc)  
**Emergency telephone number**

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Acute toxicity(Oral)	Category 4
Acute Inhalation(Gases)	Category 4
Acute Inhalation(Dusts/Mists)	Category 4
Reproductive Toxicity	Category 1B

### GHS Label elements, including precautionary statements

**Emergency Overview****Signal word****Danger****Hazard Statements**

Cause skin irritation  
 Harmful in contact with skin  
 Harmful if swallowed  
 Harmful inhaled  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause cancer  
 May damage fertility or the unborn child  
 Cause damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance.  
 This is a battery. In case of rupture: the above hazards exist.

**Appearance** Silver**Physical State** Solid**Odor** Odorless**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wear eye/face protection

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash before reuse  
 If skin irritation or rash occurs: Get medical advice/attention

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity****Other information**

Very toxic to aquatic life with long lasting effects

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

#### Interactions with Other Chemicals

No information available

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight %
Lithium Cobalt Oxide	12190-79-3	37.9
Cobalt(II) oxide	1307-96-6	7.4
Manganese dioxide	1313-13-9	15.4
Nickel oxide	1313-99-1	3.3
Carbon	7440-44-0	13
Polyvinylidene Fluoride (PVDF)	24937-79-9	1.6
Aluminum foil	7429-90-5	4
Copper	7440-50-8	8
Aluminum	7429-90-5	6
Ethylene carbonate	96-49-1	1.2
Diethyl carbonate	105-58-8	1.1
Dimethyl carbonate	616-38-6	1.1

### 4. FIRST AID MEASURES

#### First aid measures

##### General Advice

First aid is upon rupture of sealed battery. Show this safety data sheet to the doctor in attendance

##### **Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area

##### **Skin Contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.

##### **Inhalation**

Remove to fresh air. If symptoms persist, call a physician. Get medical attention immediately if symptoms occur.

##### **Ingestion**

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

##### **Self-protection of the first aider**

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8)

#### Most important symptoms and effects, both acute and delayed

##### **Most Important Symptoms and Effects**

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

#### Indication of any immediate medical attention and special treatment needed

##### **Notes to Physician**

May cause sensitization of susceptible persons. Treat symptomatically

### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

CAUTION: Use of water spray when fighting fire may be inefficient

**Specific Hazards Arising from the Chemical**

Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous Combustion Products**

Carbon Oxides

**Explosion Data****Sensitivity to Mechanical Impact** No.**Sensitivity to Static Discharge** No.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand,MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Personal Precautions</b>	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.
<b>Other Information</b>	Refer to protective measures listed in Sections 7 and 8
<b><u>Environmental Precautions</u></b>	
<b>Environmental Precautions</b>	Refer to protective measures listed in Sections 7 and 8.
<b>Methods for cleaning up</b>	Pick up and transfer to properly labeled containers
<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for cleaning up</b>	Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE****Precautions for safe handling**

<b>Handling</b>	In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing.
-----------------	---

**Conditions for safe storage, including any incompatibilities**

<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place.
<b>Incompatible Products</b>	Strong acids. Strong oxidizing agents. Strong bases.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>		
Cobalt(II) oxide	TWA: 0.02 mg/m <sup>3</sup> Co		

1307-96-6			
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m <sup>3</sup> Mn TWA: 0.1 mg/m <sup>3</sup> Mn	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn TWA: 1 mg/m <sup>3</sup> Mn STEL: 3 mg/m <sup>3</sup> Mn
Nickel oxide 1313-99-1	TWA: 1.5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> Cu dust and mist	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> Al Aluminum	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures**

Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

**Skin and Body Protection**

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves

**Respiratory Protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical State</b>	Solid	<b>Odor</b>	Odorless
<b>Appearance</b>	Silver	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	0.00001	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

### **Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

None known based on information supplied.

### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

### Hazardous Decomposition Products

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information In case of rupture
<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Corrosive by inhalation.(based on components).
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available. Expected to be and irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components).

### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel oxide 1313-99-1	> 9000 mg/kg ( Rat )	-	-
Manganese dioxide 1313-13-9	= 9000 mg/kg ( Rat )	-	-

### Information on toxicological effects

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing.Itching. Rashes Hives.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization of susceptible persons. May cause sensitization by skin contact. May cause sensitization by inhalation.

**Mutagenic Effects** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel oxide 1313-99-1		Group 2B Group 1	Reasonably Anticipated	X
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B		X
Cobalt(II) oxide 1307-96-6	A3	Group 2B		X

#### **ACGIH (American Conference of Governmental Industrial Hygienists)**

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

#### **IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

#### **NTP (National Toxicology Program)**

Known - Known Carcinogen

#### **OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X- Present

<b>Reproductive Toxicity</b>	Contains a known or suspected reproductive toxin
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
<b>Chronic Toxicity</b>	No known effect based on information supplied. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. May cause adverse liver effects.
<b>Target Organ Effects</b>	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive System. Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Lungs. Nasal cavities. Cardiovascular system. Systemic Toxicity. Liver.
<b>Aspiration Hazard</b>	No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

ATEmix (dermal)

ATEmix (inhalation-dust/mist)

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Nickel oxide 1313-99-1	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available

Manganese dioxide 1313-13-9	<0
--------------------------------	----



**Other adverse effects**

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods**

Should not be released into the environment.

**Contaminated Packaging**

Dispose of in accordance with federal, state and local regulations.

**California Hazardous Waste Codes 141**

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Cobalt(II) oxide 1307-96-6	Toxic
Nickel oxide 1313-99-1	Toxic powder Ignitable powder
Aluminum 7429-90-5	Ignitable powder
Aluminum foil 7429-90-5	Ignitable powder
Copper 7440-50-8	Toxic

**14. TRANSPORT INFORMATION**

**Note:**

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

<b>DOT</b>	NOT REGULATED
<b>Proper Shipping Name</b>	NON REGULATED
<b>Hazard Class</b>	N/A
<b>TDG</b>	Not regulated
<b>MEX</b>	Not regulated
<b>ICAO</b>	Not regulated
<b>IATA</b>	Not regulated
<b>Proper Shipping Name</b>	Not regulated
<b>Hazard Class</b>	N/A
<b>IMDG/IMO</b>	Not regulated
<b>Proper Shipping Name</b>	NON-REGULATED PER SP 188
<b>Hazard Class</b>	N/A
<b>EmS No.</b>	F-A, S-I
<b>RID</b>	Not regulated
<b>ADR</b>	Not regulated
<b>AND</b>	Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	12190-79-3	37.9	0.1
Cobalt(II) oxide	1307-96-6	7.4	0.1
Manganese dioxide	1313-13-9	15.4	1.0
Nickel oxide	1313-99-1	3.3	0.1
Aluminum foil	7429-90-5	4	1.0
Aluminum	7429-90-5	6	1.0
Copper	7440-50-8	8	1.0

#### **SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	No
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			
Nickel oxide 1313-99-1			RQ 10 lb final RQ RQ 4.54 kg final RQ

### US State Regulations

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Nickel oxide - 1313-99-1	Carcinogen
Cobalt(II) oxide - 1307-96-6	Carcinogen

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	X		X	X	X

Cobalt(II) oxide 1307-96-6			X	X	X
Manganese dioxide 1313-13-9			X	X	X
Carbon 7440-44-0			X		
Ethylene carbonate 96-49-1		X	X		
Dimethyl carbonate 616-38-6	X	X	X		
Diethyl carbonate 105-58-8	X	X	X		
Nickel oxide 1313-99-1	X	X	X	X	X
Copper 7440-50-8	X	X	X	X	X
Aluminum 7429-90-5	X	X	X	X	
Aluminum foil 7429-90-5		X		X	

**International Regulations****Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Manganese dioxide 1313-13-9 (15.4%)		Mexico: TWA= 0.2 mg/m <sup>3</sup>
Nickel oxide 1313-99-1 (3.3%)		Mexico: TWA 1 mg/m <sup>3</sup>
Copper 7440-50-8(8%)		Mexico: TWA= 1 mg/m <sup>3</sup> Mexico: TWA= 0.2 mg/m <sup>3</sup> Mexico: STEL= 2 mg/m <sup>3</sup>
Aluminum 7429-90-5(6%)		Mexico: TWA= 10 mg/m <sup>3</sup>
Aluminum foil 7429-90-5(4%)		Mexico: TWA= 10 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada****WHMIS Hazard Class**

Non-controlled

**16. OTHER INFORMATION**

**NFPA** Health Hazards 1 Flammability 0 Instability 0 **Physical and Chemical Hazards -**

**HMIS** Health Hazards 3 \* Flammability 0 Physical Hazard 0 **Personal Protection**

X

Chronic Hazard Star Legend \* = Chronic Health Hazard

Prepared By JiangSu Tenpower Lithium Co.,Ltd.

**Issuing Date****Revision Date**

29-June-2015

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet