

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
 Fontana, CA 92337-8228
 951/360-6677
 CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **MSPlus Advance Wood Flooring Adhesive**
 ITEM NUMBER: MSPLUS-4
 ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.
 PRODUCT DESCRIPTION: Low Viscosity Wood Adhesive
 CHEMICAL FAMILY: MS Polymer- Resin Blend
 REVISION DATE: 07/18/12

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
 SLIGHT: 1 FLAMMABLE: 0
 MODERATE: 2 REACTIVITY: 0
 HIGH: 3
 EXTREME: 4

PREPARED BY: ROBERT DDAMULIRA
 PREEMPTS PREVIOUS MSDS SHEETS

SECTION II INGREDIENTS

COMPONENT/CAS #	ACGIH TLV	OSHA PEL	% WT	NOTES
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				
NON HAZARDOUS PER DIRECTIVE 67/548/EEC AND 1999/45/EC				

CAS #	DESCRIPTION	PERCENTAGE
MIXTURE	SILYL TERMINATED POLYETHER	10 - 35 %
TRADE SECRET	PRORIETARY PLASTICIZER	5 - 20 %
MIXTURE	PROCESS ADDITIVES	0 - 0.5 %
1317-16-3	CALCIUM CARBONATE	15 - 55 %

SECTION III PHYSICAL DATA

BOILING POINT: NO DATA
 LBS / GAL: 10.75 - 11.05
 EVAPORATION RATE: LOW
 VAPOR DENSITY: LOW
 VAPOR PRESSURE: LOW
 PERCENT VOLATILE: 0 (BY WEIGHT), 100% SOLIDS
 COLOR: OFF WHITE
 ODOR: MILD

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, PENSKEY-MARTIN C.C.: NA
 AUTO IGNITION TEMPERATURE, DEGREES F: NA
 FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA
 EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE () OTHER
 (X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS AND TURN OUT GEAR. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO KEEP THE EXPOSED CONTAINERS COOL.

PRODUCT NAME: **MSPlus Advance Wood Flooring Adhesive**
ITEM NUMBER: MSPLUS-4
ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.
REVISION DATE: 07/18/12

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.

EYES: VAPOR MAY CAUSE IRRITATION.

SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.

INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.

CHRONIC: NOT KNOWN

SECTION VI FIRST AID PROCEDURES

FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VII HANDLING AND STORAGE

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. PROTECT FROM EXTREME TEMPERATURE CONDITIONS. AVOID BREATHING BUILD-UP OF VAPORS. USE WITH ADEQUATE VENTILATION.

PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F).

KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.

RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.

CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT CONTACT.

EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD

OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.

WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

PRODUCT NAME: **MSPlus Advance Wood Flooring Adhesive**
ITEM NUMBER: MSPLUS-4
ITEM DESCRIPTION: MSPlus Advance Wood Flooring Adhesive 4-gal.
REVISION DATE: 07/18/12

SECTION IX SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

SECTION X REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: PROTECT FROM FREEZING, EXCESSIVE HEAT, MOISTURE.

INCOMPATIBILITY(MATERIALS TO AVOID): METAL SALTS MAY COAGULATE THE PRODUCT.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER, AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION XI TOXICOLOGICAL PROPERTIES

NOT AVAILABLE

SECTION XII ECOLOGICAL INFORMATION

NOT AVAILABLE

SECTION XIII DISPOSAL CONSIDERATION

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS

SECTION XIV: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT APPLICABLE

PROPER HAZARD CLASS: NOT HAZARDOUS

HAZARD CODE: NOT HAZARDOUS

SECTION XV REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE

SARA TITLE III SECTION 312 HAZARD CLASS: NONE

EPA SARA TITLE III SECTION 313: NONE

ALL COMPONENTS OF THIS PRODUCT ARE EITHER LISTED OR EXEMPT IN THE U.S. EPA TSCA INVENTORY LIST

SECTION XVI OTHER INFORMATION

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
