

P11VT3



★★★★★ 4.6 (14) [Write a review](#)



Outlet Count 8 9 10 11 12
Cord Length 6 ft 8 ft 15 ft
Network Line No Yes
Color Beige Black

Maximum Power Surge Protection for Computers, Notebooks and Other Electronics

Includes: Coaxial cable, Telephone Cable, User Manual

Technical Specifications

Output

Number of Outlets	11.0
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	8ft (2.44meters)
Number of Power Cords	1

Surge Protection and Filtering

Surge energy rating	3020Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)
Data Lines Protected (multi-line only)	1-4
ts_nm_surge_response	1ns

Physical

Maximum Height	1.57inches (40MM, 4.0CM)
Maximum Width	4.7inches (119MM, 11.9CM)
Maximum Depth	11.89inches (302MM, 30.2CM)
Net Weight	2.33lbs. (1.06KG)
Shipping weight	2.97lbs. (1.35KG)
Shipping Height	2.36inches (60MM, 6.0CM)
Shipping Width	7.56inches (192MM, 19.2CM)

Shipping Depth	13.58inches (345MM, 34.5CM)
Color	Black
Master Carton Dimensions (Length x Width x Height)	15 x 8 x 15inches (378 x 210 x 377MM)
Master Carton Units	6.0
Master Carton Weight	19.58lbs. (8.9)
SCC Codes	1073130424903 7

Environmental

Operating Temperature	5 - 113 °F (-15 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	CSA, UL 1363, UL 1449
Equipment protection policy	Lifetime : \$100000
Standard warranty	Lifetime

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab