

- > Easy installation including MAGNA MOUNT<sup>™</sup> and screw mount.
- > Adjustable light angel and dimmable.
- > Amber White 2200k to Soft White 3000k CCT
- > Lasts 45 years\* or 50,000 Hours **Continuous Use**
- > Maintenance Free No **Bulb Replacements**
- > 5 Year Limited Warranty



500lms | 120VAC | Model 53503111 | Part UC-18-9-930-SV-D



## **SPECIFICATIONS**


Model	53503111	
Part	UC-18-9-930-SV-D	
Description	18" Beam Adjustable Under Cabinet Light-Dimmable	
Input Voltage (VAC)	120	
Wattage	9	
Dimmability	Triac	
Average Rated Life <sup>1</sup>	50,000 hours	
Typical Lumens <sup>2</sup>	500	
CCT <sup>3</sup>	2200-3000k	
Location Rating	UL Damp	lighting facts
CRI⁴	90	IIYIILIIY IACLS A Program of the U.S. DOE
Beam Angle	90	Light Output (Lumens)
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)	Watts Lumens per Watt (Efficacy)
Power Factor	>0.8	Color Accuracy
R9	59.7	Color Rendering Index (CRI)
DUV	.0025	Light Color Correlated Color Temperature (CCT) 3000 (Bright
Operating Frequency (Hz)	60	
1 Hours lifetime with 70% lumen maintenance 2 Thermally stable typical lumens (±10%)		Warm White Bright White Dayligh

2 Thermally stable typical lumens (±10%)

3 Thermally stable CCT (±10%)

4 Color rendering index/Ra





ETI

**TO ORDER:** www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754





## 18" Beam Adjustable Under Cabinet

500lms | 120VAC | Model 53503111 | Part UC-18-9-930-SV-D

## **SHIPPING INFORMATION**

Model	53503111
Part	UC-18-9-930-SV-D
UPC	849489009100
Product Dimensions (L x W x H in.)	18 x 2.4 x 1.1
Product Dimensions (L x W x H cm.)	457 x 61 x 28
Product Weight (Ibs.)	1.38
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	5
Master Carton Bar Code	50849489009105
Master Carton Dimensions (L x W x H in.)	24.8 × 9.37 × 3.66
Master Carton Dimensions (L x W x H cm.)	630 x 238 x 93
Master Carton Weight (Ibs)	8.93
Pallet Quantity	480

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754