



PARKHILL® TILE

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	12" x 24" / 304.8mm x 609.6mm
Overall Thickness*	0.25" / 6mm
Wear Layer	20 mil / 0.50mm, featuring Tuff Shield® finish
Edge	Beveled
Standard Colors	6 standard colors
Installation Method	2G Click
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.56 ft ² (2.19 m ²) per carton 12 pieces per carton 60 cartons per pallet 17 pallets per 20' container
Weight Per Carton	37.00 lbs / 16.78 kg



Strata-PKT 371

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥ 0.91
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



Gabbro
PKT 370



Strata
PKT 371



Montecelio
PKT 372



Terrace
PKT 373



Apatite
PKT 374



Sandstone
PKT 375

* All measurements are nominal.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.