

Safety Data Sheets (SDSs)

Client	Seiko Instruments Inc.Micro-Energy Division			
Add. of Client	45-1. Aza Matsubara, Kamiayashi, Aoba-ku, Sendai-shi, Miyagi, Japan			
Description	ML Lithium Rechargeable Battery			
Model /Type	ML414H IV01E			
Manufacturer	Seiko Instruments Inc.Micro-Energy Division			
Add. of Manufacturer	45-1. Aza Matsubara, Kamiayashi, Aoba-ku, Sendai-shi, Miyagi, Japan			
Nominal Voltage	3.0V, 1.0mAh			
Date of Receipt	2017-05-25			
Laboratory	Shenzhen ZRLK Testing Technology Co., Ltd.			
Address	6F, Fuxinfa Industrial Park, Liuxiandong, Xili Street, Nanshan District, Shenzhen, China			
Approved Signatory	Maggie.Gao Mog gie Goo			
Inspected by	Ailis.Ma Lahm Peng Lahm Peng			
Censored by	Lahm Peng Lahm Peng			

Report No.: ZKS170531188 Page 1 of 10



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: ML Lithium Rechargeable Battery

Model: ML414H IV01E

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use: Used in portabl electronic equipments;

Uses advidsed against:

- a) Do not dismantle, open or shred batteries.
- b) Do not expose batteries to heat or fire. Avoid storage in direct sunlight.
- c) Do not short-circuit battery. Do not store batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- d) Do not remove a battery from its original packaging until required for use.
- e) Do not subject batteries to mechanical shock.
- f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- g) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- h) Do not use any cell or battery which is not designed for use with the equipment.
- i) Do not mix cells of different manufacture, capacity, size or type within a device.
- i) Battery usage by children should be supervised.
- k) Seek medical advice immediately if a cell or a battery has been swallowed.
- 1) Always purchase the battery recommended by the device manufacturer for the equipment.
- m) Keep cells and batteries clean and dry.
- n) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.
- o) Use only the cell or battery in the application for which it was intended.
- p) When possible, remove the battery from the equipment when not in use.
- q) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: Seiko Instruments Inc.Micro-Energy Division

Address: 45-1. Aza Matsubara, Kamiayashi, Aoba-ku, Sendai-shi, Miyagi, Japan

Telephone number of the supplier: +81-22-391-9331

Postcode: 989-3124

E-mail address: sii.sendai-qa01@sii.co.jp

Emergency telephone number

Company Emergency Phone Number: +81-22-391-9331

2. HAZARDS IDENTIFICATION

Report No.: ZKS170531188 Page 2 of 10



Classification

No harm at the normal use. If contact the Electrolyte in the ML Lithium Rechargeable Battery, reference as

Classification of the substance or mixture

Classification according to GHS

Acute Toxicity, Oral(Hazard category 4)

Acute Toxicity, inhalation(Hazard category 4)

Serious eye damage/eye irritation (Hazard category 2A)

GHS Label elements, including precautionary statements:



GHS07

Signal word: Warning **Hazard statement(s):**

H319: Causes serious eye irritaion;

H332:Harmful if inhaled:

H302:Harmful if swallowed;

precautionary statements:

Prevention:

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid brething dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P312:Call a Poison center or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED:Remove person to fresh air and keep comfortable for breathing.

P301+P312:IF SWALLOWED:Call a Poison center or doctor/physician if you feel unwell.

P330 Rinse mouth.

Storage:

None

Disposal

P501: Dispose of contents/container in accordance with local/national regulations

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available.

COMPOSITION/INFORMATION ON INGREDIENTS

Report No.: ZKS170531188 Page 3 of 10



Chemical characterixation: Mixtures

Description:

Product: Consisting of the following components.

Common Chamical Name	Concentration	CAS
Common Chemical Name	(%)	Number
Tin	5	7440-31-5
Nickel	5	7440-02-0
Ethylene glycol diethyl ether	10	629-14-1
Lithium	13	7439-93-2
Manganese dioxide	10	1313-13-9
Methylal	7	109-87-5
Perchloric acid, lithium salt	3	7791-03-9
Graphite	5	7782-42-5
Iron	5	7439-89-6
Lithium-aluminum alloy	5	87871-87-2
Lithium manganese oxide (LiMn2O4)	30	12057-17-9
Stainless steel	2	12597-68-1

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

4. FIRST-AID MEASURES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Report No.: ZKS170531188 Page 4 of 10



Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Unsuitable Extinguishing Media: No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Report No.: ZKS170531188 Page 5 of 10



Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

Conditions for safe storage, including any incompatibilities

If the ML Lithium Rechargeable Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the ML Lithium Rechargeable Battery periodically.

3 months: -10° C \sim +40 $^{\circ}$ C, 45 to 85%RH

And recommended at $0^{\circ}\text{C} \sim +35^{\circ}\text{C}$ for long period storage.

Do not storage ML Lithium Rechargeable Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose ML Lithium Rechargeable Battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

CAS Number	ACGIH	NIOSH	OSHA
7782-42-5	TLV-TWA 2mg/m ³	RELs-TWA2.5mg/m ³	PELs-TWA 15mppcf
1333-86-4	TLV-TWA 3mg/m ³	RELs-TWA3.5mg/m ³	PELs-TWA 3.5mg/m ³
1313-13-9	PELs-TWA 0.1mg/m ³ PELs-TWA 0.02mg/m ³	N/A	N/A

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers


Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Body protection:

Report No.: ZKS170531188 Page 6 of 10



Protective work clothing.

Skin protection:



Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

	Form: button			
Physical	Color: silver			
State	Odour: Odourless			
	Odor Threshold: No information a	vailable		
Change in co	ondition:			
pH, with ind	ication of the concentration	Not determined.		
Melting poin	nt/freezing point	Not determined.		
Initial boiling	g point and Boiling range:	Not determined.		
Flash Point		Not determined.		
Evaporation	rate	Not determined.		
Flammability (solid, gas)		Not determined.		
Upper/lower flammability or explosive limits		Not determined.		
Vapor Pressi	ure:	Not determined.		
Vapor Densi	ty:	Not determined.		
relative density:		Not determined.		
Solubility in	Water:	Not determined.		
Solubility in	other solvents	Not determined.		
n-octanol/wa	ater partition coefficient	Not determined.		

Report No.: ZKS170531188 Page 7 of 10



Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Odout threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	:
Voltage	3.0V
Electric capacity	1.0mAh
Lithium content	0.0003g

10. STABILITY AND REACTIVITY

Reactivity: Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

<u>Hazardous Decomposition Products:</u>Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

12. Ecological Information

Toxicity:

Acquatic toxicity:

No further relevant information available.

Report No.: ZKS170531188 Page 8 of 10



Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

Land transport

ADR/RID class: Not regulated. UN-Number: UN3090 or UN3091.

Maritime transport

IMDG Class: Class 9.

UN Number: UN3090 or UN3091.

Marine pollutant: No

Air transport

ICAO/IATA Class: Class 9

UN/ID Number: UN3090 or UN3091 Environmental hazards: Not applicable. Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The ML Lithium Rechargeable Battery had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The lithium batteries according to Section II of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION 969~970 of the Dangerous Goods regulations 58th Edition may be transported. The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of Special Provision 188 of IMDG(37-14) to be transported as non-dangerous goods

Report No.: ZKS170531188 Page 9 of 10



Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available. **Restrictions on use:** No information available.

Regulatory information

CAS No.	EU	US	Japan	Canada	Austrlia	Korea	China
	(EINECS	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
)			NDSL)			
7440-31-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7440-02-0	Listed	Listed	Listed	DSL	Listed	Listed	Listed
629-14-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7439-93-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1313-13-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
109-87-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7791-03-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7439-89-6	Listed	Listed	Listed	DSL	Listed	Listed	Listed
87871-87-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
12057-17-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
12597-68-1	Listed	Listed	Listed	DSL	Listed	Listed	Listed

Chemical safety assessment A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed. H332: Harmful if inhaled.

Report No.: ZKS170531188 Page 10 of 10



Safety Data Sheets (SDSs)

Client	SHENZHEN GAONENGDA BATTERY CO., LTD.				
	No. 28, Changjin Road, Changjiangpu Industrial Zone, He'ao, Henggang				
Add. of Client	Town, Shenzhen City, China				
Description	Lithium button cell				
Model /Type	CR1220				
Manufacturer	SHENZHEN GAONENGDA BATTERY CO., LTD.				
Add. of	No. 28, Changjin Road, Changjiangpu Industrial Zone, He'ao, Henggang				
Manufacturer	Town, Shenzhen City, China				
Nominal Voltage	3.0V, 40mAh, 0.12Wh				
Date of Receipt	2015-06-06				
Laboratory	Shenzhen ZRLK Testing Technology Co., Ltd.				
Address	6F, Fuxinfa Industrial Park, Liuxiandong, Xili Street, Nanshan District, Shenzhen, China				
Approved Signatory	Williau. liu William · Liu				
Inspected by	Williau. liu Bella. Wang Bella. Wang Frank. feng Frank. feng				
Censored by	Frank. feng				

Report No.: ZRLK1506060007 Page 1 of 10



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: Lithium button cell

Model: CR1220

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use: Used in portabl electronic equipments;

Uses advidsed against:

- a) Do not dismantle, open or shred batteries.
- b) Do not expose batteries to heat or fire. Avoid storage in direct sunlight.
- c) Do not short-circuit battery. Do not store batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- d) Do not remove a battery from its original packaging until required for use.
- e) Do not subject batteries to mechanical shock.
- f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- g) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- h) Do not use any cell or battery which is not designed for use with the equipment.
- i) Do not mix cells of different manufacture, capacity, size or type within a device.
- i) Battery usage by children should be supervised.
- k) Seek medical advice immediately if a cell or a battery has been swallowed.
- l) Always purchase the battery recommended by the device manufacturer for the equipment.
- m) Keep cells and batteries clean and dry.
- n) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.
- o) Use only the cell or battery in the application for which it was intended.
- p) When possible, remove the battery from the equipment when not in use.
- q) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: SHENZHEN GAONENGDA BATTERY CO., LTD.

Address: No. 28, Changjin Road, Changjiangpu Industrial Zone, He'ao, Henggang Town, Shenzhen City

China

Telephone number of the supplier: 0086-0755-28626184

Fax: 0086-0755-28625176

Postcode: 518115

E-mail address: gld@gld-battery.com

Emergency telephone number

Company Emergency Phone Number: 0086-0755-28626184

2. HAZARDS IDENTIFICATION

Report No.: ZRLK1506060007 Page 2 of 10



Classification

No harm at the normal use. If contact the Electrolyte in the Lithium button cell, reference as follows:

Classification of the substance or mixture

Classification according to GHS

Acute Toxicity, Oral(Hazard category 4)

Acute Toxicity, inhalation(Hazard category 4)

Serious eye damage/eye irritation (Hazard category 2A)

GHS Label elements, including precautionary statements:



GHS07

Signal word: Warning

Hazard statement(s):

H319: Causes serious eye irritaion;

H332:Harmful if inhaled;

H302: Harmful if swallowed;

precautionary statements:

Prevention:

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid brething dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P312:Call a Poison center or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists:Get medical advice/attention.

P304+P340 IF INHALED:Remove person to fresh air and keep comfortable for breathing.

P301+P312:IF SWALLOWED:Call a Poison center or doctor/physician if you feel unwell.

P330 Rinse mouth.

Storage:

None

Disposal

P501: Dispose of contents/container in accordance with local/national regulations

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Report No.: ZRLK1506060007 Page 3 of 10



Chemical characterization: Mixtures

Description:

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number	EC No.
Lithium	1.5	7439-93-2	231-102-5
Propylene carbonate	4.5	108-32-7	203-572-1
Manganese dioxide	26.3	1313-13-9	215-202-6
Steel manufacture, chemicals	50.8	65997-19-5	
Polypropylene	7.7	9003-07-0	
Graphite	3.1	7782-42-5	231-955-3
Carbon black	1.0	1333-86-4	215-609-9
Ethylene glycol dimethyl ether	4.1	110-71-4	203-794-9
Perchloric acid, lithium salt	1.0	7791-03-9	232-237-2

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

4. FIRST-AID MEASURES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Unsuitable Extinguishing Media:No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Report No.: ZRLK1506060007 Page 4 of 10



Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

Report No.: ZRLK1506060007 Page 5 of 10



Conditions for safe storage, including any incompatibilities

If the Lithium button cell is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Lithium button cell periodically.

3 months: -10° C $\sim +40^{\circ}$ C, 45 to 85% RH

And recommended at 0°C~+35°C for long period storage.

Do not storage Lithium button cell haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Lithium button cell to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

CAS Number	ACGIH	NIOSH	OSHA
7782-42-5	TLV-TWA 2mg/m ³	RELs-TWA2.5mg/m ³	PELs-TWA 15mppcf
1333-86-4	TLV-TWA 3mg/m ³	RELs-TWA3.5mg/m ³	PELs-TWA 3.5mg/m ³
108-32-7	TLV-TWA 2ppm	RELs-TWA3.5mg/m ³	PELs-TWA 240mg/m ³
1313-13-9	PELs-TWA 0.1mg/m ³ PELs-TWA 0.02mg/m ³	N/A	N/A

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Tightly sealed goggles

Body protection:

Protective work clothing.

Skin protection:

Report No.: ZRLK1506060007 Page 6 of 10





Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

	Form: button				
Physical State	Color: silver				
	Odour: Odourless				
	Odor Threshold: No information available				
Change in co	ondition:				
pH, with ind	lication of the concentration	Not determined.			
Melting poir	nt/freezing point	Not determined.			
Initial boilin	g point and Boiling range:	Not determined.			
Flash Point		Not determined.			
Evaporation rate		Not determined.			
Flammabilit	y (solid, gas)	Not determined.			
Upper/lower	flammability or explosive limits	Not determined.			
Vapor Pressure:		Not determined.			
Vapor Densi	ity:	Not determined.			
relative dens	sity:	Not determined.			
Solubility in	Water:	Not determined.			
Solubility in	other solvents	Not determined.			
n-octanol/wa	ater partition coefficient	Not determined.			
Auto-ignitio	n temperature	Product is not self-igniting.			
Decomposit	ion temperature	Not determined.			

Report No.: ZRLK1506060007 Page 7 of 10



Odout threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	:
Voltage	3.0V
Electric capacity	40mAh
Lithium content	0.012g

10. STABILITY AND REACTIVITY

Reactivity: Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

<u>Hazardous Polymerization:</u> Hazardous polymerization does not occur.

<u>Conditions to avoid:</u> Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

Hazardous Decomposition Products: Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information available.

12. Ecological Information

Toxicity:

Acquatic toxicity:

No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Report No.: ZRLK1506060007 Page 8 of 10



Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

Land transport

ADR/RID class: Not regulated. UN-Number: UN3090 or UN3091.

Maritime transport

IMDG Class: Class 9.

UN Number: UN3090 or UN3091.

Marine pollutant: No

Air transport

ICAO/IATA Class: Class 9

UN/ID Number: UN3090 or UN3091 Environmental hazards: Not applicable. Special precautions for user: Not applicable.

Transport/Additional information: Not restricted goods according to the above specifications.

The Lithium button cell had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;

The lithium ion batteries according to Section II/Section IB of PACKING INSTRUCTION 968, or Section II of PACKING INSTRUCTION $969\sim970$ of the Dangerous Goods regulations 56th Edition may be transported.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Meets requirements of Special Provision 188 of IMDG(36-12) to be transported as non-dangerous goods Meets the requirements of 49CFR173.185 to be transported as non-dangerous goods for road, rail, air, and vessel (Effective August 6, 2014 per HM224F)

The package must be handled with care and that a flammability hazard exists if the package is damaged;

Report No.: ZRLK1506060007 Page 9 of 10



15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available. **Restrictions on use:** No information available.

Regulatory information

CAS No.	EU	US	Japan	Canada	Austrlia	Korea	China
	(EINECS)	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
				NDSL)			
7439-93-2	Listed	Listed	Listed	DSL	Listed	Listed	Listed
108-32-7	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1313-13-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed
65997-19-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
9003-07-0	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1333-86-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed
110-71-4	Listed	Listed	Listed	DSL	Listed	Listed	Listed
7791-03-9	Listed	Listed	Listed	DSL	Listed	Listed	Listed

<u>Chemical safety assessment</u> A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed.

H332: Harmful if inhaled.

Report No.: ZRLK1506060007 Page 10 of 10