

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

SECTION 1: Identification

1.1 Product identifier

Trade name **Zar® Poly OMU Interior (Oil Modified) - Satin**
Alternative number(s) 36212; UFI: S5WG-2EPJ-QA0S-D6NX
36213; UFI: 2R5H-PEQ8-CA08-HAXD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc.
1396 Jefferson Avenue
Dunmore PA 18509
United States

Telephone: +1 (570) 344-1202
Telefax: (570) 969-7634
e-mail: sales@ugl.com
Website: <http://www.ugl.com/>

e-mail (competent person) mark.fortese@ugl.com (Mark Fortese)

1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)
Emergency telephone number: Outside office hours

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.7	reproductive toxicity	1B	Repr. 1B	H360D

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H360D May damage the unborn child.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

- Precautionary statements

- P201 Obtain special instructions before use.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 If exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling 1-methyl-2-pyrrolidinone

2.3 Other hazards

Hazards not otherwise classified

Contains . May produce an allergic reaction.
Safety data sheet available on request.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
triethylamine	CAS No 121-44-8	0.05 - < 1	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 Flam. Liq. 2 / H225
1-methyl-2-pyrrolidinone	CAS No 872-50-4	0.05 - < 1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Repr. 1B / H360D STOT SE 3 / H335 Flam. Liq. 4 / H227

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as

Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	triethylamine	121-44-8	PEL (CA)					1	4.1		Cal/ OSHA PEL
US	triethylamine	121-44-8	TLV®	0.5		1					ACGIH® 2019
US	triethylamine	121-44-8	PEL	25	100						29 CFR 1910.1000
US	triethylamine	121-44-8	REL							appx-D	NIOSH REL
US	N-methyl-pyrrolidone (NMP) (1-methyl-2-pyrrolidone) (N-methyl-2-pyrrolidone)	872-50-4	PEL (CA)	1	4						Cal/ OSHA PEL

Notation

appx-D

Ceiling-C

STEL

TWA

see Appendix D - Substances with No Established RELS

ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	N-methyl-2-pyrrolidone	5-hydroxy-N-methyl-2-pyrrolidone		BEI®	100 mg/l	ACGIH® 2019

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	various
Odor	characteristic

Other safety parameters

pH (value)	7.5 – 8.5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	184 °C at 100.3 kPa
Flash point	not determined
Evaporation rate	Not determined

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	
- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	20.4 vol%
Vapor pressure	1 mmHg at 64.3 °C
Density	1.037 g/cm ³ at 25 °C
Vapor density	this information is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	194 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
triethylamine	121-44-8	oral	730 mg/kg
triethylamine	121-44-8	dermal	580 mg/kg
triethylamine	121-44-8	inhalation: vapor	3 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains . May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|--|---|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not assigned |
| 14.3 Transport hazard class(es) | not assigned |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code | The cargo is not intended to be carried in bulk. |

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
triethylamine	121-44-8		1994-12-31
1-methyl-2-pyrrolidinone	872-50-4		1994-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
triethylamine	121-44-8		1 3 4	5000 (2270)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
triethylamine	121-44-8		CA TACs OEHHA RELs
1-methyl-2-pyrrolidinone	872-50-4		EC Annex VI CMRs - Cat. 1B Prop 65

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
triethylamine	121-44-8				1.0 %
1-methyl-2-pyrrolidinone	872-50-4				1.0 %

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
triethylamine	121-44-8		F3
1-methyl-2-pyrrolidinone	872-50-4		TE F2

Legend

F2 Flammable - Second Degree
F3 Flammable - Third Degree
TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ETHANAMINE, N,N-DIETHYL-	121-44-8	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
triethylamine	121-44-8	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
N-methylpyrrolidone	872-50-4		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.4	Emergency information service: 1-800-424-9300 Chemtrec (NORTH AMERICA) This number is only available during the following office hours: Mon-Fri 08:00 AM - 05:00 PM	Emergency information service: 1-800-424-9300 Chemtrec (NORTH AMERICA) Emergency telephone number: Outside office hours	yes
3.2		Description of the mixture: change in the listing (table)	yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes

Zar® Poly OMU Interior (Oil Modified) - Satin

Version number: REV 4.0
Replaces version of: 2021-01-21 (REV 3)

Revision: 2021-03-31

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

End of safety data sheet