



# MATERIAL SAFETY DATA SHEET

Colorhouse® Inspired Multi-Purpose Primer, Flat, Eggshell, and Semi-Gloss

**Emergency telephone number:** 1-800-535-5053 US/Canada (INFOTRAC)

**Distributed by:** Colorhouse, 519 NE Hancock #B, Portland, OR 97212, 503-493-8275

The following Material Safety Data Sheet (MSDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards.

The health and hazards information given here is based on data believed to be accurate by YOLO Colorhouse LLC; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

As permitted by OSHA, each MSDS may apply to a class of products which have similar hazards and contents.

## Product list:

- 1411xx Colorhouse Inspired Flat White
- 1421xx Colorhouse Inspired Flat Medium
- 1441xx Colorhouse Inspired Flat Neutral
- 1412xx Colorhouse Inspired Eggshell White
- 1422xx Colorhouse Inspired Eggshell Medium
- 1442xx Colorhouse Inspired Eggshell Neutral
- 1413xx Colorhouse Inspired Semi-Gloss White
- 1423xx Colorhouse Inspired Semi-Gloss Medium
- 1443xx Colorhouse Inspired Semi-Gloss Neutral
- 1445xx Colorhouse Chalkboard Paint
- 1404xx Colorhouse Inspired Multi-Purpose Primer

## 1 - IDENTIFICATION

**Product code:** (See product list above)

**Product name:** Colorhouse Inspired

**Product type:** Waterborne Paint

**Product use:** Interior

**HMS codes:** H F R PP  
1 0 0 E

**Distributor:** Colorhouse  
519 NE Hancock #B  
Portland, OR 97212  
1-800-535-5053 **emergency phone**  
(503) 493-8275 **other calls**  
(503) 232-0445 **fax phone**

## 2 - HAZARDS IDENTIFICATION

**GHS Classification:** (Not Applicable)

**GHS Label Elements:** NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.

**Signal Word:** (None Required) **Hazard Statement:** (None Required) **Pictogram:** (None Required)

### Precautionary Statements:

**Prevention:** DO NOT INGEST. Use only with adequate ventilation or protection. Avoid breathing spray mist. Avoid contact with eyes and skin. Close container after use. Keep out of reach of children.

**Response:** Clean up spills with inert absorbent material, such as clay granules, paper, or cloth wipes. Allow to dry before disposal.

**Storage & Disposal:** Keep above 40°F at all times. Dispose of container and contents in accordance with applicable local, state, and federal regulations.

**Hazards Not Otherwise Classified:** None.

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients:

**NO REPORTABLE HAZARDOUS INGREDIENTS.**

NOTE: Potential unusual allergic sensitivity to trace ingredients of this product can be minimized by following recommended procedures for safe handling, storage, disposal, and use.

---

### 4 - FIRST AID MEASURES

**Eyes:** Flush eyes with fresh water for at least 15 minutes.

**Skin:** Wash thoroughly with soap and water.

**Ingestion:** Have victim drink enough fresh water to ensure dilution.

**Inhalation:** Move victim to fresh air.

**Notes to first aid providers:** Call for emergency medical care if symptoms persist.

---

### 5 - FIRE FIGHTING MEASURES

**Flammable limits in air (% by volume):** Upper: Not applicable. Lower: Not applicable.

**Flash point:** Not applicable.

**Autoignition temperature:** Not applicable.

**HMIS hazard classification:** Health: 1 Flammability: 0 Reactivity: 0 Protection: E

**Extinguishing media:** Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog.

**Special fire fighting procedures:** Use self-contained breathing apparatus in confined spaces. Observe recommended procedures for handling ordinary combustible materials.

**Unusual fire and explosion hazards:** Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers can develop internal pressure and may rupture when subjected to extreme heat.

**Hazardous decomposition products:** Combustion can produce carbon monoxide and/or carbon dioxide.

---

### 6 - ACCIDENTAL RELEASE MEASURES

Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of liquid spilled.

---

### 7 - HANDLING AND STORAGE

**Handling and storage:** Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area rotate stock, use older material first. DO NOT FREEZE.

**Other precautions:** Inspect all containers for leaks periodically.

---

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls:** Use signs or barriers to restrict access to painting work area.

**Ventilation:** Normal air circulation should be sufficient. Otherwise, use portable fans.

**Respiratory protection:** For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

**Eye protection:** Use safety glasses, goggles, or face shield to protect eyes.

**Skin protection:** Use waterproof gloves (latex, vinyl, rubber, or neoprene) to avoid skin contact.

**Other protective clothing or equipment:** Waterproof head covering and general protective clothing are recommended for protection as necessary.

**Work hygienic practices:** Wash hands and face before eating or drinking.

## 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Opaque liquid dispersion

**Physical state:** Liquid

**Boiling point:** 212°F, 100°C

**Vapor pressure:** Same as water vapor

**Specific gravity (H<sub>2</sub>O = 1):** 1.4

**Solubility in water:** partly soluble

**Percent volatile:** 60-65% by volume, 43-49% by weight

**Odor:** Very mild odor

**pH as supplied:** 8.5 - 9.0

**Freezing point:** 32°F, 0°C

**Vapor density:** Same as water vapor

**Evaporation rate:** Same as water

**Percent solids:** 35-40% by volume, 51-57% by weight

**Maximum volatile organic compound (VOC) content:**

**With water:** 1 gram per liter (0.0083 pound per gallon)

**Without water:** 2 grams per liter (0.0167 pound per gallon)

---

## 10 - STABILITY AND REACTIVITY

**Stability:** Stable.

**Conditions to avoid (stability):** Avoid storage or use at temperatures below 40°F.

**Incompatibility (materials to avoid):** Avoid water-reactive materials, strong oxidizers, acids and alkalis.

**Hazardous decomposition products:** Combustion can produce carbon monoxide and/or carbon dioxide.

**Hazardous polymerization:** Will not occur.

---

## 11 - TOXOLOGICAL INFORMATION

No information available.

---

## 12 - ECOLOGICAL INFORMATION

No information available.

---

## 13 - DISPOSAL CONSIDERATIONS

**Waste disposal method:** Collect spilled material and contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

**RCRA hazard class:** Non-hazardous

---

## 14 - TRANSPORTATION INFORMATION

This product is not subject to DOT, IATA/ICAO, or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

---

## 15 - REGULATORY INFORMATION (not meant to be all inclusive)

**U.S. federal regulations:**

**TSCA:** All components are listed in TSCA inventory or exempt.

**CERCLA:** Not listed as a hazardous substance.

**SARA title III:** Not listed as a hazardous substance.

**311/312 hazard categories:** Not applicable.

**313 reportable ingredients:** Not applicable.

**State regulations:** Not applicable.

**International regulations:** Not applicable.

---

## 16 - OTHER INFORMATION

**Other information:** Do not store in areas subject to freezing temperatures. Keep above 40°F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with eyes and skin. Close container after each use. Keep out of reach of children.

**Preparer information:** YOLO Colorhouse, LLC; 503-493-8275 (phone) Date: 6/6/2014

**Disclaimer:** The information conveyed above, although obtained from sources we consider reliable, is furnished by YOLO Colorhouse, LLC, without any warranty (whether express or implied) as to its accuracy, adequacy, or applicability to any particular needs or circumstances.