

medium

INSIDE CORNER DRYWALL TAPE

Straighter, Stronger,
Twice as Fast
Half the Work!



APPLICATIONS

- Inside 90° corners and angled corners.
- Inside angles of bay windows.
- Commercial "Top Out" applications where drywall meets concrete ceilings.
- Inside ceiling corners.

PRODUCT DESCRIPTION

- Produced straight, strong, and professional inside corners.
- Two times stronger than paper or mesh tapes.
- Twice as fast as paper or mesh tapes.
- Slotted edges ensure superior bond.
- Straightens minor framing irregularities for vertical corners.
- Resists dents, paint chipping, shrinkage, and common cracking problems.
- Rustproof.
- Cuts easily with knife or scissors.
- Installs using standard compounds. No special tools or fasteners needed. No nail pops.
- Second coat of compound can be applied immediately – very light skim-coat to finish.
- Slightly thinner than Strait-Flex's Original.

medium

ADVANTAGES OVER COMPETITORS

STRAIT-FLEX MEDIUM

Straightens Common
Drywall Imperfections
In Corners

Will Not Soften or Sag

Two Times Stronger
Than Paper Tape

No Blisters or Fuzz-Ups

Superior Bonding

Ideal for Novice or Pro

COMPETITOR PAPER TAPES

Conforms to Framing
Imperfections. Rounds
Out When Drying.


Softens and Sags When Wet

Tends to Hairline Crack with Temperature
Change or Structural Movement

Fuzzes Up During Sanding

Good Bonding

Requires Skill or a Professional



DIRECTIONS FOR USE

- 1 Cut Strait-Flex MEDIUM to desired length. Fold MEDIUM in half at center crease with print side facing each other. For inside corners, fold less than desired angle with print side facing out.
- 2 Using a 4" or 5" taping knife, apply a smooth, liberal coat of compound to corner.
- 3 Press MEDIUM into wet compound. Adjust if necessary to create a straight line. Wipe down tight with taping knife using a little additional pressure on the outer edges of MEDIUM. Immediately apply a light skim coat of compound over surface of MEDIUM. Wipe down tight and smooth. Let dry completely over several hours or overnight.
- 4 Apply very light finish coat, let dry, and sand.

REPAIRS OVER PAINTED SURFACES. Strait-Flex recommends the use of Strait-Flex Super-Bond or latex paint, mixed with all-purpose joint compound, for enhanced bondability.

SPECIFICATIONS

- 2 1/4" x 50' roll size.
- Color Code GREEN
- Item# SM-50
UPC 6-56690-13125-0
- RETAIL PKG
Case Item# SM-50-6
6rls per tray. One tray
per case. (6-Pack)
Case weight: 8.5 lbs.
48 cases per pallet.
- RETAIL PKG
Case Item# SM-50-12
6rls per tray. Two trays
per case. (12-Pack)
Case weight: 16.4 lbs.
24 cases per pallet.
- 2 1/4" x 100' roll size.
- Color Code GREEN
- Item# SM-100
UPC 6-56690-12556-3
- RETAIL PKG
Case Item# SM-100-R
6rls per tray. Two trays
per case. (12-Pack)
Case weight: 31 lbs.
24 cases per pallet.
- WHOLESALE PKG
Case Item# SM-100C
12rls per case.
Case weight: 30 lbs.
24 cases per pallet.

STORAGE

Store in a dry place protected from moisture.

