

# **HSR Use and Care Manual**

## **Mix2Match™**

# **Hard Surface Repair Kit**

**For Wood, Laminate, Tile, Stone, Countertops,  
Furniture, Engineered Flooring & more**

**All surfaces should be clean and dry.  
Shake pigment bottles thoroughly before and during use.**

### **Application**

1. Choose a color from the formula chart found inside this package that closest matches the floor.

Follow directions for the Mixing Method which applies to your formula:

Method A: add the required amount of tint drops into the bowl and mix thoroughly with the stick. Dip stick in the bowl and apply mix to mixing board with a sharp tap.

Method B: add tint drops directly to the putty.

2. Measure the required amount of putty onto the mixing board by using the reference lines, then add the required tint to putty and mix until the putty is uniform in color.
3. Apply mixed putty to floor with a flat plastic spatula slightly overfilling the area of the repair. Scrape off any surrounding excess with spatula. Allow to dry.
4. When mixture is freshly dry, gently rub away the excess of the surrounding area with a damp cloth until the surface is smooth.
5. If shrinkage occurs, re-apply the above mixture.
6. Once the repair is completely dry and graining or marbling is finished, apply clear lacquer over the area using the brush.

**CAUTION: EYE IRRITANT** Read instructions carefully

**HEALTH AND SAFETY: KEEP OUT OF REACH OF CHILDREN**

- Irritating to eye and skin. In case of contact with skin, wash immediately with soap and water. In case of contact with eyes, rinse immediately with plenty of clean, fresh water.

- If swallowed, rinse mouth and throat with cold water. Immediately seek professional medical advice.

**Take this label with you. DO NOT INDUCE VOMITING**