

SAFETY DATA SHEET

Issuing Date 21-Sep-2016

Revision Date 21-Sep-2016

Revision Number 3

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Li Ion Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Stanley Black & Decker

Supplier Address 2501 SW Aviation Drive
Bentonville
AR
72712
US

Supplier Phone Number Phone:479-271-8812
Fax:479-271-9798

Supplier Email mellody.fletcher@bdk.com

Emergency telephone number

Company Emergency Phone Number 479-254-3404

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4

Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 2
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger
Hazard Statements Harmful if swallowed Harmful in contact with skin Fatal if inhaled Causes severe skin burns and eye damage May cause an allergic skin reaction May cause cancer May damage fertility or the unborn child May cause respiratory irritation Causes damage to organs through prolonged or repeated exposure	
This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.	
Appearance Solid	Physical state Solid
Odor None	

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

60 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Copper	7440-50-8	10 - 30	*
Steel manufacture, chemicals	65997-19-5	7 - 13	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	7 - 13	*
Aluminum	7429-90-5	7 - 13	*
Lithium manganese oxide (LiMn2O4)	12057-17-9	5 - 10	*
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	5 - 10	*
Cobalt lithium manganese nickel oxide	182442-95-1	5 - 10	*
Aluminum cobalt lithium nickel oxide	193214-24-3	5 - 10	*
Nickel	7440-02-0	3 - 7	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

First aid is upon rupture of sealed battery.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice. May cause an allergic skin reaction.

Inhalation

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur. Do not breathe dust.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions

Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible Products

Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Steel manufacture, chemicals 65997-19-5	STEL: 10 mg/m ³ Zr TWA: 0.05 mg/m ³ Pb TWA: 0.00005 mg/m ³ Be inhalable particulate matter TWA: 1 mg/m ³ Cu dust and mist TWA: 0.2 mg/m ³ Se TWA: 1 mg/m ³ Y TWA: 5 mg/m ³ Zr TWA: 0.02 mg/m ³ Mn respirable particulate matter TWA: 0.1 mg/m ³ Mn inhalable particulate matter TWA: 0.5 mg/m ³ Hf	TWA: 50 µg/m ³ Pb TWA: 2 µg/m ³ Be TWA: 0.2 mg/m ³ Se TWA: 5 mg/m ³ Zr Action Level: 30 µg/m ³ Pb Poison; See 29 CFR 1910.1025 (vacated) TWA: 2 µg/m ³ Be (vacated) TWA: 0.2 mg/m ³ Se (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 25 µg/m ³ 30 min (vacated) STEL: 10 mg/m ³ Zr (vacated) Ceiling: 5 µg/m ³ (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 µg/m ³ Be Ceiling: 5 mg/m ³ Mn	IDLH: 4 mg/m ³ Be IDLH: 100 mg/m ³ Cu dust and mist IDLH: 500 mg/m ³ Mn IDLH: 1 mg/m ³ Se IDLH: 500 mg/m ³ Y IDLH: 25 mg/m ³ Zr IDLH: 100 mg/m ³ Pb IDLH: 10 mg/m ³ Ni IDLH: 50 mg/m ³ Hf Ceiling: 0.05 mg/m ³ V dust and fume 15 min Ceiling: 0.0005 mg/m ³ Be TWA: 1 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ Mn TWA: 0.2 mg/m ³ except Selenium hexafluoride Se TWA: 1 mg/m ³ Y TWA: 5 mg/m ³ except Zirconium tetrachloride Zr TWA: 0.050 mg/m ³ Pb TWA: 0.015 mg/m ³ except Nickel carbonyl Ni TWA: 0.5 mg/m ³ Hf STEL: 3 mg/m ³ Mn STEL: 10 mg/m ³ Zr
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Lithium manganese oxide (LiMn2O4) 12057-17-9	TWA: 0.2 mg/m ³ Mn	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m ³	-	
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m ³ Co TWA: 0.02 mg/m ³ Mn respirable particulate matter TWA: 0.1 mg/m ³ Mn inhalable particulate matter	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn IDLH: 10 mg/m ³ Ni TWA: 1 mg/m ³ Mn TWA: 0.015 mg/m ³ except Nickel carbonyl Ni STEL: 3 mg/m ³ Mn
Aluminum cobalt lithium nickel oxide 193214-24-3	TWA: 0.02 mg/m ³ Co	-	
Nickel 7440-02-0	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse. Do not breathe dust. For environmental protection, remove and wash all contaminated protective equipment before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Solid	Odor	None
Appearance	Solid	Odor Threshold	No information available
Color	No information available		
Property	Values	Remarks	Method
pH	No data available	None known	

Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Insoluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	0	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Fatal if inhaled.
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May be absorbed through the skin in harmful amounts. Harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization in susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Steel manufacture, chemicals 65997-19-5	A1	Group 1	Known Reasonably Anticipated	X
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	A3	Group 2B		X
Cobalt lithium manganese nickel oxide 182442-95-1	A3	Group 2B Group 1	Known	X
Aluminum cobalt lithium nickel oxide 193214-24-3	A3	Group 2B Group 1	Known	X

Nickel 7440-02-0		Group 2B	Reasonably Anticipated	X
---------------------	--	----------	------------------------	---

ACGIH (American Conference of Governmental Industrial Hygienists)
 A1 - Known Human Carcinogen
 A3 - Animal Carcinogen
 IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 NTP (National Toxicology Program)
 Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive toxicity	Contains a known or suspected reproductive toxin.
STOT - single exposure	Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Respiratory system.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Systemic Toxicity. Reproductive System. Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Lungs. Nasal cavities. Digestive System.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

327.00 mg/kg

ATEmix (dermal)

1,200.00 mg/kg

ATEmix (inhalation-gas)

400.04 ppm

ATEmix (inhalation-dust/mist)

0.20 mg/l

ATEmix (inhalation-vapor)

2.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio)		48h EC50: = 0.03 mg/L
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

Chemical name	California Hazardous Waste
Copper 7440-50-8	Toxic
Steel manufacture, chemicals 65997-19-5	Toxic
Aluminum 7429-90-5	Ignitable powder
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic
Aluminum cobalt lithium nickel oxide 193214-24-3	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)
Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT

Proper Shipping Name NOT REGULATED
 Hazard Class NON-REGULATED
 Emergency Response Guide N/A
 Number 147

TDG

Not regulated

MEX

Not regulated

ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
IMDG/IMO	Not regulated
Hazard Class	N/A
EmS-No.	F-A, S-I
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Copper - 7440-50-8	7440-50-8	10 - 30	1.0
Steel manufacture, chemicals - 65997-19-5	65997-19-5	7 - 13	1.0 0.1
Aluminum - 7429-90-5	7429-90-5	7 - 13	1.0
Lithium manganese oxide (LiMn2O4) - 12057-17-9	12057-17-9	5 - 10	1.0
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	5 - 10	0.1
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	5 - 10	1.0 0.1
Nickel - 7440-02-0	7440-02-0	3 - 7	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	
Steel manufacture, chemicals		X		

65997-19-5				
Cobalt lithium manganese nickel oxide 182442-95-1		X		
Nickel 7440-02-0		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Steel manufacture, chemicals - 65997-19-5	Carcinogen
Cobalt lithium manganese nickel oxide - 182442-95-1	Carcinogen
Aluminum cobalt lithium nickel oxide - 193214-24-3	Carcinogen
Nickel - 7440-02-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Copper 7440-50-8	X	X	X	X	X
Ethylene carbonate 96-49-1		X	X		
Aluminum 7429-90-5	X	X	X	X	
Diethyl carbonate 105-58-8	X	X	X		
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X				
Steel manufacture, chemicals 65997-19-5	X		X	X	X
Lithium manganese oxide (LiMn2O4) 12057-17-9	X		X	X	X
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	X		X	X	X
Cobalt lithium manganese nickel oxide 182442-95-1	X		X	X	X
Aluminum cobalt lithium nickel oxide 193214-24-3	X		X		X
Nickel 7440-02-0	X	X	X	X	X

International Regulations**Mexico****National occupational exposure limits**

Chemical name	Carcinogen Status	Exposure Limits
Copper		Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Steel manufacture, chemicals	A3	Mexico: TWA 0.15 mg/m ³

	A2	Mexico: TWA 0.002 mg/m ³ Mexico: TWA 0.2 mg/m ³ Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³
Aluminum		Mexico: TWA= 10 mg/m ³
Lithium manganese oxide (LiMn2O4)		Mexico: TWA 0.2 mg/m ³
Cobalt lithium manganese nickel oxide		Mexico: TWA 0.2 mg/m ³
Nickel		Mexico: TWA 1 mg/m ³

A2 - Suspected Human Carcinogen
 A3 - Confirmed Animal Carcinogen
 Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class
 Non-controlled

16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 0	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 0	Flammability 0	Physical Hazard 0	

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 21-Sep-2016
Revision Date 21-Sep-2016
Revision Note No information available

Disclaimer
 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet