

MEDIUM

-	
DESCRIPTION	Patented PVC tight fibered cotton composite corner tape that is 2 1/4" wide, .013" thick and
(Speed,	comes in 100' rolls.
Perfection and	Strait-Flex Medium and Medium with Holes have recess running the length of tape, which
Longevity)	makes folding quick and is adjustable to any angle. Material is very stable with temperature
	changes and is flexible while maintaining it's rigidity when wet.
ADVANTAGES	• Strait-Flex creates a fast, perfect intricate off angles and inside 90° corners. Straightens
	small framing irregularities.
	Forms easily to all angles and corners
	• Will not shrink, blister, tear, sag or wrinkle.
	Water resistant and rustproof.
	• Saves 25-50% on installation time.
	 Material can be second coated immediately.
	• Solid rolls ensure no waste or damage in transit or in rough site conditions.
	• Does not require fasteners, stapling, or any special tools.
	• Resists common cracking problems as encountered when using paper tapes.
	• Requires very light fill coat to finish product. Medium with holes promotes quicker
	drying time and easy detection of voids or air pockets behind tape.
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure,
	built on a permanent foundation using recommended application techniques, we warrant that
	these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex
	International Inc for complete details.
DIRECTIONS	Cut Strait-Flex to desired length. Fold in half at center crease, and adjust to desired
	angle.
	Apply using a liberal coat of all-purpose compound with joint knife. Use tile setting
	compounds in wet areas.
	Press Strait-Flex into wet compound. Adjust if necessary to create straight line and
	wipe down with joint knife. Immediately apply light skim coat and let dry.
	Apply final coat, let dry and sand.
STORAGE	Store in dry place protected from moisture
Submittal Approvals:	
Loh Momos	

Job Name:

Contractor:

Date: