MODERN FORMS SMART FANS





PRODUCT DESCRIPTION

As its name suggests, Hydra is all about water. Like all of our smart fans, it's wet-rated for outdoor use so you can maintain the continuity of your décor inside and out. Even with an impressive 120" blade sweep, this epically scaled smart fan moves a massive amount of air without consuming much energy, thanks to a powerful DC motor that runs up to 70% more efficient than AC motors. Control it all with our exclusive Modern Forms app. Available in 80 inches, 96 inches and 120 inches.

SPECIFICATIONS

Construction: Aluminum

Blade: 14° Pitch, 120" sweep, extruded aluminum

Downrod: 1" O.D. x 6"H included **Mounting Slope:** Up to 30°

Lead Wire: 80"

Hanging Weight: 46 lbs **Total Power:** 67.5W

Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 23.5W Dimming: Integrated Color Temperature: 3000K Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 compliant

ESTIMATED AIR PERFORMANCE

Airflow: 13300 cubic ft per minute on high

Power: 44 watts on high

Airflow Efficiency: 302 cubic ft per minute per watt

Revolutions Per Minute: 40 RPMs on high/28 RPMs on average

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens		Housing	Blade	
FR-W1805- 120L	2041	1013	BZ TT	Bronze Titanium Silver	Bronze Titanium Silver	

Example: FR-W1805-120L-BZ

*Results may vary based on application and surroundings.







OPTIONAL ACCESSORIES

Wi-Fi Touch Panel Wall Control	F-WC	WT White BK Black WT White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan. Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod Couplers	XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Sil BZ Bronze CFI Carbon Fiber** DW Dark Walnut GB Gloss Black GH Graphite GW Gloss White MB Matte Black	
Sloped Ceiling Kit	XF-SCK	MW Matte White OB Oil Rubbed Bro SS Stainless Steel TT Titanium Silver	

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW NOTE:** Recommended maximum downrod length of 72" with 80" lead wire.

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13′	12′	11′	10′	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

^{**}Carbon Fiber downrods available in 12", 18", 24" and 36"