## Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

(a) Product identifier	
Product name:	Rechargeable Li-Polymer Battery
(b) Other means of ident	ification
Product description:	Model: 98-10001
	Nominal Voltage: 3.7V
	Ampere-hour: 5.2Ah
	Typical Capacity: 5200mAh
	Weight: 100g
	Dimension: 69.0mm×59.0mm×18.1mm (L×W×T)
(c) Recommended use of	the chemical and restrictions on use
Recommended use:	LITHIUM ION BATTERIES.
Restriction on use:	No information available.
(d) Details of the supplie	r of the product
Company name	HUIZHOU JUHEYUAN SCIENCE & TECHNOLOGY CO., LTD.
Address:	A02, Jingyang Science and Technology Park, No. 4 Donghua South Road, Dongjiang
	Industrial Park, Zhongkai High-tech District, Huizhou City, Guangdong Province, P. F
	China
E-mail:	529972681@qq.com
Telephone:	+86-75584516700
(e) Emergency phone nui	nber
+86-13418477980	

#### 2. Hazard(s) identification

#### (a) Classification of the chemical

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Skin sensitization	Category 1
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Danger

(b) GHS Label elements, including precautionary statements

#### **Emergency Overview** Signal word **Hazard Statements** Harmful if swallowed Causes severe skin burns and eye damage May cause an allergic skin reaction

Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

Causes serious eye damage

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

case of rupture: the above hazards exist.

#### **Precautionary Statements – Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

#### **Precautionary Statements – Response**

Specific measures (see .? on this label)

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician.

if you feel unwell, Rinse mouth. Don't induce vomiting

Precautionary Statements – Storage: Store locked up

**Precautionary Statements – Disposal:** Dispose of contents/container to an approved waste disposal plant **Hazards not otherwise classified (HNOC):** Not applicable

(c) Other information

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

Very toxic to aquatic life with long lasting effects; Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. *(d) Interactions with Other Chemicals* No information available.

#### 3. Composition/information on ingredients

Chemical name	CAS No.	Concentration%
Lithium Cobalt Oxide (CoLiO2)	12190-79-3	37.7
Graphite	7782-42-5	11.2
Phosphate(1-), hexafluoro-, lithium	21324-40-3	14.3
Ethylene carbonate	96-49-1	3.5
Dimethyl carbonate	616-38-6	2.5
Aluminum	7429-90-5	10.8
Copper	7440-50-8	10.8
Polyethylene	9002-88-4	2.7
Polypropylene	9003-07-0	2.9
Polyvinylidene fluoride	24937-79-9	3.6

#### 4. First-aid measures

#### (a) Description of first aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to
	do. Continue rinsing. Seek immediate medical attention/advice.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required. May cause an allergic skin reaction.
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other
	proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider:	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

#### (b) Most important symptoms/effects, acute and delayed

Most important Itching, Coughing and/ or wheezing. Burning sensation. symptoms and

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

#### effects:

#### (c) Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

#### 5. Fire-fighting measures

#### (a) Extinguishing media

Suitable extinguishing media:	Use foam, dry powder or dry sand, CO <sub>2</sub> as appropriate.
Unsuitable extinguishing media:	No information available.

#### (b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO<sub>2</sub>, Metal oxides, Irritating fumes

#### (c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

#### 6. Accidental release measures

#### (a) Personal precautions, protective equipment and emergency procedures

Personal Precautions	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other Information (b) Environmental Precautions	Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.
(c) Methods and materials for conta	inment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

#### 7. Handling and storage

(a) Precautions for safe handling

Version: 1.0/EN	
Product name: Rechargeable Li-Polymer Battery	

Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

Handling	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.	
(b) Conditions for safe storage	e, including any incompatibilities	
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep out of the reach of children. Store away from other materials.	
Incompatible Products	Acids. Bases. Oxidizing agent.	

#### 8. Exposure controls/personal protection

#### (a) Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	TWA: 0.02 mg/m³		
Graphite	TWA: 2 mg/m3 respirable	TWA: 15 mg/m3 total dust	IDLH: 1250 mg/m3
7782-42-5	fraction all forms except	synthetic	TWA: 2.5 mg/m3 respirable
	graphite fibers	TWA: 5 mg/m3 respirable fraction synthetic	dust
		(vacated) TWA: 2.5 mg/m3	
		respirable dust natural	
		(vacated) TWA: 10 mg/m3	
		total dust synthetic	
		(vacated) TWA: 5 mg/m3	
		respirable fraction synthetic	
		TWA: 15 mppcf natural	
Phosphate(1-), hexafluoro-, lithium	TWA: 2.5 mg/m3 F	TWA: 2.5 mg/m3 F	
21324-40-3		TWA: 2.5 mg/m3 dust	
		(vacated) TWA: 2.5 mg/m3	
Copper	TWA: 0.2 mg/m3 fume	TWA: 0.1 mg/m3 fume	IDLH: 100 mg/m3 dust, fume
7440-50-8	TWA: 1 mg/m3 Cu dust and	TWA: 1 mg/m3 dust and mist	and mist
	mist	(vacated) TWA: 0.1 mg/m3 Cu	TWA: 1 mg/m3 dust and mist
		dust, fume, mist	TWA: 0.1 mg/m3 fume
Aluminum	TWA: 1 mg/m3 respirable	TWA: 15 mg/m3 total dust	TWA: 10 mg/m3 total dust
7429-90-5	fraction	TWA: 5 mg/m3 respirable	TWA: 5 mg/m3 respirable
		fraction	dust
		(vacated) TWA: 15 mg/m3 total dust	
		(vacated) TWA: 5 mg/m3	
		respirable fraction (vacated)	
		TWA: 5 mg/m3 Al Aluminum	
ACCILL TINK American Conference		Illumination Thursday Id Lineit V	L]

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Va

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

#### (b) Appropriate engineering controls

Engineering Measures Showers

Version: 1.0/EN
Product name: Rechargeable Li-Polymer Battery

#### Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

#### Eyewash stations Ventilation systems

#### (c) Individual protection measures, such as personal protective equipment

Eye/Face Protection	None required for consumer use. If there is a risk of contact:. Tight sealing safety goggles. Face protection shield.
Skin and Body Protection	None required for consumer use. If there is a risk of contact:. Wear protective gloves and protective clothing.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.

#### 9. Physical and chemical properties

(a) Appearance	Solid
(b) Odor	Odorless
(c) Odor threshold	Not available.
(d) pH	Not available.
(e) Melting point/freezing point	Not available.
(f) Initial boiling point and boiling range	Not available.
(g) Flash point	Not applicable.
(h) Evaporation rate	Not applicable.
(i) Flammability	Non flammable.
(j) Upper/lower flammability or explosive limits	Not available.
(k) Vapor pressure	Not applicable.
(I) Vapor density	Not available.
(m) Relative density	Not available.
(n) Solubility(ies)	Insoluble in water.
(o) Partition coefficient: n-octanol/water	Not available.
(p) Auto-ignition temperature	Not available.
(q) Decomposition temperature	Not available.
(r) Viscosity	Not available.

#### **10. Stability and reactivity**

#### (a) Reactivity

Stable under recommended storage and handling conditions.

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

#### (b) Chemical stability

Stable under recommended storage conditions.

#### (c) Possibility of hazardous reactions

None under normal processing.

#### (d) Conditions to avoid

Exposure to air or moisture over prolonged periods.

#### (e) Incompatible materials

Strong oxidizer, strong acid.

#### (f) Hazardous decomposition products

Carbon oxides.

#### **11.** Toxicological information

(a) Information on the likely routes of exposure						
Product Information	Product does not present an acute toxicity hazard based on known or					
	supplied information.					
	In case of rupture:					
Inhalation:	Specific test data for the substance or mixture is not available. Corrosive by					
	inhalation. (based on components). Inhalation of corrosive fumes/gases					
	may cause coughing, choking, headache, dizziness, and weakness for					
	several hours. Pulmonary edema may occur with tightness in the chest,					
	shortness of breath, bluish skin, decreased blood pressure, and increased					
	heart rate. Inhaled corrosive substances can lead to a toxic edema of the					
	lungs. Pulmonary edema can be fatal. May cause irritation of respiratory					
	tract.					
Ingestion:	Specific test data for the substance or mixture is not available. Causes					
	burns. (based on components). Ingestion causes burns of the upper					
	digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood					
	pressure may decrease. Brownish or yellowish stains may be seen around					
	the mouth. Swelling of the throat may cause shortness of breath and					
	choking. May cause lung damage if swallowed. May be fatal if swallowed					
	and enters airways. Ingestion may cause irritation to mucous membranes.					
	Ingestion may cause gastrointestinal irritation, nausea, vomiting and					
	diarrhea. May be harmful if swallowed.					
Skin contact:	Specific test data for the substance or mixture is not available. Corrosive.					
	, (based on components). Causes burns. May be absorbed through the skin					
	in harmful amounts. Harmful in contact with skin.					
Eye contact:	Specific test data for the substance or mixture is not available. Causes					
	burns. (based on components). Corrosive to the eyes and may cause severe					
	damage including blindness. Causes serious eye damage. May cause					

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

irreversible damage to eyes.

#### **Component Information**

Symptoms

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Graphite > 10000 mg/kg (Rat)				
7782-42-5				
Aluminum	> 15900 mg/kg bw(rat)		> 0.888 mg/L/4 h(rat)	
7429-90-5	> 13900 Hig/kg bw(lat)		> 0.888 mg/ L/4 m(rat)	
Copper	> 2500 mg/kg bw(rat)	> 2000 mg/kg bw(rat)	=1.03 mg/L/4 h(rat)	
7440-50-8			-1.05 mg/ c/4 m(rat)	

#### (b) Information on toxicological characteristics

Erythema (skin redness). Burning. May cause blindness. Coughing and/ or
wheezing. Itching. Rashes. Hives.

#### (C) Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization		May cause sensitization of susceptible person, May cause sensitization by skin contact. May cause sensitization by inhalation.				
Mutagenic Effects			No information available.			
Carcinogenicity			The table below indicates whether each agency has listed any ingredient as			
		a c	arcinogen.			
Chemical Name	ACGIH		IARC	NTP	OSHA	
			a an			

Chemical Name	ACGIH	IARC	NIP	USHA
Lithium Cobalt Oxide	A3	Group 2B		Х
(CoLiO2)				
12190-79-3				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

#### OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present **Reproductive Toxicity** No information available STOT - single exposure No information available Causes damage to organs through prolonged or repeated exposure. Based STOT - repeated exposure on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE). Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects. Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Target Organ Effects Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Lungs. No information available. Aspiration Hazard

#### 12. Ecological information

#### (a) Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity	to	Daphnia	Magna
			Microorganisms		(Water Flea)	
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus			48h EC50: = 0.	03 mg/L
	subcapitata)	carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)				

#### (b) Persistence and Degradability

No information available.

#### (c) Bioaccumulative potential

No information available.

#### (d) Other adverse effects

No information available.

#### 13. Disposal considerations

(a) Waste treatment metho	ds				
Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulation CFR 261). This material could become a hazardous waste if it is mixed with or other comes in contact with a hazardous waste, if chemical additions are made to this mat or if the material is processed or otherwise altered. Consult 40 CFR 261 to deter whether the altered material is a hazardous waste. Consult the appropriate s regional, or local regulations for additional requirements.					
Contaminated Packaging	Dispose of contents/containe	rs in accordance with local regulations			
California Hazardous Waste	141				
Codes	Codes				
This product contains one or	This product contains one or more substances that are listed with the State of California as a hazardous waste.				
Chemic	al Name	California Hazardous Waste			

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	<u>-</u> .
12190-79-3	Тохіс

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

#### Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

Copper 7440-50-8	Тохіс
Aluminum 7429-90-5	Ignitable powder

#### 14. Transport information

Note:	The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary
	Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule) Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with
	equipment", or "Lithium batteries contained in equipment" may not be classified as
	"Dangerous Goods" when shipped in accordance with "special provision A45 of
	IATA-DGR" or "special provision 188 of IMO-IMDG Code"
UN number	3480&3481
DOT	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
IMDG/IMO	Not regulated
Hazard Class	N/A
EmS-No.	F-A, S-I
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

#### **15. Regulatory information**

#### (a) Safety, health and environmental regulations specific for the product in question

	USA	EU	Japan	Korea	China	Canada
CAS No.	TSCA	EINECS	ENCS	ECL	IECSC	DSL
12190-79-3	Listed	Listed	Listed	Listed	Listed	Listed
7782-42-5	Listed	Listed	Not listed	Listed	Listed	Listed
21324-40-3	Not listed	Listed	Listed	Listed	Listed	Not listed

#### Version: 1.0/EN Product name: Rechargeable Li-Polymer Battery

#### Revision date: 19-Mar-2019 Printing date: 19-Mar-2019

96-49-1	Listed	Listed	Listed	Listed	Listed	Listed
616-38-6	Not listed	Listed	Listed	Listed	Listed	Not listed
7429-90-5	Not listed	Listed	Listed	Listed	Listed	Not listed
7440-50-8	Listed	Not listed	Listed	Listed	Listed	Listed
9002-88-4	Listed	Listed	Listed	Listed	Listed	Listed
9003-07-0	Listed	Listed	Not listed	Listed	Listed	Listed
24937-79-9	Listed	Listed	Listed	Listed	Listed	Not listed

#### 16. Other information, including date of preparation or last revision

#### (a) Preparation and revision information

Date of previous revision: Not applicable.Date of this revision: 19-Mar-2019Revision summary: The first New SDS

#### (b) Abbreviations and acronyms

TSCA:	Toxic Substances Control Act, The American chemical inventory.
DSL	Domestic Substances List
EINECS:	European Inventory of Existing Commercial chemical Substances
ENCS	Japanese Existing and New Chemical Substances
ECL:	Existing Chemicals List, the Korean chemical inventory.
IECSC:	Inventory of existing chemical substances in China.

#### (c) Disclaimer

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

----- End of the SDS ------