



SDS

SAFETY DATA SHEET

Prepared For : FULLYMAX BATTERY CO.,LTD
Room 02&03, Block B, Dongjiang Industrial Zone, Shuikou Sub-District
Office, HuiCheng District, Huizhou City, Guangdong Province,
P.R.China

Prepared By : Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd
Road, Bao'an District, Shenzhen, P.R.C. (518101)

Issue Date : Jan. 30, 2018
Report Number : STRD1801110S

Written by: Sean Zeng

Approved by: Davis yang



Section 1-Chemical Product and Company Identification

Product: Rechargeable Lithium ion Polymer Battery

Common name: Rechargeable Lithium ion Polymer Battery

Model: GB1-1100mAh-3.8V

Rating of battery: 3.8V, 1100mAh, 4.18Wh

Trademark: /

Weight:26.5g

Shape and Physical Dimension (mm): $\Phi 67.7*26.2*9.7$ mm

Manufacture: FULLYMAX BATTERY CO.,LTD

Address: Room 02&03, Block B, Dongjiang Industrial Zone, Shuikou Sub-District Office, HuiCheng District,
Huizhou City, Guangdong Province, P.R.China

Telephone number of the supplier: +86-0752-2322549

Fax No: +86-0752-2322221

Emergency Telephone: +86-2750-2322283

Post Code: 516000

E-mail address: marketing@fullymax.com

Section 2- Hazards Identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and Workplace Hazardous Materials Information System (WHMIS) 2015. This product is an article which is a sealed battery and as such does not require an MSDS/SDS per the OSHA hazard communication standard and WHMIS 2015 Supplier Requirements, unless ruptured. The hazards indicated are for a ruptured battery:

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure) Category	Category 1
Flammable liquid and vapor	Category 3

(b) GHS Label elements, including precautionary statements

Emergency Overview

Signal word**Hazard Statements**

Causes skin irritation

Causes serious eye damage

May cause cancer

Suspected of damaging fertility or unborn exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance Blue

Physical State Solid

Odor Odorless

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Immediately call a POISON CENTER or doctor/physician

Skin



IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

No information available.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

(c) Hazards not otherwise classified (HNOC)

No information available.

(d) Unknown Toxicity

10% of the mixture consists of ingredient(s) of unknown toxicity.

(e) Other information

No information available.

(f) Interactions with Other Chemicals

No information available.

Section 3- Composition/Information on Ingredient

Common Chemical Name	Concentration (%)	CAS Number	EC No.
Aluminium Foil	5.9	7429-90-5	231-072-3
Lithium cobaltate	36	12190-79-3	235-362-0
Polyvinylidene fluoride	2	24937-79-9	---
Copper Foil	6	7440-50-8	231-159-6
Graphite	24	7782-42-5	231-955-3
Nickel	1.9	7440-02-0	231-111-4
Polypropylene	0.7	9003-07-0	---
Phosphate(1-), hexafluoro-, lithium	7	21324-40-3	244-334-7
Ethylene carbonate	3	96-49-1	202-510-0
Dimethyl carbonate	3	616-38-6	210-478-4
Propylene carbonate	1	108-32-7	203-572-1
Ethyl methyl carbonate	3	623-53-0	---
polyethylene	3	9002-88-4	200-815-3



Conductive Carbon	3	7440-44-0	231-153-3
Nylon	0.5	32131-17-2	---

Section 4- First Aid Measures

The battery is not hazard with eye and skin contact under normal circumstance. In case of the enclosure is damaged, the battery can not be used and touched. It is safety except that the battery is damaged by fire or rupture. The leakage of internal hazardous substance and formation of hazardous substance would occur, take the following measures if contact with the battery.

Skin touch: If there is any unwell reaction, wash thoroughly with soap & water, flush with plenty of water. If irritation persists, seek medical advice.

Eyes touch: Rinse immediately with plenty of water for at least 15 mins. Contact a doctor if symptoms persist.

Inhalation: Remove from exposure site to fresh air. Keep at rest. Obtain medical attention.

Ingestion: Rinse mouth out with water. Seek medical advice immediately.

Self-protection of the first aider: Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Information for doctor

Most important sumpoms and effects, both acute and delayed: no further relavant information available.

Indication of any immediate dedical attention and special treatment needed:No further relevant information availabel

Section 5- Fire Fighting Measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO2 as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO2, Metal oxides, Irritating fumes.

(c) Special protective equipment and precautions for fire-fighters



Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed wit sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and Storage

Precautions for safe handling:

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery



casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries Use recommended charging time and current.

Storage conditions:

If the batteries are subject to storage for such a long term as more than 3 months, it is recommended to recharge the Rechargeable Lithium ion Polymer Battery periodically.

Storage Temperature:

Short period less than 3 months: -20~+45°C, 75%RH Max

Long period more than 3 months: +5°C~+35°C,75%RH Max

Do not storage Rechargeable Lithium ion Polymer Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children. Do not expose Li-Polymer battery to heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials.

Section 8- Exposure Controls, Personal Protection

(a)Control parameters

Exposure Guidelines

Table with 4 columns: Chemical Name, ACGIH TLV, OSHA PEL, NIOSH IDLH. Rows include Lithium Cobalt Oxide, Aluminum, Copper, and Phosphate(1-), hexafluoro-, lithium.

ACGIH TLV: American Conference of Governmental Industrial Hygienists -Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines: Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992) See section 15 for national exposure control parameters

(b) Appropriate engineering controls

Engineering Measures: 1.Showers 2.Eyewash stations 3.Ventilation systems

(c) Individual protection measures, such as personal protective equipment

Respiratory protection: No necessary under normal use. In case electrolyte leakage from the battery, protect hand with chemical resistant rubber gloves. If battery is burning, leave the area immediately. In abuse, use NIOSH approved acid gas filter mask or self-contained breathing apparatus.

Hand protection: None under normal use. In case of spilling, use PVC, neoprene or nitrile gloves of 15mils (0.015 inch) or thicker.

Eye/Face protection: None required under normal conditions. Use approved chemical work safety goggles or face shield, if handling a leaking or rupture battery.

Skin and body protection: No necessary under normal use. Use rubber apron and protective working in case of handling of a rupture battery.

Other protective equipment: Chemical resistance clothing is recommended along with eye wash station and safety shower should be available. Work hygienic practices: Use good chemical hygiene practice. Wash hands after use and before drinking, eating or smoking. Wash hands thoroughly after cleaning-up component spill caused by leaking battery. No eating, drinking, or smoking in battery storage area. Launder contaminated cloth before reuse.

Section 9- Physical and Chemical Properties

Information on basic physical and chemical properties

General information

Form: Solid **Colour:** Black **Odour:** Odourless **Odour threshold:** Not available

pH-value: Not available



Change in condition

Melting point/Melting range: Not available

Boiling point/Boiling range: Not available

Freezing point: Not available

Flash point: Not available

Flammability (solid, gaseous): Not available

Auto-ignition temperature: Not available

Decomposition temperature: Not available

Self-igniting: Product is not selfigniting.

Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

Explosion limits

Lower: Not available

Upper: Not available

Oxidizing properties: Not available

Vapour pressure: Not available

Density: Not available

Relative density: Not available

Vapour density: Not available

Evaporation rate: Not available

Solubility in / Miscibility with water: Not available

Partition coefficient (n-octanol/water): Not available.

Viscosity

Dynamic: Not available.

Kinematic: Not available

Other information: No further relevant information available.

Section 10- Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies controlled release of pressure without ignition.

(d) Conditions to avoid

Do not subject Rechargeable Lithium ion Polymer Battery to mechanical shock. Keep away from open flames, high temperature.

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

Section 11- Toxicological information

(a) Information on the likely routes of exposure

Inhalation: Inhalation of a large number of vapors or fumes released due to heat may cause respiratory.

Ingestion: Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

Skin contact: Contact with battery electrolyte may cause burns and skin irritation.

Eye contact: Contact with battery electrolyte may cause burns. Eye damage is possible.

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity: No data available.

Skin corrosion/irritation: The liquid in the battery irritates.

Serious eye damage/irritation: The liquid in the battery irritates.

Respiratory sensitization: The liquid in the battery may cause sensitization to some person.

Skin sensitization: The liquid in the battery may cause sensitization to some person.

Carcinogenicity: Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).



Germ Cell Mutagenicity: No data available.

Reproductive Toxicity: No data available.

STOT-Single Exposure: No data available.

STOT-Repeated Exposure: No data available.

Aspiration Hazard: No data available.

Sensitization: No data available.

Mutagenic Effects: No data available.

Carcinogenicity: No data available.

Reproductive Toxicity: No data available.

Chronic Toxicity: No data available.

Target Organ Effects: No data available.

Aspiration Hazard: No data available.

Section 12- Ecological Information


Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behaviour in environmental systems:** No further relevant information available
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information**
- **General notes:**
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

packed with equipment

Transport hazard class(es)

· ADR, IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.

Label 9

Packing group

· ADR, IMDG, IATA II

· **Marine pollutant:** No

Special precautions for user: Warning: Miscellaneous dangerous substances and articles.

· **Danger code (Kemler):** -

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.

· **UN "Model Regulation":** UN3480 or UN3481, Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment, 9, II

Section 15- Regulatory information

OSHA hazard communication standard (29 CFR 1910.1200)

_____ Hazardous Non-hazardous
 Workplace Hazardous Materials Information System (WHMIS) 2015

_____ Hazardous Non-hazardous

Section 16- Other Information

Note: The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This



Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd
Road, Bao'an District, Shenzhen, P.R.C. (518101)

Safety Data Sheet

information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.