# Vulkem 116 Table of Contents

	1
Vulkem 116 Buff SDS - EN	1
Vulkem 116 Dark Bronze SDS - EN	20
Vulkem 116 Limestone SDS - EN	38



# **SAFETY DATA SHEET**

## 1. Identification

Material name: VULKEM 116 LV BUFF 30 CTG/CS Material: 426707L 323

## Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

#### Contact person: Telephone: Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

#### Hazard Classification

Health Hazards	
Acute toxicity (Inhalation - vapor)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Unknown toxicity - Health	
Acute toxicity, oral	34.11 %
Acute toxicity, dermal	41.28 %
Acute toxicity, inhalation, vapor	97.33 % 99.01 %
Acute toxicity, inhalation, dust or mist	99.01 %
Environmental Hazards	
Acute hazards to the aquatic environment	Category 2
Unknown toxicity - Environment	
Acute hazards to the aquatic environment	78.43 %
Chronic hazards to the aquatic environment	100 %

## Label Elements

Hazard Symbol:



(!	
Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

# 3. Composition/information on ingredients

## Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Titanium dioxide	13463-67-7	3 - 7%
**	**	3 - 7%
Heavy aromatic naphtha	64742-94-5	1 - 5%
Aromatic petroleum distillates	64742-95-6	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5%



4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.5 - 1.5%			
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%			
1,3,5-Trimethylbenzene	108-67-8	0.1 - 1%			
Aluminum oxide	1344-28-1	0.1 - 1%			
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%			
* All concentrations are perce	nt by weight unless i	ngredient is a gas. Gas concentrations are in percent by volume.			
Trade secret information:		fic chemical identity and/or percentage of composition has been s a trade secret.			
4. First-aid measures					
Ingestion:	Call a POI	SON CENTER/doctor//if you feel unwell. Rinse mouth.			
Inhalation:		sician or poison control center immediately. If breathing stops, tificial respiration. Move to fresh air. If breathing is difficult, give			
Skin Contact:	clean cont shoes and	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.			
Eye contact:	water. If e	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.			
Most important symptoms/ef	fects, acute an	d delayed			
Symptoms:	May cause	May cause skin and eye irritation.			
Indication of immediate medic	cal attention and	d special treatment needed			
Treatment:	Symptoms	s may be delayed.			
5. Fire-fighting measures					
General Fire Hazards:	No unusua	No unusual fire or explosion hazards noted.			
Suitable (and unsuitable	e) extinguishi	ing media			
Suitable extinguishing media:	Use fire-ex	xtinguishing media appropriate for surrounding materials.			
Unsuitable extinguishing media:	Do not use	Do not use water jet as an extinguisher, as this will spread the fire.			
Specific hazards arising fron the chemical:	n During fire	During fire, gases hazardous to health may be formed.			

Special protective equipment and precautions for firefighters



Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
6. Accidental release measures	3
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.
Conditions for safe storage, including any incompatibilities:	Store locked up.

# 8. Exposure controls/personal protection

## **Control Parameters**

# Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)



				(02 2006)
**	TWA		10 mg/m3	US. ACGIH Threshold Limit Values
			. eg,e	(03 2015)
	TWA		3 mg/m3	US. ACGIH Threshold Limit Values
	1004		- <b>J</b>	(03 2015)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air
			0	Contaminants (29 CFR 1910.1000)
				(02 2006)
	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air
			0	Contaminants (29 CFR 1910.1000)
				(02 2006)
	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR
			U	1910.1000) (2000)
	TWA		50 millions	US. OSHA Table Z-3 (29 CFR
			of particles	1910.1000) (2000)
			, per cubic	
			foot of air	
	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR
	IVVA		<b>9</b> , <b>0</b>	1910.1000) (2000)
	TWA		15 millions	US. OSHA Table Z-3 (29 CFR
	IVVA		of particles	1910.1000) (2000)
			per cubic	,
			foot of air	
Heavy aromatic	TWA		200	US. ACGIH Threshold Limit Values
naphtha - Non-aerosol.			mg/m3	(03 2014)
- as total hydrocarbon			<u>g</u> ,e	
vapor				
Heavy aromatic	PEL	100 ppm	400	US. OSHA Table Z-1 Limits for Air
naphtha		i co ppin	mg/m3	Contaminants (29 CFR 1910.1000)
napitila			mg/me	(02 2006)
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values
1,2,1 1111001131001120110		20 pp.m		(2011)
4,4'-Methylene	TWA	0.005 ppm		US. ACGIH Threshold Limit Values
bis(phenylisocyanate)		0.000 ppm		(2011)
ble(prioriyiloooyanato)	C allin a	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air
	Ceiling	0.02 pp	0.2 mg/mo	Contaminants (29 CFR 1910.1000)
				(02 2006)
Polymethylene	TWA	0.005 ppm		US. ACGIH Threshold Limit Values
polyphenyl isocyanate		erece bb		(2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air
	Cenng	•••• PP···	s	Contaminants (29 CFR 1910.1000)
				(02 2006)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values
.,_,_				(2011)
Aluminum oxide -	TWA		1 mg/m3	US. ACGIH Threshold Limit Values
Respirable fraction.			g/110	(2011)
2-p	PEL	1	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			5 mg/m0	Contaminants (29 CFR 1910.1000)
				(02 2006)
Aluminum oxide - Total	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.			10 mg/m0	Contaminants (29 CFR 1910.1000)
				(02 2006)
Crystalline Silica	TWA		0.025	US. ACGIH Threshold Limit Values
(Quartz)/ Silica Sand -			mg/m3	(2011)
Respirable fraction.			mg/m3	
Crystalline Silica	TWA		2.4	US. OSHA Table Z-3 (29 CFR
Crystannie Onica		I	2.4	5/19



(Quartz)/ Silica Sand -		millions of	1910.1000) (2000)
Respirable.		particles	
		per cubic	
		foot of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR
		_	1910.1000) (2000)
Crystalline Silica	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -		_	1910.1000) (2000)
Total dust.			

Chemical name	type	Exposure Limit Values	Source
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Respirable particles.	TWAEV	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Inhalable	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWAEV	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Heavy aromatic naphtha	TWA	400 ppm	1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
4,4'-Methylene bis(phenylisocyanate)	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene bis(phenylisocyanate)	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97,



				as amended) (07 2007)
Polymethylene	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of
polyphenyl isocyanate				Exposure to Biological or Chemical
	CEV	0.02 ppm		Agents) (11 2010) Canada. Ontario OELs. (Control of
	CEV	0.02 ppm		Exposure to Biological or Chemical
				Agents) (11 2010)
Polymethylene	TWA	0.005 ppm	0.051	Canada. Quebec OELs. (Ministry of
polyphenyl isocyanate			mg/m3	Labor - Regulation Respecting the
				Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs.
				(Occupational Exposure Limits for
				Chemical Substances, Occupational
				Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of
				Exposure to Biological or Chemical
				Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123	Canada. Quebec OELs. (Ministry of
			mg/m3	Labor - Regulation Respecting the Quality of the Work Environment) (12
				2008)
Crystalline Silica	TWA		0.025	Canada. British Columbia OELs.
(Quartz)/ Silica Sand -			mg/m3	(Occupational Exposure Limits for
Respirable fraction.				Chemical Substances, Occupational
				Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica	TWAEV		0.10	Canada. Ontario OELs. (Control of
(Quartz)/ Silica Sand -			mg/m3	Exposure to Biological or Chemical
Respirable.	<b>T</b> 14/4			Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand -	TWA	(	).1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the
(Quanz)/ Silica Sand - Respirable dust.				Quality of the Work Environment) (12
				2008)

#### Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

#### Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.	
Eye/face protection:	Wear goggles/face shield.	
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.	
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.	



Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

Appearance		
Physical state:	solid	
Form:	Paste	
Color:	Tan	
Odor:	Mild	
Odor threshold:	No data available.	
pH:	No data available.	
Melting point/freezing point:	No data available.	
Initial boiling point and boiling range:	No data available.	
Flash Point:	99 °C 210 °F(ISO 3679 (seta closed))	
Evaporation rate:	Slower than n-Butyl Acetate	
Flammability (solid, gas):	No	
Upper/lower limit on flammability or explosive limits		
Flammability limit - upper (%):	No data available.	
Flammability limit - lower (%):	No data available.	
Explosive limit - upper (%):	No data available.	
Explosive limit - lower (%):	No data available.	
Vapor pressure:	No data available.	
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.	
Relative density:	1.16	
Solubility(ies)		
Solubility in water:	Insoluble in water	
Solubility (other):	No data available.	
Partition coefficient (n-octanol/water):	No data available.	
Auto-ignition temperature:	No data available.	
Decomposition temperature:	No data available.	
Viscosity:	No data available.	
40 Ctability and reactivity		

# 10. Stability and reactivity

## **Reactivity:**

No data available.



Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	No data available.	
Conditions to avoid:	Avoid heat or contamination.	
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	

11. Toxicological information

## Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

## Information on toxicological effects

## Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 11,594.99 mg/kg	
Dermal Product:	ATEmix: 17,370.93 mg/kg	
Inhalation Product:	ATEmix: 17.97 mg/l	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
<b>Specified substance(s):</b> Titanium dioxide	in vivo (Rabbit): Experimental result, Supporting study	



	Heavy aromatic naphtha	in vivo (Rabbit): Experimental result, Key study	
	Aromatic petroleum distillates	in vivo (Rabbit): Experimental result, Key study	
	1,2,4-Trimethylbenzene	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study	
	4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit): Read-across based on grouping of substances (category approach), Key study	
	1,3,5-Trimethylbenzene	in vivo (Rabbit): Experimental result, Key study	
	Aluminum oxide	in vivo (Rabbit): Experimental result, Key study	
Sorious	Serious Eye Damage/Eye Irritation Product: No data available.		
Р			
Р	roduct: pecified substance(s):	No data available.	
Р	roduct: pecified substance(s): Titanium dioxide Heavy aromatic	No data available. in vivo (Rabbit, 24 hrs): Not irritating	
Р	roduct: pecified substance(s): Titanium dioxide Heavy aromatic naphtha Aromatic petroleum	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating	
Р	<b>pecified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating	
Р	<b>Product:</b> <b>pecified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates 1,2,4-Trimethylbenzene 4,4'-Methylene	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 30 min): Not irritating	
P S Respira	<b>Product:</b> <b>Specified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates 1,2,4-Trimethylbenzene 4,4'-Methylene bis(phenylisocyanate)	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 30 min): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 hrs): Not irritating	



#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica Overall evaluation: Carcinogenic to humans. (Quartz)/ Silica Sand

US. National Toxicology Program (NTP) Report on Carcinogens: Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

#### Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicit Product:	t <b>y - Single Exposure</b> No data available.
Specific Target Organ Toxicit Product:	ty - Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

### 12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:

No data available.

Specified substance(s):



1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality	
1,3,5-Trimethylbenzene	LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): 1,2,4-Trimethylbenzene	LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality	
1,3,5-Trimethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication	
Chronic hazards to the aquation	c environment:	
Fish Product:	No data available.	
<b>Specified substance(s):</b> Titanium dioxide	ED 0 (Phoxinus phoxinus, 30 d): >= 1,000 mg/l Experimental result, Supporting study LC 10 (Oncorhynchus mykiss, 28 d): 0.981 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 28 d): 7.31 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 1 (Oncorhynchus mykiss, 28 d): 0.191 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 1 (Oncorhynchus mykiss, 28 d): 0.191 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l Experimental result, Supporting study	
Heavy aromatic naphtha	NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/I QSAR QSAR, Key study	
Aromatic petroleum distillates	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study NOAEL (Pimephales promelas, 14 d): 2.6 mg/l Experimental result, Supporting study NOAEL (Daphnia magna, 21 d): 2.6 mg/l Other, Key study	
Aluminum oxide	NOAEL (Pimephales promelas, 28 d): 4.7 mg/l Experimental result, Weight of Evidence study IC 25 (Pimephales promelas, 7 d): 11.59 mg/l Experimental result, Weight of Evidence study LOAEL (Salvelinus fontinalis, 60 d): 0.35 mg/l Experimental result, Weight of Evidence study NOAEL (Pimephales promelas, 7 d): 0.4 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study NOAEL (Pimephales promelas, 7 d): >= 0.831 mg/l Experimental result, Weight of Evidence study	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	



Persistence and Degradability			
Biodegradation Product:	No data available.		
BOD/COD Ratio Product:	No data available.		
Bioaccumulative Potential Bioconcentration Factor (B Product:	<b>CF)</b> No data available.		
Partition Coefficient n-octa Product:	<b>nol / water (log Kow)</b> No data available.		
Mobility in Soil:	No data available.		
Other Adverse Effects:	Toxic to aquatic organisms.		
13. Disposal considerations			
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.		
Contaminated Packaging:	No data available.		
14. Transport information			
TDG:			
Not Regulated			

## CFR / DOT:

Not Regulated

## IMDG:

Not Regulated

# 15. Regulatory information

## **US Federal Regulations**



#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity	
P-chlorobenzotrifluoride	De minimis concentration:	1.0% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

## CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Barium sulfate	1000 lbs.
Chromium	5000 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

## SARA 302 Extremely Hazardous Substance

<u>Reportable</u>
quantity
100 lbs.
100 lbs.

Threshold Planning Quantity 500 lbs. 100 lbs.

## SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Diisodecyl phthalate	
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Barium sulfate	1000 lbs.
Chromium	5000 lbs.



## SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Calcium Carbonate	500 lbs
(Limestone)	
Titanium dioxide	500 lbs
Polyethylene	500 lbs
Heavy aromatic naphtha	500 lbs
Aromatic petroleum	500 lbs
distillates	
1,2,4-Trimethylbenzene	500 lbs
4,4'-Methylene	500 lbs
bis(phenylisocyanate)	
Polymethylene polyphenyl	500 lbs
isocyanate	
1,3,5-Trimethylbenzene	500 lbs
Aluminum oxide	500 lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	<b>Reportable quantity</b>	
Xylene	100 lbs.	

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical	Identity
Chemical	identity

#### **Reportable quantity**

2,4-Toluene diisocyanate	10000 lbs
Toluene-2,6-Diisocyanate	10000 lbs

#### **US State Regulations**

#### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Calcium Carbonate (Limestone) Titanium dioxide P-chlorobenzotrifluoride Heavy aromatic naphtha Crystalline Silica (Quartz)/ Silica Sand



One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or

One or more components in this product are

One or more components in this product are

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

not listed on or exempt from the Inventory.

not listed on or exempt from the Inventory.

exempt from the Inventory.

#### US. Massachusetts RTK - Substance List

#### Chemical Identity

Calcium Carbonate (Limestone) Titanium dioxide Heavy aromatic naphtha Crystalline Silica (Quartz)/ Silica Sand 2,4-Toluene diisocyanate Toluene-2,6-Diisocyanate Chromium

#### US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Diisodecyl phthalate Calcium Carbonate (Limestone) Titanium dioxide Heavy aromatic naphtha

#### **US. Rhode Island RTK**

<u>Chemical Identity</u> Disodecyl phthalate

#### **Other Regulations:**

Regulatory VOC (less water	47 g/l
and exempt solvent):	
VOC Method 310:	2.61 %

#### **Inventory Status:**

Australia AICS:

Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):

Canada NDSL Inventory:

Philippines PICCS:



US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	03/28/2016
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



# **SAFETY DATA SHEET**

## 1. Identification

Material name: VULKEM 116 LV DARK BRONZE 30 CTG/CS Material: 426721L 323

### Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

#### Contact person: Telephone: Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

#### Hazard Classification

Hea	alth Hazards	
	Acute toxicity (Inhalation - vapor)	Category 4
I	Respiratory sensitizer	Category 1
;	Skin sensitizer	Category 1
(	Germ Cell Mutagenicity	Category 1B
(	Carcinogenicity	Category 1A
Unknow	wn toxicity - Health	
	Acute toxicity, oral	37.49 %
	Acute toxicity, dermal	41.27 %
	Acute toxicity, inhalation, vapor	97.34 %
1	Acute toxicity, inhalation, dust or mist	99.16 %
Environm	ental Hazards	
	Acute hazards to the aquatic environment	Category 2
Unknow	wn toxicity - Environment	
	Acute hazards to the aquatic environment	78.56 %
	Chronic hazards to the aquatic environment	100 %

## Label Elements

#### Hazard Symbol:



(!	
Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

# 3. Composition/information on ingredients

## Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	15 - 40%
Polyethylene	9002-88-4	3 - 7%
Heavy aromatic naphtha	64742-94-5	1 - 5%
Aromatic petroleum distillates	64742-95-6	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5%
4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.5 - 1.5%



Carbon Black	1333-86-4	0.1 - 1%
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%
1,3,5-Trimethylbenzene	108-67-8	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
Most important symptoms/effect	ts, acute and delayed
Symptoms:	May cause skin and eye irritation.
Indication of immediate medical a	attention and special treatment needed
Treatment:	Symptoms may be delayed.
5. Fire-fighting measures	
5. Fire-fighting measures General Fire Hazards:	No unusual fire or explosion hazards noted.
General Fire Hazards:	
General Fire Hazards: Suitable (and unsuitable) e Suitable extinguishing	xtinguishing media
General Fire Hazards: Suitable (and unsuitable) e Suitable extinguishing media: Unsuitable extinguishing	xtinguishing media Use fire-extinguishing media appropriate for surrounding materials.
General Fire Hazards: Suitable (and unsuitable) e Suitable extinguishing media: Unsuitable extinguishing media: Specific hazards arising from	xtinguishing media Use fire-extinguishing media appropriate for surrounding materials. Do not use water jet as an extinguisher, as this will spread the fire. During fire, gases hazardous to health may be formed.



Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
6. Accidental release measure	s	
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.	
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.	
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so.	
7. Handling and storage		
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.	
Conditions for safe storage, including any incompatibilities:	Store locked up.	

# 8. Exposure controls/personal protection

## **Control Parameters**

#### **Occupational Exposure Limits**

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyethylene - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
Polyethylene - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
Polyethylene - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



Polyethylene - Total	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.			10 mg/mo	Contaminants (29 CFR 1910.1000)
				(02 2006)
	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		50 millions	US. OSHA Table Z-3 (29 CFR
			of particles	1910.1000) (2000)
			per cubic	
			foot of air	
Polyethylene - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		15 millions	US. OSHA Table Z-3 (29 CFR
			of particles	1910.1000) (2000)
			per cubic	
Lleour cromotio	TWA		foot of air	US. ACGIH Threshold Limit Values
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TVVA		200 mg/m3	(03 2014)
Heavy aromatic	PEL	100 ppm	400	US. OSHA Table Z-1 Limits for Air
naphtha			mg/m3	Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL		3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air
	Cening	0.0 <b>–</b> pp	og,o	Contaminants (29 CFR 1910.1000) (02 2006)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA		0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Iron oxide - Respirable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (2011)



Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyethylene - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Respirable particles.	TWAEV		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Inhalable	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWAEV		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Heavy aromatic naphtha	TWA	400 ppm	1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
4,4'-Methylene	CEILING	0.01 ppm		Canada. British Columbia OELs.



bis(phenylisocyanate)				(Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene bis(phenylisocyanate)	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV		3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polymethylene polyphenyl isocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of



				Exposure to Biological or Chemical Agents) (11 2010)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0	.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

## Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.



**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

## 9. Physical and chemical properties

#### Appearance Physical state: solid Form: Paste Color: Dark brown Odor: Mild **Odor threshold:** No data available. pH: No data available. Melting point/freezing point: No data available. Initial boiling point and boiling range: No data available. Flash Point: 99 °C 210 °F(ISO 3679 (seta closed)) **Evaporation rate:** Slower than n-Butyl Acetate Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits No data available. Flammability limit - upper (%): Flammability limit - lower (%): No data available. No data available. Explosive limit - upper (%): No data available. Explosive limit - lower (%): Vapor pressure: No data available. Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers. **Relative density:** 1.16 Solubility(ies) Solubility in water: Insoluble in water Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. No data available. Auto-ignition temperature: **Decomposition temperature:** No data available. Viscosity: No data available.

## 10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.



Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		
Information on likely routes of exp Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.	
Eye contact:	Eye contact is possible and should be avoided.	
Information on toxicological effe	cts	
Acute toxicity (list all possible	routes of exposure)	
Oral Product:	ATEmix: 16,365.91 mg/kg	
Dermal Product:	ATEmix: 17,474.23 mg/kg	
Inhalation Product:	ATEmix: 17.97 mg/l	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
<b>Specified substance(s):</b> Heavy aromatic naphtha	in vivo (Rabbit): Experimental result, Key study	
Aromatic petroleum distillates	in vivo (Rabbit): Experimental result, Key study	
1,2,4-Trimethylbenzene	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study	



	4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit): Read-across based on grouping of substances (category approach), Key study
	Carbon Black	in vivo (Rabbit): Experimental result, Key study
	1,3,5-Trimethylbenzene	in vivo (Rabbit): Experimental result, Key study
	Iron oxide	in vivo (Rabbit): Experimental result, Weight of Evidence study
	s Eye Damage/Eye Irritati roduct:	<b>on</b> No data available.
S	<b>pecified substance(s):</b> Heavy aromatic naphtha	in vivo (Rabbit, 24 - 72 hrs): Not irritating
	Aromatic petroleum distillates	in vivo (Rabbit, 24 - 72 hrs): Not irritating
	1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
	4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit, 24 - 72 hrs): Not irritating
	Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
	Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating
Respiratory or Skin Sensitizatior Product:		<ul> <li>n May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.</li> </ul>
	ogenicity roduct:	No data available.
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:		
	Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
	Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.
US. Nat		m <b>(NTP) Report on Carcinogens:</b> Known To Be Human Carcinogen.



# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

No data available.

#### Germ Cell Mutagenicity

In vitro	
Product:	No data available.

- In vivo Product: No data available.
- Reproductive toxicity Product: No data available.
- Specific Target Organ Toxicity<br/>Product:Single Exposure<br/>No data available.Specific Target Organ Toxicity<br/>Product:Repeated Exposure<br/>No data available.Aspiration Hazard<br/>Product:No data available.
- Other effects:

## **12. Ecological information**

## Ecotoxicity:

#### Acute hazards to the aquatic environment:

No data available.
LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality
No data available.
LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality
EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication

Chronic hazards to the aquatic environment:



Fish Product:	No data available.
Specified substance(s): Heavy aromatic naphtha	NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR QSAR, Key study
Aromatic petroleum distillates	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study NOAEL (Pimephales promelas, 14 d): 2.6 mg/l Experimental result, Supporting study NOAEL (Daphnia magna, 21 d): 2.6 mg/l Other, Key study
Carbon Black	NOAEL (Salmo sp., 30 d): 17 mg/l QSAR QSAR, Key study
Iron oxide	LOAEL (Salvelinus fontinalis, 35 Weeks): 12 mg/l Experimental result, Supporting study NOAEL (Salvelinus fontinalis, 35 Weeks): 6 mg/l Experimental result, Supporting study NOAEL (Pimephales promelas, 33 d): 1 mg/l Experimental result, Supporting study LOAEL (Pimephales promelas, 12 Months): 1.5 mg/l Experimental result, Supporting study NOAEL (Pimephales promelas, 33 d): 1.6 mg/l Experimental result, Supporting study
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative Potential Bioconcentration Factor (BC Product:	CF) No data available.
Partition Coefficient n-octan Product:	<b>Iol / water (log Kow)</b> No data available.
Mobility in Soil:	No data available.



Other Adverse Effects:	Toxic to aquatic organisms.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	

#### TDG:

Not Regulated

## CFR / DOT:

Not Regulated

## IMDG:

Not Regulated

# 15. Regulatory information

### **US Federal Regulations**

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity	
P-chlorobenzotrifluoride	De minimis concentration:	1.0% One-Time Export Notification only.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

## CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Barium sulfate	1000 lbs.
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Chromium	5000 lbs.



#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

## SARA 302 Extremely Hazardous Substance

	Reportable		
Chemical Identity	quantity	Threshold Planning Quantity	
2,4-Toluene diisocyanate	100 lbs.	500 lbs.	
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.	

## SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Diisodecyl phthalate	
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Barium sulfate	1000 lbs.
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Chromium	5000 lbs.

## SARA 311/312 Hazardous Chemical

2,4-Toluene diisocyanate500lbsToluene-2,6-Diisocyanate100lbsCalcium Carbonate500 lbs(Limestone)500 lbsPolyethylene500 lbsHeavy aromatic naphtha500 lbsAromatic petroleum500 lbsdistillates1,2,4-Trimethylbenzene1,2,4-Trimethylbenzene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate1,3,5-Trimethylbenzene500 lbs500 lbsSilica Sand500 lbs	Chemical Identity	Threshold Planning Quantity
Calcium Carbonate500 lbs(Limestone)FolyethylenePolyethylene500 lbsHeavy aromatic naphtha500 lbsAromatic petroleum500 lbsdistillates1,2,4-Trimethylbenzene1,2,4-Trimethylbenzene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate500 lbs1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbs	2,4-Toluene diisocyanate	500lbs
(Limestone)Polyethylene500 lbsHeavy aromatic naphtha500 lbsAromatic petroleum500 lbsdistillates1,2,4-Trimethylbenzene1,2,4-Trimethylbenzene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate1,3,5-Trimethylbenzene1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbs	Toluene-2,6-Diisocyanate	100lbs
Polyethylene500 lbsHeavy aromatic naphtha500 lbsAromatic petroleum500 lbsdistillates1,2,4-Trimethylbenzene1,2,4-Trimethylbenzene500 lbs4,4'-Methylene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate500 lbs1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	Calcium Carbonate	500 lbs
Heavy aromatic naphtha500 lbsAromatic petroleum500 lbsdistillates500 lbs1,2,4-Trimethylbenzene500 lbs4,4'-Methylene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate500 lbs1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	(Limestone)	
Aromatic petroleum500 lbsdistillates1,2,4-Trimethylbenzene500 lbs1,2,4-Trimethylbenzene500 lbs4,4'-Methylene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate500 lbs1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	Polyethylene	500 lbs
distillates 1,2,4-Trimethylbenzene 500 lbs 4,4'-Methylene 500 lbs bis(phenylisocyanate) Carbon Black 500 lbs Polymethylene polyphenyl 500 lbs isocyanate 1,3,5-Trimethylbenzene 500 lbs Crystalline Silica (Quartz)/ 500 lbs Silica Sand	Heavy aromatic naphtha	500 lbs
1,2,4-Trimethylbenzene500 lbs4,4'-Methylene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	Aromatic petroleum	500 lbs
4,4'-Methylene500 lbsbis(phenylisocyanate)500 lbsCarbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate1,3,5-Trimethylbenzene1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	distillates	
bis(phenylisocyanate) Carbon Black 500 lbs Polymethylene polyphenyl 500 lbs isocyanate 1,3,5-Trimethylbenzene 500 lbs Crystalline Silica (Quartz)/ 500 lbs Silica Sand		500 lbs
Carbon Black500 lbsPolymethylene polyphenyl500 lbsisocyanate1,3,5-TrimethylbenzeneCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	4,4'-Methylene	500 lbs
Polymethylene polyphenyl500 lbsisocyanate1,3,5-Trimethylbenzene500 lbsCrystalline Silica (Quartz)/500 lbsSilica Sand500 lbs	bis(phenylisocyanate)	
isocyanate 1,3,5-Trimethylbenzene 500 lbs Crystalline Silica (Quartz)/ 500 lbs Silica Sand	Carbon Black	500 lbs
1,3,5-Trimethylbenzene 500 lbs Crystalline Silica (Quartz)/ 500 lbs Silica Sand	Polymethylene polyphenyl	500 lbs
Crystalline Silica (Quartz)/ 500 lbs Silica Sand	isocyanate	
Silica Sand		500 lbs
	Crystalline Silica (Quartz)/	500 lbs
Iron ovido E00 lbo	Silica Sand	
TUTI UXIDE 300 IDS	Iron oxide	500 lbs

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	100 lbs.



### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

#### Chemical Identity

2,4-Toluene diisocyanate Toluene-2,6-Diisocyanate

Reportable quantity 10000 lbs 10000 lbs

#### **US State Regulations**

#### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Calcium Carbonate (Limestone) P-chlorobenzotrifluoride Heavy aromatic naphtha Carbon Black Crystalline Silica (Quartz)/ Silica Sand

#### **US. Massachusetts RTK - Substance List**

#### **Chemical Identity**

Calcium Carbonate (Limestone) Heavy aromatic naphtha Crystalline Silica (Quartz)/ Silica Sand 2,4-Toluene diisocyanate Toluene-2,6-Diisocyanate Chromium

# US. Pennsylvania RTK - Hazardous Substances

#### **Chemical Identity**

Diisodecyl phthalate Calcium Carbonate (Limestone) Heavy aromatic naphtha

#### **US. Rhode Island RTK**

<u>Chemical Identity</u> Diisodecyl phthalate

#### **Other Regulations:**

48 g/l	
2.59 %	
	One or more components in this product are not listed on or exempt from the Inventory.
	All components in this product are listed on or exempt from the Inventory.
	One or more components in this product are not listed on or exempt from the Inventory.
	0



Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	03/28/2016
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



# **SAFETY DATA SHEET**

### 1. Identification

Material name: VULKEM 116 LV LIMESTONE 30 CTG/CS Material: 426805L 323

### Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

#### Contact person: Telephone: Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### Hazard Classification

Health Hazards	
Acute toxicity (Inhalation - vapor)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Unknown toxicity - Health	
Acute toxicity, oral	34.56 %
Acute toxicity, dermal	41.76 %
Acute toxicity, inhalation, vapor Acute toxicity, inhalation, dust or mist	97.23 % 99.05 %
Environmental Hazards	
Acute hazards to the aquatic environment	Category 2
Unknown toxicity - Environment	
Acute hazards to the aquatic environment	77.82 %
Chronic hazards to the aquatic environment	100 %

# Label Elements

#### Hazard Symbol:



(!	
Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

# 3. Composition/information on ingredients

# Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Titanium dioxide	13463-67-7	3 - 7%
**	**	3 - 7%
Heavy aromatic naphtha	64742-94-5	1 - 5%
Aromatic petroleum distillates	64742-95-6	1 - 5%
1,2,4-Trimethylbenzene	95-63-6	1 - 5%



4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.5 - 1.5%		
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%		
1,3,5-Trimethylbenzene	108-67-8	0.1 - 1%		
Aluminum oxide	1344-28-1	0.1 - 1%		
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%		
* All concentrations are perce	nt by weight unless i	ingredient is a gas. Gas concentrations are in percent by volume.		
Trade secret information:		fic chemical identity and/or percentage of composition has been is a trade secret.		
4. First-aid measures				
Ingestion:	Call a POI	ISON CENTER/doctor//if you feel unwell. Rinse mouth.		
Inhalation:		sician or poison control center immediately. If breathing stops, tificial respiration. Move to fresh air. If breathing is difficult, give		
Skin Contact:	clean cont shoes and	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.		
Eye contact:	water. If e	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.		
Most important symptoms/e	fects, acute an	d delayed		
Symptoms:	May cause	e skin and eye irritation.		
Indication of immediate medio	cal attention an	d special treatment needed		
Treatment:	Symptoms	s may be delayed.		
5. Fire-fighting measures				
General Fire Hazards:	No unusua	No unusual fire or explosion hazards noted.		
Suitable (and unsuitable) extinguishing media				
Suitable extinguishing media:	Use fire-e	xtinguishing media appropriate for surrounding materials.		
Unsuitable extinguishing media:	Do not use	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical:	n During fire	During fire, gases hazardous to health may be formed.		

Special protective equipment and precautions for firefighters



Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
6. Accidental release measures	3
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.
Conditions for safe storage, including any incompatibilities:	Store locked up.

# 8. Exposure controls/personal protection

# **Control Parameters**

# Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)



				(02 2006)
**	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	TWA		3 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Heavy aromatic naphtha	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Aluminum oxide - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica	TWA		2.4	US. OSHA Table Z-3 (29 CFR 5/19



(Quartz)/ Silica Sand -		millions of	1910.1000) (2000)
Respirable.		particles	
		per cubic	
		foot of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR
		_	1910.1000) (2000)
Crystalline Silica	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -		_	1910.1000) (2000)
Total dust.			

Chemical name	type	Exposure Limit Values	Source
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Polyethylene - Respirable particles.	TWAEV	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Inhalable	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWAEV	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Heavy aromatic naphtha	TWA	400 ppm	1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
4,4'-Methylene bis(phenylisocyanate)	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene bis(phenylisocyanate)	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97,



				as amended) (07 2007)
Polymethylene polyphenyl isocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)
1,3,5-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	(	).1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

### Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

#### Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.	
Eye/face protection:	Wear goggles/face shield.	
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.	
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.	



Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

Appearance	
Physical state:	solid
Form:	Paste
Color:	Pale gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	99 °C 210 °F(ISO 3679 (seta closed))
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explose	ive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.16
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
40. Ctability and recetivity	

# 10. Stability and reactivity

# **Reactivity:**

No data available.



Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

# Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

# Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 11,336.4 mg/kg
Dermal Product:	ATEmix: 15,351.01 mg/kg
Inhalation Product:	ATEmix: 17.97 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Specified substance(s): Titanium dioxide	in vivo (Rabbit): Experimental result, Supporting study



	Heavy aromatic naphtha	in vivo (Rabbit): Experimental result, Key study
	Aromatic petroleum distillates	in vivo (Rabbit): Experimental result, Key study
	1,2,4-Trimethylbenzene	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study
	4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit): Read-across based on grouping of substances (category approach), Key study
	1,3,5-Trimethylbenzene	in vivo (Rabbit): Experimental result, Key study
	Aluminum oxide	in vivo (Rabbit): Experimental result, Key study
Seriou	s Eye Damage/Eye Irritati	on
	roduct:	No data available.
Р		
Р	roduct: pecified substance(s):	No data available.
Р	roduct: pecified substance(s): Titanium dioxide Heavy aromatic	No data available. in vivo (Rabbit, 24 hrs): Not irritating
Р	roduct: pecified substance(s): Titanium dioxide Heavy aromatic naphtha Aromatic petroleum	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating
Р	<b>pecified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating
Р	<b>Product:</b> <b>pecified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates 1,2,4-Trimethylbenzene 4,4'-Methylene	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 30 min): Not irritating
PS	<b>Product:</b> <b>Specified substance(s):</b> Titanium dioxide Heavy aromatic naphtha Aromatic petroleum distillates 1,2,4-Trimethylbenzene 4,4'-Methylene bis(phenylisocyanate)	No data available. in vivo (Rabbit, 24 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 30 min): Not irritating in vivo (Rabbit, 24 - 72 hrs): Not irritating in vivo (Rabbit, 24 hrs): Not irritating



#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica Overall evaluation: Carcinogenic to humans. (Quartz)/ Silica Sand

US. National Toxicology Program (NTP) Report on Carcinogens: Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

#### Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicit Product:	<b>y - Single Exposure</b> No data available.
Specific Target Organ Toxicit Product:	y - Repeated Exposure No data available.
Aspiration Hazard	
Product:	No data available.

# 12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:

No data available.

Specified substance(s):



1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
1,3,5-Trimethylbenzene	LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality
Aquatic Invertebrates Product:	No data available.
<b>Specified substance(s):</b> 1,2,4-Trimethylbenzene	LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality
1,3,5-Trimethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication
Chronic hazards to the aquation	c environment:
Fish Product:	No data available.
<b>Specified substance(s):</b> Titanium dioxide	ED 0 (Phoxinus phoxinus, 30 d): >= 1,000 mg/l Experimental result, Supporting study LC 10 (Oncorhynchus mykiss, 28 d): 0.981 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 28 d): 7.31 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 1 (Oncorhynchus mykiss, 28 d): 0.191 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 1 (Oncorhynchus mykiss, 28 d): 0.191 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l Experimental result, Supporting study
Heavy aromatic naphtha	NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/I QSAR QSAR, Key study
Aromatic petroleum distillates	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study NOAEL (Pimephales promelas, 14 d): 2.6 mg/l Experimental result, Supporting study NOAEL (Daphnia magna, 21 d): 2.6 mg/l Other, Key study
Aluminum oxide	NOAEL (Pimephales promelas, 28 d): 4.7 mg/l Experimental result, Weight of Evidence study IC 25 (Pimephales promelas, 7 d): 11.59 mg/l Experimental result, Weight of Evidence study LOAEL (Salvelinus fontinalis, 60 d): 0.35 mg/l Experimental result, Weight of Evidence study NOAEL (Pimephales promelas, 7 d): 0.4 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study NOAEL (Pimephales promelas, 7 d): >= 0.831 mg/l Experimental result, Weight of Evidence study
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.



Persistence and Degradability	
Biodegradation Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative Potential Bioconcentration Factor (Be Product:	CF) No data available.
Partition Coefficient n-octar Product:	<b>nol / water (log Kow)</b> No data available.
Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	
TDG:	
Not Regulated	

# CFR / DOT:

Not Regulated

# IMDG:

Not Regulated

# 15. Regulatory information

# **US Federal Regulations**



#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity	
P-chlorobenzotrifluoride	De minimis concentration:	1.0% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

# CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Chromium	5000 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

# SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>		
Chemical Identity	quantity	Threshold Planning Quantity	
2,4-Toluene diisocyanate	100 lbs.	500 lbs.	
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.	

## SARA 304 Emergency Release Notification Chemical Identity Reportable quantity

Chemical Identity	Reportable qu
Diisodecyl phthalate	
4,4'-Methylene	5000 lbs.
bis(phenylisocyanate)	
Polymethylene	5000 lbs.
polyphenyl isocyanate	
Cumene	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Xylene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Ethylbenzene	1000 lbs.
Chromium	5000 lbs.



# SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Calcium Carbonate	500 lbs
(Limestone)	
Titanium dioxide	500 lbs
Polyethylene	500 lbs
Heavy aromatic naphtha	500 lbs
Aromatic petroleum	500 lbs
distillates	
1,2,4-Trimethylbenzene	500 lbs
4,4'-Methylene	500 lbs
bis(phenylisocyanate)	
Polymethylene polyphenyl	500 lbs
isocyanate	
1,3,5-Trimethylbenzene	500 lbs
Aluminum oxide	500 lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	

#### SARA 313 (TRI Reporting) Chemical Identity

1,2,4-Trimethylbenzene

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	100 lbs.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity	Reportable quantity
2,4-Toluene diisocyanate	10000 lbs
Toluene-2,6-Diisocyanate	10000 lbs

#### **US State Regulations**

### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Calcium Carbonate (Limestone) Titanium dioxide P-chlorobenzotrifluoride Heavy aromatic naphtha 1,2,4-Trimethylbenzene Crystalline Silica (Quartz)/ Silica Sand



### US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone) Titanium dioxide Heavy aromatic naphtha 1,2,4-Trimethylbenzene Crystalline Silica (Quartz)/ Silica Sand 2,4-Toluene diisocyanate Toluene-2,6-Diisocyanate

#### US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Diisodecyl phthalate Calcium Carbonate (Limestone) Titanium dioxide Heavy aromatic naphtha 1,2,4-Trimethylbenzene

### US. Rhode Island RTK

#### Chemical Identity

Diisodecyl phthalate 1,2,4-Trimethylbenzene

#### **Other Regulations:**

Regulatory VOC (less water	49 g/l
and exempt solvent):	
VOC Method 310:	2.70 %

#### **Inventory Status:**

Australia AICS:

Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):

Canada NDSL Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.



Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	03/29/2016
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.