



**DIF® QUICK  
WALLPAPER STRIPPER**

**DESCRIPTION AND USES**

Zinsser® DIF® Quick Wallpaper Stripper is a biodegradable, non-toxic and non-staining wallpaper stripper. It is fast-penetrating, removing the most difficult adhesives in 1-2 minutes. It will effectively remove 75 square feet of wallpaper per 32 ounce spray and 300 square feet per gallon.

**PRODUCTS**

SKU	Description
249055	32 Fluid Ounces
249054	1-Gallon

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

**PRODUCT APPLICATION (cont.)**

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying

**APPLICATION**

Spray on or sponge apply DIF Quick Wallpaper Stripper. Do not use a fine mist sprayer. Protect adjacent areas from overspray. Wait 2-5 minutes for DIF to penetrate and loosen wallpaper. Scrape off loose wallpaper with the Paper Scraper™ being careful not to gouge the wall. If the top layer does not peel off easily, score (10 holes per square inch) with Paper Tiger™ and apply more DIF Quick Wallpaper Stripper. Allow DIF to penetrate for 2-5 additional minutes. Repeat the removal process and re-apply the stripper if necessary. To remove residual adhesive, re-apply the DIF solution, wait 2-5 minutes and scrape or sponge off. Rinse with clean water. **KEEP OUT OF REACH OF CHILDREN.**

**SPILLAGE**

Open container carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly.

**CLEAN-UP**

Clean up tools and equipment with soap and water.

**TECHNICAL DATA****DIF® QUICK WALLPAPER STRIPPER****PHYSICAL PROPERTIES**

Physical Properties		QUICK WALLPAPER STRIPPER
Composition		Propylene Glycol, Water
Weight	Per Gallon	8.3 lbs.
	Per Liter	1.00 kg
Volatile Organic Compounds		109 g/l
Practical Coverage		Varies with porosity of wallpaper
Shelf Life		5 years
Flash Point		200°F (93°C)
Caution!		Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. <b>KEEP OUT OF REACH OF CHILDREN.</b>
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.