



The Power Gas 10L unit by Marey is the perfect solution for 2 points of use. This unit provides 30°F increase at 3.0 GPM.

No electrical connection required. Can last a lifetime, keeping up to 87% efficiency level.

Please consult temperature map for suggested points-of-use according to geographical area.

- The Power Gas 10L unit is recommended for 2 simultaneous points of use.
- **Endless hot water on demand:** Activated by water pressure (5 to 140 PSI) from the moment the faucet is opened.
- **Tankless water heaters save energy** because they use up to 80% less energy than conventional tank water heaters. As a result, they are cost effective and environmentally friendly.
- **No need for pre-heating:** instant hot water on demand.
- **Must be installed by a professional plumber or electrician** to ensure safety and quality.



NATURAL GAS



GALLONS PER MINUTE



MULTIPLE POINTS OF USE



MAX. DISTANCE TO POINT OF USE



ACTVATES BY WATER FLOW



NO ELECTRICITY NEEDED



MAX. ENERGY SAVING



EASY TO USE



COMPACT SAVES SPACE



INSTANT HOT WATER



SAVE UP TO 80% IN ENERGY



5 YEARS WARRANTY

TECHNICAL SPECIFICATIONS	GA10NG
Hot Water Outlet per Minute	10 LPM / 3.1 GPM
Heat Loss	79,228 BTU/h
Min. Pressure Water Activation	10 PSI
Maximum Flow Rate	3.1 GPM
Dimensions	13.6" x 23.6" x 6.9"
Weight	21 lbs
Gas Type	Natural Gas
Safe Operating Pressure	5 PSI - 140 PSI
Related Gas Pressure (PSI)	0.25 up to 0.5 PSI
Exhaust Discharge Mode	Flue Duct Type
Aplicable Water Pressure	3.6 - 145.0 PSI / 0.25 - 10 bar
Ignition	2D Cell Battery Powered (not included)
Energy Efficiency	54% - 87%

\* No need for electricity, starts with pulse ignition, powered by 2 D cell batteries.

GPM	Temp. Increase per GPM	
	HIGHEST	LOWEST
0.5	-	68°F
1.0	100°F	34°F
1.5	67°F	23°F
2.0	50°F	17°F
2.5	40°F	14°F
3.1	30°F	9°F

\*Highest gas setting: set Winter/High  
\*Lowest gas setting: set for Summer/Low



# GA10NG

## TANKLESS GAS WATER HEATER