



Dependable. Reliable. Professional.

557 HVAC PRO-GRADE DUCT

UL LISTED TAPE



- Backing:** Printed Polyethylene Coated Cloth
- Adhesive:** Natural Rubber
- Liner:** N/A
- Specifications:** UL 181B-FX Listed
- Colors:** Silver
- Available Size:** 1.89 in x 60.1 yd x 14 mil
(48 mm x 50 m x 355 µm)

Applications

- Tough, heavy-duty closure system intended for use on UL Listed flexible, non-metallic ducts
- Heavy-duty HVAC sealing and repairs
- Sheet metal and duct repair
- Challenging bonding, protecting, bundling, and patching

Features

Benefits

UL 181B-FX Listed	<ul style="list-style-type: none"> • Meets code requirements for sealing flexible air ducts and connections • Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®
Natural Rubber Adhesive	<ul style="list-style-type: none"> • Excellent bond to sheet metal and other surfaces • High strength to withstand duct system pressure • Resistant to moisture and mold
Polyethylene Coated Cloth Backing	<ul style="list-style-type: none"> • High strength and durable • Conformable to wrap ducts for an effective seal • 181B-FX printed for easy inspector identification
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	14 mils	355 µm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	29 lb/in	50.79 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.