

SPEAKMAN® S-1495-AF

Exposed Anti-Scald Balanced Pressure Shower

FEATURES:

- Sentinel Mark II exposed anti-scald balanced pressure Shower.
- Brass lever handle.
- Adjustable temperature limit stop.
- Chrome plated cast brass body.
- Pressure balancing & ceramic temperature regulating cartridge with built-in check valves.
- 1/2 in. NPTF inlets.
- Vandal-resistant standard.
- Exposed anti-scald balanced pressure shower.
- Adjustable stops and supply connections from floor, ceiling or wall.
- 7-1/2 in. center to center.
- Polished chrome plated brass gooseneck with supporting strap.
- S-2252 showerhead with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum

FINISH:



PC

COMPLIANCE:

- Valve meets ASSE 1016 standard and ASME A112.18.1/CSA B125.1 standard.
- Showerheads meet ASME A112.18.1/CSA B125.1 standard.

OPTIONS: Add suffix to model

- Less showerhead -LH
- S-2251 showerhead -1
- S-2253 showerhead -3
- S-2272-E2 showerhead -5

WARRANTY:

- Shower Head: 1 year limited
- Valve: 5 year limited



DIMENSIONS: NOTE: 1. Dimensions shown above are for the installation inclusive of the S-2252 showerhead. Dimensions will vary slightly depending on showerhead choice. 2. Dimensions are subject to change without notice. 3. Unit can also be installed using a ceiling or floor supply.

