QO612L100RBCP

Load center, QO, 1 phase, 6 spaces, 12 circuits, 100A fixed main lugs, NEMA3R, UL, consumer pack





Main

Marketing Trade Name	QO
Product	Load Center
Enclosure type	Weatherproof enclosure
Cover type	Surface cover

Complementary

Complementary		
Tightening torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
Load Center Type	Main lugs	
Line Rated Current	100 A	
Number of spaces	6	
Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	12	
Maximum Number of Tandem Breakers	6	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Electrical Connection	Lugs	
Grounding Bar	Grounding bar (ordered separately)	
Electrical connection	Lugs	
Wiring configuration	3-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded galvannealed steel	
Cover Finish	Baked enamel Gray	
Box number	2R	
Maximum Height	12.64 in (321 mm)	
Maximum Width	8.90 in (226 mm)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL Listed

Ordering and shipping details

Category	01303 - QO MAIN LUG LOAD CENTERS
Discount Schedule	CPQ
GTIN	00047569805097
Nbr. of units in pkg.	1
Package weight(Lbs)	9.55 lb(US) (4.33 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.20 in (13.208 cm)	
Package 1 width	10.20 in (25.908 cm)	
Package 1 Length	14.20 in (36.068 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	80	
Package 2 Weight	818.00 lb(US) (371.038 kg)	
Package 2 Height	33.00 in (83.82 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	[☑] Product Environmental Profile	

Contractual warranty

Warranty	18 months	